

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PENTOIL-(ROST-OFF-BLACK)-500ML
Product code : 0890200500

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricant, Corrosion inhibitors, Detergent

1.3 Details of the supplier of the safety data sheet

Company : WÜRTH IRELAND LTD.
Monaclinoe Ind. Est. Ballysimon
Limerick

Telephone : +353 61 430200

Telefax : +353 61 412428

E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

2.3 Other hazards

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned 01-2119458869-15	Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 50 - < 70
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6 265-156-6 649-466-00-2	Asp. Tox. 1; H304	>= 10 - < 20
Fatty acids, tall-oil, reaction products with polyethylenepolyamines	68910-93-0 272-756-1	Skin Corr. 1C; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8 203-749-3	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400	>= 0.1 - < 0.25
Substances with a workplace exposure limit :			
Carbon dioxide	124-38-9 204-696-9	Press. Gas Liquefied gas; H280	>= 1 - < 10

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

SECTION 4: First aid measures

4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

- Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
- Advice on safe handling : Do not spray on an open flame or other ignition source.

Do not get on skin or clothing.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
- Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
- Recommended storage temperature : < 50 °C

7.3 Specific end use(s)

- Specific use(s) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	OELV - 8 hrs (TWA)	1,000 ppm	IE OEL
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	OELV - 8 hrs (TWA) (inhalable fraction)	5 mg/m ³	IE OEL
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	OELV - 8 hrs (TWA) (inhalable fraction)	5 mg/m ³	IE OEL
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
Propane	74-98-6	OELV - 8 hrs (TWA)	1,000 ppm	IE OEL
Further information	Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants, Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used			
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	2006/15/EC
Further information	Indicative			
		OELV - 8 hrs (TWA)	5,000 ppm 9,000 mg/m ³	IE OEL
Further information	Indicative Occupational Exposure Limit Value			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	Workers	Inhalation	Long-term systemic effects	0.2 mg/m ³
	Workers	Inhalation	Acute systemic effects	18 mg/m ³
	Workers	Inhalation	Long-term local effects	0.01 mg/m ³
	Workers	Inhalation	Acute local effects	18 mg/m ³
	Workers	Skin contact	Long-term systemic effects	10 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	100 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	0.1 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

			effects	
	Consumers	Inhalation	Acute systemic effects	9 mg/m ³
	Consumers	Inhalation	Long-term local effects	5 µg/m ³
	Consumers	Inhalation	Acute local effects	9 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	92 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hydrotreated light naphthenic	Oral (Secondary Poisoning)	9.33 mg/kg food
Distillates (petroleum), hydrotreated heavy paraffinic	Oral (Secondary Poisoning)	9.33 mg/kg food
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	Fresh water sediment	0.43 µg/l
	Marine sediment	0.043 µg/l
	Intermittent use/release	4.3 µg/l
	Sewage treatment plant	13 mg/l

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection

Material : Nitrile rubber
Break through time : ≤ 480 min
Glove thickness : 0.35 mm

Material : Fluorinated rubber
Break through time : ≤ 480 min
Glove thickness : 0.4 mm

Remarks : Choose gloves to protect hands against chemicals depending

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Skin and body protection : Wear the following personal protective equipment: Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Self-contained breathing apparatus
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Propellant : Butane, Propane, Isobutane
- Colour : dark grey
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : Not applicable
- Relative vapour density : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Relative density	:	No data available
Density	:	0.83 g/cm ³ (20 °C)
Solubility(ies)	:	
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg
Acute dermal toxicity : LD50 (Rat): > 3,400 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 1.01 - 1.85 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit
Result: No skin irritation

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Species: Rabbit
Result: Corrosive after 1 to 4 hours of exposure
Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit
Result: No eye irritation

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Result: Irreversible effects on the eye
Remarks: Based on skin corrosivity.

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rabbit
Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Result: negative
Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species: Rat
Application Route: inhalation (vapour)
Exposure time: 105 weeks
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)

Distillates (petroleum), hydrotreated light naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species: Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

NOAEL: 3.9 mg/l
Application Route: inhalation (vapour)
Exposure time: 90 Days
Method: OECD Test Guideline 413

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 Weeks
Method: OECD Test Guideline 410

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Species: Rat
NOAEL: 300 mg/kg
Application Route: Ingestion
Exposure time: 28 Days

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rat
NOAEL: > 0.06 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days
Method: OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated light naphthenic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 - 200 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 5.5 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.76 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: 0.316 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
Exposure time: 4 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.43 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.48 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.638 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.395 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC10 : 24 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.32 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 9.3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.43 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 6.3 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : NOEC : 10 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74.7 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Fatty acids, tall-oil, reaction products with polyethylenepolyamines:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 36 %
Exposure time: 28 d

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 85.2 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Partition coefficient: n- : log Pow: 3.5 - 4.2
octanol/water

Carbon dioxide:

Partition coefficient: n- : log Pow: 0.83
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)
- Waste Code : The following Waste Codes are only suggestions:
- used product
160504, gases in pressure containers (including halons) containing dangerous substances
 - unused product
160504, gases in pressure containers (including halons) containing dangerous substances
 - uncleaned packagings
150110, packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

- ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

- ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN
Environmentally hazardous : no

ADR
Environmentally hazardous : no

RID

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version 1.1 Revision Date: 04.10.2017 SDS Number: 1614923-00002 Date of last issue: 02.05.2017
Date of first issue: 02.05.2017

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 80.19 %

Regulation (EC) No. 648/2004, as amended : 30 % and more: Aromatic hydrocarbons, Aliphatic hydrocarbons

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Press. Gas : Gases under pressure
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
IE OEL : Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2006/15/EC / TWA : Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - EMERGENCY Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PENTOIL-(ROST-OFF-BLACK)-500ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
1.1	04.10.2017	1614923-00002	Date of first issue: 02.05.2017

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1 H222, H229
Aquatic Chronic 3 H412

Classification procedure:

Based on product data or assessment
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN