

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALLROUNDER WIT-VM 250 - 420 ML (comp. A)
Product code : 0903450205

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives
stance/Mixture : Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single ex- H335: May cause respiratory irritation.
posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Precautionary statements : **Prevention:**
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Ethylene dimethacrylate
Methacrylic acid, monoester with propane-1,2-diol

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Quartz	14808-60-7 238-878-4	Carc. 1A; H350i STOT RE 1; H372 (Lungs)	>= 50 - < 70
Ethylene dimethacrylate	97-90-5 202-617-2 607-114-00-5	Skin Sens. 1; H317 STOT SE 3; H335	>= 10 - < 20
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3 254-075-1	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 0,25 - < 1
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 0,25 - < 1

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire- : Exposure to combustion products may be a hazard to health.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

fighting

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapours or spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
- Storage class (TRGS 510) : 11, Combustible Solids
- Recommended storage temperature : 5 - 25 °C

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Quartz	14808-60-7	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
Silicon, amorphous	112945-52-	AGW (Inhalable)	4 mg/m ³	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version
10.6

Revision Date:
29.09.2020

SDS Number:
331907-00007

Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

	5	fraction)	(Silica)	900
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethylene dimethacrylate	Workers	Inhalation	Long-term systemic effects	2,45 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,45 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
Methacrylic acid, monoester with propane-1,2-diol	Workers	Inhalation	Long-term systemic effects	14,7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,8 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
1,1'-(p-tolylimino)dipropan-2-ol	Workers	Inhalation	Long-term systemic effects	2 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,6 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,4 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,3 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	Workers	Inhalation	Long-term systemic effects	17,62 mg/m ³
	Workers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,35 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
--	-----------	-----------	----------------------------	----------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethylene dimethacrylate	Fresh water	0,139 mg/l
	Marine water	0,0139 mg/l
	Intermittent use/release	0,15 mg/l
	Sewage treatment plant	57 mg/l
	Fresh water sediment	1,6 mg/kg
	Marine sediment	0,16 mg/kg
Methacrylic acid, monoester with propane-1,2-diol	Fresh water	0,904 mg/l
	Marine water	0,904 mg/l
	Intermittent use/release	0,972 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	6,28 mg/kg
	Marine sediment	6,28 mg/kg
1,1'-(p-tolylimino)dipropan-2-ol	Fresh water	0,017 mg/l
	Marine water	0,0017 mg/l
	Intermittent use/release	0,17 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	0,0782 mg/kg
	Marine sediment	0,00782 mg/kg
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	Fresh water	0,014 mg/l
	Marine water	0,001 mg/l
	Sewage treatment plant	3 mg/l
	Fresh water sediment	5,29 mg/kg dry weight (d.w.)
	Marine sediment	0,529 mg/kg dry weight (d.w.)
	Soil	1,05 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	83,3 mg/kg food

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

Break through time : > 480 min
Glove thickness : > 0,7 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste
Colour : beige
Odour : characteristic
Odour Threshold : No data available
pH : No data available
Melting point/freezing point : No data available
Initial boiling point and boiling range : No data available
Flash point : Not applicable
Evaporation rate : Not applicable
Flammability (solid, gas) : Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit : No data available
Lower explosion limit / Lower

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

flammability limit

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 1,69 - 1,73 g/cm³ (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Quartz:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Ethylene dimethacrylate:

Acute oral toxicity : LD50 (Rat): 8.300 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Methacrylic acid, monoester with propane-1,2-diol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

1,1'-(p-tolylimino)dipropan-2-ol:

Acute oral toxicity : LD50 (Rat): > 25 - 200 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethylene dimethacrylate:

Species : Rabbit
Result : No skin irritation

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rabbit
Result : No skin irritation

1,1'-(p-tolylimino)dipropan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Ethylene dimethacrylate:

Species : Rabbit
Result : No eye irritation

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

1,1'-(p-tolylimino)dipropan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 7 days

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Ethylene dimethacrylate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Methacrylic acid, monoester with propane-1,2-diol:

Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

1,1'-(p-tolylimino)dipropan-2-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethylene dimethacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Methacrylic acid, monoester with propane-1,2-diol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Components:

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rat
Application Route : Inhalation
Exposure time : 102 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Ethylene dimethacrylate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Methacrylic acid, monoester with propane-1,2-diol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

1,1'-(p-tolylimino)dipropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause respiratory irritation.

Components:

Ethylene dimethacrylate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Quartz:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Ethylene dimethacrylate:

Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Quartz:

Species : Humans
LOAEL : 0,053 mg/m³
Application Route : inhalation (dust/mist/fume)
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Ethylene dimethacrylate:

Species : Rat, male
NOAEL : 100 mg/kg
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 50 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 1,23 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rat
NOAEL : >= 300 mg/kg
Application Route : Ingestion
Exposure time : 49 Days
Method : OECD Test Guideline 422

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rat, male
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 12: Ecological information

12.1 Toxicity

Components:

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility

Chronic aquatic toxicity : No toxicity at the limit of solubility

Ethylene dimethacrylate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 15,95 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44,9 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 17,3 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 6,93 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 570 mg/l
Exposure time: 30 min
Method: ISO 8192

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 5,05 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Methacrylic acid, monoester with propane-1,2-diol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 493 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 143 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 97,2 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): >= 97,2 mg/l

Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1.140 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 45,2 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

1,1'-(p-tolylimino)dipropan-2-ol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 17 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 28,8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 57,8 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 245 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 : > 1.995 mg/l
Exposure time: 30 min

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,55 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,46 mg/l
Exposure time: 48 h
Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 7,49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,56 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,7 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

Ethylene dimethacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71,6 %
Exposure time: 30 d
Method: OECD Test Guideline 301C

Methacrylic acid, monoester with propane-1,2-diol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

1,1'-(p-tolylimino)dipropan-2-ol:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 90,1 %
Exposure time: 60 d
Method: OECD Test Guideline 301B

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Biodegradability : Result: rapidly biodegradable
Biodegradation: 70,73 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Ethylene dimethacrylate:

Partition coefficient: n-octanol/water : log Pow: 2,4

Methacrylic acid, monoester with propane-1,2-diol:

Partition coefficient: n-octanol/water : log Pow: 0,97

1,1'-(p-tolylimino)dipropan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 2,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 1.130 - 1.200
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 4,91
Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

unused product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances
15 01 02, plastic packaging

Acc. Packaging Ordinance properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version 10.6 Revision Date: 29.09.2020 SDS Number: 331907-00007 Date of last issue: 03.08.2020
Date of first issue: 09.04.2015

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %, 0 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H300 : Fatal if swallowed.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H350i : May cause cancer by inhalation.
H361d : Suspected of damaging the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
2004/37/EC / TWA : Long term exposure limit
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ALLROUNDER WIT-VM 250 - 420 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 03.08.2020
10.6	29.09.2020	331907-00007	Date of first issue: 09.04.2015

ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Sens. 1	H317
STOT SE 3	H335

Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN