

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Super Glue 50g
Product code : 0893 090

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives
stance/Mixture : Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Würth UK Ltd
1 Centurion Way
Erith, Kent

Telephone : +44 (0)3300 555 444
Telefax : +44 (0)3300 555 666
E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- H335: May cause respiratory irritation.
posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Hazard statements : H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

Ethyl 2-cyanoacrylate

Additional Labelling

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Ethyl 2-cyanoacrylate	7085-85-0 230-391-5 607-236-00-9 01-2119527766-29	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 90 - <= 100
1,4-Benzenediol	123-31-9 204-617-8 604-005-00-4 01-2119524016-51	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.025 - < 0.1
		M-Factor (Acute	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

		aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
--	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
Eyelid bonding: see a doctor.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2020
6.14	15.12.2020	607779-00007	Date of first issue: 21.12.2009

Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2020
6.14	15.12.2020	607779-00007	Date of first issue: 21.12.2009

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitised individuals should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|---|
| Requirements for storage areas and containers | : | Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. |
|---|---|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethyl 2-cyanoacrylate	7085-85-0	STEL	0.3 ppm 1.5 mg/m ³	GB EH40
1,4-Benzenediol	123-31-9	TWA	0.5 mg/m ³	GB EH40
Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethyl 2-cyanoacrylate	Workers	Inhalation	Long-term systemic effects	9.25 mg/m ³
	Workers	Inhalation	Long-term local effects	9.25 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	9.25 mg/m ³
	Consumers	Inhalation	Long-term local effects	9.25 mg/m ³
1,4-Benzenediol	Workers	Inhalation	Long-term systemic effects	7 mg/m ³
	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Workers	Skin contact	Long-term systemic effects	128 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.74 mg/m ³
	Consumers	Inhalation	Long-term local effects	0.5 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	64 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,4-Benzenediol	Fresh water	0.114 µg/l
	Marine water	0.0114 µg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

	Intermittent use/release	1.34 µg/l
	Sewage treatment plant	0.71 mg/l
	Fresh water sediment	0.00098 mg/kg
	Marine sediment	0.000097 mg/kg
	Soil	0.000129 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to BS EN 166

Hand protection

Material : butyl-rubber
Break through time : 60 min
Glove thickness : > 0.6 mm
Directive : Equipment should conform to BS EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Colour : colourless

Odour : irritating

Odour Threshold : No data available

pH : substance/mixture reacts with water

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : 70 - < 90 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1.05 g/cm³ (20 °C)
Method: DIN 51757

Solubility(ies)
Water solubility : hydrolyses

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : 20 - 40 mPa.s (25 °C)
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Ethyl 2-cyanoacrylate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

1,4-Benzenediol:

Acute oral toxicity : LD50 (Rat): 375 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): 7.8 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Exposure time: 1 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Ethyl 2-cyanoacrylate:

Species : Rabbit
Result : Skin irritation

1,4-Benzenediol:

Species : Rat
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethyl 2-cyanoacrylate:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

1,4-Benzenediol:

Result : Irreversible effects on the eye
Remarks : Based on harmonised classification in EU regulation 1272/2008, Annex VI

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,4-Benzenediol:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Assessment : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethyl 2-cyanoacrylate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

1,4-Benzenediol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: positive

Germ cell mutagenicity- Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Carcinogenicity

Not classified based on available information.

Components:

1,4-Benzenediol:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

1,4-Benzenediol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Application Route: Ingestion
Result: negative

STOT - single exposure

May cause respiratory irritation.

Components:

Ethyl 2-cyanoacrylate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

1,4-Benzenediol:

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,4-Benzenediol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.638 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.061 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.33 mg/l
Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.034 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : IC50 : 71 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Exposure time: 2 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.0029 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

Ethyl 2-cyanoacrylate:

Biodegradability : Remarks: No data available

1,4-Benzenediol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

Ethyl 2-cyanoacrylate:

Partition coefficient: n-octanol/water : Pow: 0.776

1,4-Benzenediol:

Partition coefficient: n-octanol/water : log Pow: 0.59

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2020
6.14	15.12.2020	607779-00007	Date of first issue: 21.12.2009

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

unused product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : UN 3334

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Aviation regulated liquid, n.o.s.
(Ethyl 2-cyanoacrylate)

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

IATA : 9

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version 6.14 Revision Date: 15.12.2020 SDS Number: 607779-00007 Date of last issue: 11.11.2020
Date of first issue: 21.12.2009

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 95 %

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H341 : Suspected of causing genetic defects.
H351 : Suspected of causing cancer.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Muta. : Germ cell mutagenicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Super Glue 50g

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2020
6.14	15.12.2020	607779-00007	Date of first issue: 21.12.2009

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335

Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

Super Glue 50g

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2020
6.14	15.12.2020	607779-00007	Date of first issue: 21.12.2009

GB / EN