

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
 Date of first issue: 05/10/2019

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
 P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
 P332 + P317 If skin irritation occurs: Get medical help.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P391 Collect spillage.

Storage:

P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
 Date of first issue: 05/10/2019

Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 50
Liquified petroleum gas (LPG)	68476-85-7	>= 30 - < 50
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based	72623-87-1	>= 30 - < 50

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
 Vapours may form explosive mixtures with air.
 Exposure to combustion products may be a hazard to health.
 If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
 Date of first issue: 05/10/2019

- only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
 Avoid breathing spray.
 Do not swallow.
 Avoid contact with eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.
 Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable liquids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Explosives
- Recommended storage temperature : < 40 °C
- Storage period : 12 Months

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based	72623-87-1	TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
Date of first issue: 05/10/2019

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber

Glove thickness : 3 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Liquefied petroleum gas (LPG)

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
Date of first issue: 05/10/2019

Colour : amber

Odour : perfumed

Odour Threshold : No data available

pH : 7

Melting point/freezing point : No data available

Initial boiling point and boiling range : 30 °C

Flash point : 38 - 42 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 0.80 - 0.82 g/cm³ (30 °C)

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 220 - 255 °C

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

Particle size : Not applicable

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:
Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Acute inhalation toxicity : LC50 (Mouse): 520400 ppm
Exposure time: 2 h
Test atmosphere: gas
Remarks: Based on data from similar materials

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:**Distillates (petroleum), hydrotreated light:**

Species : Rabbit
Result : Skin irritation

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light:**

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light:**

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
Date of first issue: 05/10/2019

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Liquified petroleum gas (LPG):**

Species : Mouse
Application Route : inhalation (gas)
Exposure time : 103 weeks
Result : negative

PENTOIL-(ROST-OFF)-BL-50ML

Version 1.2 Revision Date: 11/19/2020 SDS Number: 4270384-00003 Date of last issue: 10/23/2019
Date of first issue: 05/10/2019

Components:**Distillates (petroleum), hydrotreated light:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated light:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0.48 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 1.93 mg/l
Exposure time: 4 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated light:**

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Liquified petroleum gas (LPG):**

- Partition coefficient: n-octanol/water : log Pow: 1.09

Mobility in soil

No data available

Other adverse effects

No data available

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)
-

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
(Distillates (petroleum), hydrotreated light)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

16. OTHER INFORMATION
Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

IN OEL : India. Permissible levels of certain chemical substances in work environment.

IN OEL / TWA : Time-Weighted Average Concentration (TWA) (8 hrs.)

IN OEL / STEL : Short-term exposure Limit STEL (15 min)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods;

PENTOIL-(ROST-OFF)-BL-50ML

Version	Revision Date:	SDS Number:	Date of last issue: 10/23/2019
1.2	11/19/2020	4270384-00003	Date of first issue: 05/10/2019

vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IN / EN