

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ADD-DIESEL-250ML

Product code : 5861001325

Manufacturer or supplier's details

Company : Wuerth India Pvt. Ltd.

Address : 703/704, Windfall, Sahar Plaza Complex
Andheri (East), Mumbai 400059

Telephone : +91 8828111830

Emergency telephone number : 1800 102 5061

E-mail address : customer.care@wuerth.in

Recommended use of the chemical and restrictions on use

Recommended use : Fuels and fuel additives

2. HAZARDS IDENTIFICATION**Manufacture, Storage and Import of Hazardous Chemicals Rules 1989****Classification**

Flammable liquid

GHS Classification

Flammable liquids : Category 4

Aspiration hazard : Category 1

Long-term (chronic) aquatic hazard : Category 3

Skin corrosion/irritation : Category 3



Serious eye damage/eye irritation : Category 2A

Short-term (acute) aquatic hazard : Category 2

GHS label elements

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
 Date of first issue: 01/14/2015

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H227 Combustible liquid. H304 May be fatal if swallowed and enters airways. H316 Causes mild skin irritation. H319 Causes serious eye irritation. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<p>Prevention:</p> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <p>Response:</p> P301 + P316 IF SWALLOWED: Get emergency medical help immediately. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P331 Do NOT induce vomiting. P332 + P317 If skin irritation occurs: Get medical help. P337 + P317 If eye irritation persists: Get medical help. <p>Storage:</p> P405 Store locked up. <p>Disposal:</p> P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.
 Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 70 - < 90
2-Ethylhexyl nitrate	27247-96-7	>= 5 - < 10

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
 Date of first issue: 01/14/2015

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 5 - < 10
2-Ethylhexan-1-ol	104-76-7	>= 2.5 - < 5
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	>= 1 - < 2.5
Heptadecenyl imidazoline ethanol	95-38-5	>= 0.25 - < 1
Morpholine	110-91-8	>= 0.25 - < 1

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 If vomiting occurs have person lean forward.
 Call a physician or poison control centre immediately.
 Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
 Causes mild skin irritation.
 Causes serious eye irritation.
 Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

7. HANDLING AND STORAGE

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
 Date of first issue: 01/14/2015

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
 Avoid inhalation of vapour or mist.
 Do not swallow.
 Do not get in eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep container tightly closed.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labelled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA	300 ppm 900 mg/m ³	IN OEL
		STEL	500 ppm 1,500 mg/m ³	IN OEL
		TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL
Morpholine	110-91-8	TWA	20 ppm	ACGIH

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Hand protection

Material : Nitrile rubber

Break through time : 480 min

Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

Odour : characteristic

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Odour Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	100 °C
Flash point	:	62 °C Method: ISO 3679
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0.5 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.831 g/cm ³ (20 °C) Method: DIN 51757
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	215 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	2.11 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

10. STABILITY AND REACTIVITY

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapours may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 40 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 4,951 mg/m ³ Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): >= 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

2-Ethylhexyl nitrate:

- Acute oral toxicity : LD50 (Rat): > 9,600 mg/kg
Acute toxicity estimate: 500 mg/kg
Method: Expert judgement
- Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Test atmosphere: vapour
Method: Expert judgement
- Acute dermal toxicity : LD50 (Rabbit): > 4,800 mg/kg
Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement

Distillates (petroleum), hydrotreated heavy paraffinic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

2-Ethylhexan-1-ol:

- Acute oral toxicity : LD50 (Rat): 2,047 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 0.89 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 1 - 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Acute oral toxicity : LD50 (Rat): 1,265 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Morpholine:

Acute oral toxicity : LD50 (Rat): 1,900 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit, male): 500 mg/kg

Skin corrosion/irritation

Causes mild skin irritation.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Ethylhexyl nitrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Morpholine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Result : Irreversible effects on the eye
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Species : Rabbit
Result : Irreversible effects on the eye

Morpholine:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Test Type : Maurer optimisation test
Exposure routes : Skin contact
Species : Guinea pig

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Result : negative

Morpholine:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

2-Ethylhexyl nitrate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2-Ethylhexan-1-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Morpholine:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Test system: Rat
Result: negative
Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Hamster
Application Route: Ingestion
Result: negative
Remarks: In vivo tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

2-Ethylhexan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Morpholine:

Effects on foetal development : Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

Components:**2-Ethylhexan-1-ol:**

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**2-Ethylhexan-1-ol:**

Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Heptadecenyl imidazoline ethanol:

Exposure routes : Ingestion
Target Organs : Gastrointestinal tract, thymus gland
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Morpholine:

Exposure routes : Inhalation
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
NOAEL : >= 1,000 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Remarks : Based on data from similar materials

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

2-Ethylhexyl nitrate:

Species : Rabbit
NOAEL : 500 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 980 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks

2-Ethylhexan-1-ol:

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : 0.6384 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Species : Rat
NOAEL : 20 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 31 - 51 Days
Method : OECD Test Guideline 422

Morpholine:

Species : Rat

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

NOAEL	:	50 mg/kg
Application Route	:	inhalation (vapour)
Exposure time	:	104 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 2 mg/l
Exposure time: 96 h

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 12.6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.22 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 1.54 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

2-Ethylhexan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 28.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 39 mg/l

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
 Date of first issue: 01/14/2015

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0.03 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 0.014 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : IC50: 26 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

M-Factor (Chronic aquatic toxicity) : 1

Morpholine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 380 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 45 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 28 mg/l
 Exposure time: 96 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
 Exposure time: 30 min
 Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 5 mg/l
 Exposure time: 21 d
 Species: Daphnia magna (Water flea)
 Method: OECD Test Guideline 211

Persistence and degradability**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F
 Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Biodegradability : Result: Not readily biodegradable.

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 310

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-Ethylhexan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 - 99.9 %
Exposure time: 14 d

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Morpholine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 93 %
Exposure time: 25 d
Method: OECD Test Guideline 301E

Bioaccumulative potential**Components:****2-Ethylhexyl nitrate:**

Partition coefficient: n-octanol/water : log Pow: 5.24

2-Ethylhexan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 2.9

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Partition coefficient: n-octanol/water : log Pow: < 4

Morpholine:

ADD-DIESEL-250ML

Version 7.0 Revision Date: 01/29/2021 SDS Number: 732093-00009 Date of last issue: 12/14/2020
Date of first issue: 01/14/2015

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 2.8

Partition coefficient: n-octanol/water : log Pow: -2.55

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

16. OTHER INFORMATION**Further information**Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
IN OEL	: India. Permissible levels of certain chemical substances in work environment.
ACGIH / TWA	: 8-hour, time-weighted average
IN OEL / TWA	: Time-Weighted Average Concentration (TWA) (8 hrs.)
IN OEL / STEL	: Short-term exposure Limit STEL (15 min)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

ADD-DIESEL-250ML

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2020
7.0	01/29/2021	732093-00009	Date of first issue: 01/14/2015

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IN / EN