

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : NEUTRAL SILICONE WEATHER SEALANT BLACK  
Product code : 089253882

**Manufacturer or supplier's details**

Company : Wurth Lanka (PVT) LTD  
Address : 375/B, High Level Road  
Makumbura, Pannipitya, Sri Lanka  
Telephone : 0094-112894930  
Emergency telephone number : 0094-777328880  
E-mail address : prodsafe@wuerth.com  
Telefax : 0094-112894955

**Recommended use of the chemical and restrictions on use**

Recommended use : Sealant

---

**2. HAZARDS IDENTIFICATION****GHS Classification**

Acute toxicity (Oral) : Category 5  
Skin corrosion/irritation : Category 3  
Serious eye damage/eye irritation : Category 2A  
Skin sensitisation : Category 1  
Carcinogenicity : Category 1B  
Specific target organ toxicity - single exposure (Inhalation) : Category 2 (Upper respiratory tract)

**GHS label elements**

Hazard pictograms :   
Signal word : Danger

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

Hazard statements	:	<p>H303 May be harmful if swallowed. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350 May cause cancer. H371 May cause damage to organs (Upper respiratory tract) if inhaled.</p>
Precautionary statements	:	<p><b>Prevention:</b> P203 Obtain, read and follow all safety instructions before use. P260 Do not breathe vapours. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p><b>Response:</b> P301 + P333 + P317 IF SWALLOWED or if skin irritation or rash occurs: Get medical help. P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P316 IF exposed or concerned: Get emergency medical help immediately. P337 + P317 If eye irritation persists: Get medical help. P362 + P364 Take off contaminated clothing and wash it before reuse.</p> <p><b>Storage:</b> P405 Store locked up.</p> <p><b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.</p>

### Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 10 - < 20
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime	22984-54-9	>= 2.5 - < 5

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

Ethyl methyl ketoxime	96-29-7	$\geq 1 - < 2.5$
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime	2224-33-1	$\geq 0.25 - < 1$
3-(2-Aminoethylamino) propyltrimethoxysilane	1760-24-3	$\geq 0.25 - < 1$

### 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May be harmful if swallowed.  
Causes mild skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause cancer.  
May cause damage to organs if inhaled.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire- : Exposure to combustion products may be a hazard to health.

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

fighting

Hazardous combustion products : Carbon oxides  
Silicon oxides  
Nitrogen oxides (NOx)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

		<p>Do not breathe vapours. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep container tightly closed. Keep away from water. Protect from moisture. Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.</p>
	Conditions for safe storage	: Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.
	Materials to avoid	: Do not store with the following product types: Strong oxidizing agents

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

	<b>Engineering measures</b>	: Processing may form hazardous compounds (see section 10). Minimize workplace exposure concentrations. If sufficient ventilation is unavailable, use with local exhaust ventilation.
--	-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Personal protective equipment

	Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
	Filter type	: Combined particulates and organic vapour type
	Hand protection	
	Material	: Nitrile rubber
	Break through time	: 10 - 60 min
	Glove thickness	: > 0.1 mm
	Material	: butyl-rubber
	Break through time	: > 480 min
	Glove thickness	: > 0.3 mm

	Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous sub-
--	---------	----------------------------------------------------------------------------------------------------------------------

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version 4.0	Revision Date: 09/22/2021	SDS Number: 977112-00005	Date of last issue: 11/12/2020 Date of first issue: 10/25/2016
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

---

stance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection	:	Wear the following personal protective equipment: Safety goggles
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	:	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	coloured
Odour	:	strong
Odour Threshold	:	No data available
pH	:	ca. 7
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 250 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper	:	No data available

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

flammability limit

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 1.00 (23 °C)

Density : 1.00 g/cm<sup>3</sup> (23 °C)

Solubility(ies)

Water solubility : hydrolyses, Decomposes in contact with water.

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : ca. 430 °C  
Method: DIN 51794

Decomposition temperature : > 150 °C

Viscosity

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

### 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air.  
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture

Incompatible materials : Oxidizing agents  
Water

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

**Hazardous decomposition products**

Contact with water or humid air : Ethyl methyl ketoxime

---

**11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

|| May be harmful if swallowed.

**Product:**

|| Acute oral toxicity : Acute toxicity estimate: 4,538 mg/kg  
Method: Calculation method  
|| Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Components:****Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Acute oral toxicity : LD50 (Rat): 2,453 mg/kg  
Method: OECD Test Guideline 401  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

**Ethyl methyl ketoxime:**

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg  
Method: Expert judgement  
Acute inhalation toxicity : LC50 (Rat): > 4.83 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg

---



**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

Method: Expert judgement

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 2,009 mg/kg  
Method: OECD Test Guideline 402

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Acute oral toxicity : LD50 (Rat, female): 1,897 mg/kg  
Method: OPPTS 870.1100

Acute inhalation toxicity : LC50 (Rat): 1.49 - 2.44 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OPPTS 870.1300

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OPPTS 870.1200

**Skin corrosion/irritation**

|| Causes mild skin irritation.

**Components:****Distillates (petroleum), hydrotreated middle:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Ethyl methyl ketoxime:**

Species : Rabbit  
Result : Skin irritation

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

**Serious eye damage/eye irritation**

|| Causes serious eye irritation.

**Components:****Distillates (petroleum), hydrotreated middle:**

Result : No eye irritation

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

**Ethyl methyl ketoxime:**

Species : Rabbit  
Result : Irreversible effects on the eye

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irreversible effects on the eye

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irreversible effects on the eye

**Respiratory or skin sensitisation****Skin sensitisation**

|| May cause an allergic skin reaction.

**Respiratory sensitisation**

|| Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Test Type : Human repeat insult patch test (HRIPT)  
Exposure routes : Skin contact  
Result : negative

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

### Ethyl methyl ketoxime:

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	positive

Assessment	:	Probability or evidence of skin sensitisation in humans
------------	---	---------------------------------------------------------

### Butan-2-one O,O',O''-(vinylsilyldiyne)trioxime:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	positive
Remarks	:	Based on data from similar materials

Assessment	:	Probability or evidence of skin sensitisation in humans
------------	---	---------------------------------------------------------

### 3-(2-Aminoethylamino) propyltrimethoxysilane:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	positive

Assessment	:	Probability or evidence of low to moderate skin sensitisation rate in humans
------------	---	------------------------------------------------------------------------------

### Germ cell mutagenicity

|| Not classified based on available information.

#### Components:

#### Distillates (petroleum), hydrotreated middle:

Genotoxicity in vitro	:	Test Type: In vitro sister chromatid exchange assay in mammalian cells
		Result: negative

#### Butan-2-one O,O',O''-(methylsilyldiyne)trioxime:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES)
		Result: negative

#### Ethyl methyl ketoxime:

Genotoxicity in vitro	:	Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
		Method: OECD Test Guideline 482
		Result: negative

Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
		Species: Rat

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

Application Route: Ingestion  
Result: negative

### **Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: positive

Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### **3-(2-Aminoethylamino) propyltrimethoxysilane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Method: OPPTS 870.5900  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### **Carcinogenicity**

**II** May cause cancer.

### **Components:**

#### **Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assess- : Sufficient evidence of carcinogenicity in animal experiments

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

ment

### Ethyl methyl ketoxime:

Species : Rat  
 Application Route : inhalation (vapour)  
 Exposure time : 26 Months  
 Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

### Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:

Species : Rat  
 Application Route : inhalation (vapour)  
 Exposure time : 26 Months  
 Result : positive  
 Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

### Reproductive toxicity

|| Not classified based on available information.

### Components:

#### Butan-2-one O,O',O''-(methylsilylidyne)trioxime:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

#### Ethyl methyl ketoxime:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
 Species: Rat  
 Application Route: Ingestion

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

Method: OECD Test Guideline 414  
Result: negative

**Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**STOT - single exposure**

|| May cause damage to organs (Upper respiratory tract) if inhaled.

**Components:****Butan-2-one O,O',O''-(methylsilyldiyl)trioxime:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

**Ethyl methyl ketoxime:**

Assessment : May cause drowsiness or dizziness.

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Upper respiratory tract  
Assessment : Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

**STOT - repeated exposure**

|| Not classified based on available information.

**Components:****Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.  
Remarks : Based on data from similar materials

**Ethyl methyl ketoxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Exposure routes : Ingestion  
Target Organs : Blood  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.  
Remarks : Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

**Repeated dose toxicity****Components:****Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Species : Rat  
LOAEL : > 1.7 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Remarks : Based on data from similar materials

Species : Rat, male  
NOAEL : > 10 - 100 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

Remarks : Based on data from similar materials

**Ethyl methyl ketoxime:**

Species : Rat  
LOAEL : 0.054 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 26 Months

Species : Rat, male  
NOAEL : 25 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Species : Rat  
LOAEL : > 1.7 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 26 Months  
Remarks : Based on data from similar materials

Species : Rat, male  
NOAEL : > 10 - 100 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Species : Rat  
NOAEL : >= 500 mg/kg  
Application Route : Ingestion  
Exposure time : 44 Days

Species : Rat  
NOAEL : 0.015 mg/l  
LOAEL : 0.045 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

**Aspiration toxicity**

|| Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.



## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Distillates (petroleum), hydrotreated middle:**

- |                                                                        |   |                                                                                      |
|------------------------------------------------------------------------|---|--------------------------------------------------------------------------------------|
| Toxicity to fish                                                       | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 87,556 mg/l<br>Exposure time: 96 h     |
| Toxicity to daphnia and other aquatic invertebrates                    | : | EC50 (Daphnia magna (Water flea)): > 1,000 mg/l<br>Exposure time: 48 h               |
| Toxicity to algae/aquatic plants                                       | : | EC50 ( Selenastrum capricornutum (green algae)): > 1,000 mg/l<br>Exposure time: 72 h |
| Toxicity to microorganisms                                             | : | EC50: > 100 mg/l<br>Exposure time: 3 h                                               |
| Toxicity to fish (Chronic toxicity)                                    | : | NOELR: > 1,000 mg/l<br>Exposure time: 28 d                                           |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOELR: 5 mg/l<br>Exposure time: 21 d                                                 |

##### **Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

- |                                                     |   |                                                                                                                           |
|-----------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : | EC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203          |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 120 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202                   |
| Toxicity to algae/aquatic plants                    | : | ErC50 ( Pseudokirchneriella subcapitata (green algae)): 94 mg/l<br>Exposure time: 72 h<br>Method: OECD Test Guideline 201 |
|                                                     |   | NOEC ( Pseudokirchneriella subcapitata (green algae)): 30 mg/l<br>Exposure time: 72 h<br>Method: OECD Test Guideline 201  |
| Toxicity to microorganisms                          | : | EC50: > 1,000 mg/l<br>Exposure time: 3 h<br>Method: OECD Test Guideline 209                                               |
| Toxicity to fish (Chronic toxicity)                 | : | NOEC: > 1 mg/l<br>Exposure time: 14 d                                                                                     |

## NEUTRAL SILICONE WEATHER SEALANT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

Species: *Oryzias latipes* (Orange-red killifish)  
 Method: OECD Test Guideline 204  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 mg/l  
 Exposure time: 21 d  
 Species: *Daphnia magna* (Water flea)  
 Method: OECD Test Guideline 211  
 Remarks: Based on data from similar materials

### Ethyl methyl ketoxime:

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 201 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 ( *Scenedesmus capricornutum* (fresh water algae)): 11.8 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

NOEC ( *Scenedesmus capricornutum* (fresh water algae)): 2.56 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 281 mg/l  
 Exposure time: 17 h

Toxicity to fish (Chronic toxicity) : NOEC: 50 mg/l  
 Exposure time: 14 d  
 Species: *Oryzias latipes* (Japanese medaka)  
 Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 100 mg/l  
 Exposure time: 21 d  
 Species: *Daphnia magna* (Water flea)  
 Method: OECD Test Guideline 211

### Butan-2-one O,O',O''-(vinylsilyldi)trioxime:

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

Toxicity to algae/aquatic plants : ErC50 ( *Scenedesmus capricornutum* (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC ( *Scenedesmus capricornutum* (fresh water algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): > 100 mg/l  
Exposure time: 17 h  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 1 mg/l  
Exposure time: 14 d  
Species: *Oryzias latipes* (Orange-red killifish)  
Method: OECD Test Guideline 204  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: Directive 67/548/EEC, Annex V, C.2.  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 ( *Pseudokirchneriella subcapitata* (green algae)): > 1 - 10 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC ( *Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version 4.0      Revision Date: 09/22/2021      SDS Number: 977112-00005      Date of last issue: 11/12/2020  
Date of first issue: 10/25/2016

---

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1 mg/l  
Exposure time: 16 h  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC: >= 1 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Distillates (petroleum), hydrotreated middle:**

Biodegradability : Result: Inherently biodegradable.

**Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 28 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

**Ethyl methyl ketoxime:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 27 %  
Exposure time: 21 d

**Butan-2-one O,O',O''-(vinylsilylidyne)trioxime:**

Biodegradability : Result: not rapidly degradable  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A  
Remarks: Based on data from similar materials

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Biodegradability : Result: Not readily biodegradable.  
Method: Regulation (EC) No. 440/2008, Annex, C.4-A  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Butan-2-one O,O',O''-(methylsilylidyne)trioxime:**

Partition coefficient: n- : log Pow: 0.59 - 0.65  
octanol/water

**Ethyl methyl ketoxime:**

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 0.5 - 0.6  
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 0.63

**Butan-2-one O,O',O''-(vinylsilyldiene)trioxime:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 0.5 - 2.5  
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 0.59 - 0.65

**3-(2-Aminoethylamino) propyltrimethoxysilane:**

Partition coefficient: n-octanol/water : log Pow: -3.3  
Remarks: Calculation

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**13. DISPOSAL CONSIDERATIONS****Disposal methods**

- |                        |                                                                                                                                                               |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste from residues    | : Dispose of in accordance with local regulations.                                                                                                            |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.<br>If not otherwise specified: Dispose of as unused product. |
- 

**14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to IMO instruments**

Not applicable for product as supplied.

---

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

**Special precautions for user**Not applicable

---

**15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

---

**16. OTHER INFORMATION****Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

**Full text of other abbreviations**

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Sub-

**NEUTRAL SILICONE WEATHER SEALANT  
BLACK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2020
4.0	09/22/2021	977112-00005	Date of first issue: 10/25/2016

---

stances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

LK / EN