

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

**Section 1: Identification**

Product name : SILICONE REMOVER 5 LITRE

Product code : 0893 222 5

**Manufacturer or supplier's details**

Company : Wurth NewZealand Ltd

Address : 99 McLaughlins Road  
Wiri, Auckland 2104

Telephone : +64 9 262 3040

Emergency telephone number : 0800 764 766

E-mail address : prodsafe@wuerth.com

Telefax : +64 9 262 3030

**Recommended use of the chemical and restrictions on use**

Recommended use : Cleaning agent  
Detergent

---

**Section 2: Hazard identification****GHS Classification**

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.

## SILICONE REMOVER 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 09.11.2020
4.7	14.10.2021	512958-00007	Date of first issue: 18.07.2012

---

H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

Vapours may form explosive mixture with air.

Repeated exposure may cause skin dryness or cracking.

---

**Section 3: Composition/information on ingredients**

Substance / Mixture	:	Substance
Chemical nature	:	Hydrocarbons
Substance name	:	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
CAS-No.	:	64742-82-1

**Components**

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
 Date of first issue: 18.07.2012

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	>= 60 -<= 100

### Section 4: First-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 If vomiting occurs have person lean forward.  
 Call a physician or poison control centre immediately.  
 Rinse mouth thoroughly with water.  
 Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
 May cause drowsiness or dizziness.  
 Causes damage to organs through prolonged or repeated exposure.  
 Repeated exposure may cause skin dryness or cracking.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
 Flash back possible over considerable distance.  
 Vapours may form explosive mixtures with air.

## SILICONE REMOVER 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 09.11.2020
4.7	14.10.2021	512958-00007	Date of first issue: 18.07.2012

---

Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 3Y

---

**Section 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**Section 7: Handling and storage**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

---

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
 Date of first issue: 18.07.2012

- ventilation.  
 Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
 Do not breathe mist or vapours.  
 Do not swallow.  
 Avoid contact with eyes.  
 Wash skin thoroughly after handling.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Non-sparking tools should be used.  
 Keep container tightly closed.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Do not eat, drink or smoke when using this product.  
 Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
 When using do not eat, drink or smoke.  
 Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.  
 Store locked up.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable gases  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Poisonous gases  
 Explosives

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,	64742-82-1	WES-TWA	300 ppm 890 mg/m <sup>3</sup>	NZ OEL

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
 Date of first issue: 18.07.2012

aromatics (2-25%)				
		WES-STEL	500 ppm 1,480 mg/m <sup>3</sup>	NZ OEL

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

### Hand protection

Material : Nitrile rubber  
 Break through time : > 480 min  
 Glove thickness : >= 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses  
 Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
 Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

### Section 9: Physical and chemical properties

Appearance : liquid

Colour : colourless

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : < -15 °C

Initial boiling point and boiling range : 130 - 180 °C  
(1,013 hPa)  
Method: DIN 51751

Flash point : > 23 - < 40 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : 6.5 %(V)

Lower explosion limit / Lower flammability limit : 0.7 %(V)

Vapour pressure : 800 Pa (20 °C)  
3,500 Pa (50 °C)

Relative vapour density : 4.5 (20 °C )  
(Air = 1.0)

Relative density : No data available

Density : 0.770 - 0.785 g/cm<sup>3</sup> (15 °C)  
Method: DIN 51757

Solubility(ies)  
Water solubility : 40 mg/l (20 °C)

Partition coefficient: n-octanol/water : log Pow: 3.7 - 6.4

Auto-ignition temperature : No data available  
324 °C  
Method: DIN 51794

Decomposition temperature : No data available

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

Viscosity  
Viscosity, kinematic      :    0.98 mm<sup>2</sup>/s ( 25 °C)

Explosive properties      :    Not explosive

Oxidizing properties      :    The substance or mixture is not classified as oxidizing.

Refractive index      :    1.432 (20 °C)

Particle size      :    Not applicable

---

**Section 10: Stability and reactivity**

Reactivity      :    Not classified as a reactivity hazard.

Chemical stability      :    Stable under normal conditions.

Possibility of hazardous reactions      :    Flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid      :    Heat, flames and sparks.

Incompatible materials      :    Oxidizing agents

Hazardous decomposition products      :    No hazardous decomposition products are known.

---

**Section 11: Toxicological information**

Exposure routes      :    Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Acute oral toxicity      :    LD50 (Rat): > 15,000 mg/kg

Acute inhalation toxicity      :    LC50 (Rat): > 13.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity      :    LD50 (Rat): > 3,400 mg/kg

**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.



## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 105 weeks  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

**Repeated dose toxicity****Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rat  
NOAEL : 1,056 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 3.950 mg/l  
LOAEL : 7.400 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Inhalation : Symptoms: central nervous system effects

---

**Section 12: Ecological information****Ecotoxicity****Components:****Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10 - 22 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 4.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction

---

## SILICONE REMOVER 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 09.11.2020
4.7	14.10.2021	512958-00007	Date of first issue: 18.07.2012

---

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.76 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.097 mg/l  
Exposure time: 21 d

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 75.9 %  
Exposure time: 31 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

### Bioaccumulative potential

#### Components:

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Partition coefficient: n-octanol/water : Pow: > 4

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## Section 13: Disposal considerations

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

## SILICONE REMOVER 5 LITRE

Version 4.7      Revision Date: 14.10.2021      SDS Number: 512958-00007      Date of last issue: 09.11.2020  
Date of first issue: 18.07.2012

---

**Section 14: Transport information****International Regulations****UNRTDG**

UN number : UN 3295  
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 3295  
Proper shipping name : Hydrocarbons, liquid, n.o.s.  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 3295  
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****NZS 5433**

UN number : UN 3295  
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : 3Y

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**Section 15: Regulatory information**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

## SILICONE REMOVER 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 09.11.2020
4.7	14.10.2021	512958-00007	Date of first issue: 18.07.2012

---

**HSNO Approval Number**

HSR002528 Cleaning Products Flammable Group Standard 2017  
HSR002650 Solvents Flammable Group Standard 2017

**HSW Controls**

Certified handler certificate not required.  
Tracking hazardous substance not required.  
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

**The components of this product are reported in the following inventories:**

NZIoC : All ingredients listed or exempt.

---

**Section 16: Other information****Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

**Full text of other abbreviations**

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

## SILICONE REMOVER 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 09.11.2020
4.7	14.10.2021	512958-00007	Date of first issue: 18.07.2012

---

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN