

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : FILR-GF-(VAKU-70)-1800G-(COMP B)

Product code : 0892 607 02 (B)

Manufacturer or supplier's details

Company : Wurth Australia Pty Ltd

Address : 2/1 Healey Road
Dandenong South, Victoria, 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National Poisons Centre: 131 126

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Correction of paintwork damage on motor vehicles
Filler

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure : Category 1 (Auditory system)

GHS label elements

Hazard pictograms :



Signal word : Danger

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
 Date of first issue: 09.10.2018

Components

Chemical name	CAS-No.	Concentration (% w/w)
Talc	14807-96-6	>= 10 -< 30
Limestone	1317-65-3	>= 10 -< 30
Styrene	100-42-5	>= 10 -< 20
Titanium dioxide	13463-67-7	>= 1 -< 10
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	< 10

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 Causes serious eye irritation.
 Suspected of causing cancer.
 Suspected of damaging the unborn child.
 Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
 Alcohol-resistant foam

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

- Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

mine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |
| Materials to avoid | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives |

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
 Date of first issue: 09.10.2018

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWA	2.5 mg/m ³	AU OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Limestone	1317-65-3	TWA	10 mg/m ³ (Calcium carbonate)	AU OEL
Styrene	100-42-5	STEL	100 ppm 426 mg/m ³	AU OEL
		TWA	50 ppm 213 mg/m ³	AU OEL
		TWA	10 ppm	ACGIH
		STEL	20 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	AU OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Titanium dioxide

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Styrene	100-42-5	Mandelic acid plus phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	400 mg/g Creatinine	ACGIH BEI
		Styrene	Urine	End of shift (As soon as possible after exposure ceases)	40 µg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equip-

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

ment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Hand protection

Material : Fluorinated rubber

Break through time : > 60 min

Glove thickness : ≥ 0.7 mm

Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : coloured

Odour : characteristic

Odour Threshold : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Melting point/freezing point : No data available

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Initial boiling point and boiling range : 145 °C

Flash point : 34 °C
Method: DIN 53213

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 8.9 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapour pressure : 6 hPa (20 °C)

Relative vapour density : No data available

Density : 1.654 g/cm³ (20 °C)

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 480 °C
Method: DIN 51794

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : 60,000 - 80,000 mPa.s (20 °C)
Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes	:	Inhalation Skin contact Ingestion Eye contact
-----------------	---	--

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	---	--

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
---------------------------	---	---

Components:**Talc:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
---------------------	---	--

Limestone:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: Based on data from similar materials
---------------------	---	--

Acute inhalation toxicity	:	LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
---------------------------	---	---

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Styrene:

Acute oral toxicity : LD50 (Hamster): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

1,1'-(p-tolylimino)dipropan-2-ol:

Acute oral toxicity : LD50 (Rat): > 25 - 200 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:**Talc:**

Species : Rabbit
Result : No skin irritation

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Styrene:

Species	:	Rabbit
Result	:	Skin irritation

Titanium dioxide:

Species	:	Rabbit
Result	:	No skin irritation

1,1'-(p-tolylimino)dipropan-2-ol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Talc:**

Species	:	Rabbit
Result	:	No eye irritation

Limestone:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Styrene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Titanium dioxide:

Species	:	Rabbit
Result	:	No eye irritation

1,1'-(p-tolylimino)dipropan-2-ol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

Components:**Talc:**

Exposure routes : Skin contact
Species : Humans
Result : negative

Limestone:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

1,1'-(p-tolylimino)dipropan-2-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Styrene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: inhalation (vapour)
Method: OECD Test Guideline 474
Result: negative

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Talc:**

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Styrene:

Species : Rat
 Application Route : inhalation (vapour)
 Exposure time : 104 weeks
 Result : positive
 Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Titanium dioxide:

Species : Rat
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years
 Method : OECD Test Guideline 453
 Result : positive
 Remarks : The mechanism or mode of action may not be relevant in humans.
 These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:
Talc:

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Result: negative

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version 4.2 Revision Date: 20.10.2021 SDS Number: 3510913-00006 Date of last issue: 27.11.2020
Date of first issue: 09.10.2018

Styrene:

- Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: positive
- Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

1,1'-(p-tolylimino)dipropan-2-ol:

- Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
- Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

STOT - single exposure

Not classified based on available information.

Components:**Styrene:**

- Assessment : May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (Auditory system) through prolonged or repeated exposure.

Components:**Styrene:**

- Target Organs : Auditory system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:****Limestone:**

- Species : Rat

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

NOAEL : > 300 mg/kg
 Application Route : Ingestion
 Exposure time : 28 Days
 Method : OECD Test Guideline 422
 Remarks : Based on data from similar materials

Styrene:

Species : Rat
 NOAEL : 1.28 mg/l
 Application Route : inhalation (vapour)
 Exposure time : 4 Weeks

Species : Rat
 NOAEL : 1,000 - 2,000 mg/kg
 Application Route : Ingestion
 Exposure time : 78 - 100 Weeks

Titanium dioxide:

Species : Rat
 NOAEL : 24,000 mg/kg
 Application Route : Ingestion
 Exposure time : 28 Days

Species : Rat
 NOAEL : 10 mg/m³
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 yr

Aspiration toxicity

Not classified based on available information.

Components:
Styrene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
 Exposure time: 24 h

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: No toxicity at the limit of solubility
 Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: No toxicity at the limit of solubility
 Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 6.3 mg/l
 Exposure time: 96 h
 EC10 (Pseudokirchneriella subcapitata (green algae)): 0.28 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.01 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEC (Pseudomonas putida): 72 mg/l
 Exposure time: 16 h

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

1,1'-(p-tolylimino)dipropan-2-ol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 17 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 28.8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 57.8 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 245 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l
Exposure time: 30 min

Persistence and degradability
Components:
Styrene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d

1,1'-(p-tolylimino)dipropan-2-ol:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 90.1 %
Exposure time: 60 d
Method: OECD Test Guideline 301B

Bioaccumulative potential
Components:
Styrene:

Partition coefficient: n- : log Pow: 2.96

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

octanol/water

1,1'-(p-tolylimino)dipropan-2-ol:

Partition coefficient: n- : log Pow: 2.1
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : III

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number	:	UN 1866
Proper shipping name	:	RESIN SOLUTION
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	•3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform Scheduling of Medicines and Poisons	:	No poison schedule number allocated
--	---	-------------------------------------

Prohibition/Licensing Requirements	:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.
------------------------------------	---	---

The components of this product are reported in the following inventories:

AllC	:	All ingredients listed or exempt.
------	---	-----------------------------------

SECTION 16. OTHER INFORMATION**Further information**

Revision Date	:	20.10.2021
Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
Date format	:	dd.mm.yyyy

FILR-GF-(VAKU-70)-1800G-(COMP B)

Version	Revision Date:	SDS Number:	Date of last issue: 27.11.2020
4.2	20.10.2021	3510913-00006	Date of first issue: 09.10.2018

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN