

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	High Perf Dry Chain Lube 500ml
Product code	:	0893 015 13
Unique Formula Identifier (UFI)	:	FAX9-Q0CN-3004-7D0X

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Anti-friction agent and lubricant Professional use product
Recommended restrictions on use	:	Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Wurth UK Ltd 1 Centurion Way Erith, Kent
Telephone	:	+44 (0)3300 555 444
Telefax	:	+44 (0)3300 555 666
E-mail address of person responsible for the SDS	:	prodsafe@wuerth.com

#### 1.4 Emergency telephone number

+44 (0)870 190 6777

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

Long-term (chronic) aquatic hazard, Category 2      H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P273 Avoid release to the environment.

**Response:**

- P391 Collect spillage.

**Storage:**

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:  
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

#### Additional Labelling

EUH208      Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts.  
May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.  
May displace oxygen and cause rapid suffocation.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0  01-2119475514-35	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0  01-2119475515-33	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
n-Hexane	110-54-3 203-777-6 601-037-00-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 STOT RE 2; H373 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411  specific concentration limit STOT RE 2; H373 >= 5 %	>= 0.25 - < 1
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0 274-263-7	Skin Sens. 1; H317	>= 0.1 - < 1
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280	>= 1 - < 10

##### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause drowsiness or dizziness.
- May produce an allergic reaction.
- Gas reduces oxygen available for breathing.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam
-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |  |
|-------------------------|---|--|
| Technical measures      | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.  |
| Advice on safe handling | : | Do not get on skin or clothing.<br>Avoid breathing spray.<br>Do not swallow.<br>Avoid contact with eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br>Do not spray on an open flame or other ignition source. |
| Hygiene measures        | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.<br>Wash contaminated clothing before re-use.   |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Recommended storage temperature :  $\geq 10$  °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	500 ppm 2,085 mg/m <sup>3</sup>	GB EH40
		TWA	500 ppm 2,085 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				
Butane	106-97-8	TWA	600 ppm 1,450 mg/m <sup>3</sup>	GB EH40
		Further information: Capable of causing cancer and/or heritable genetic damage.		
		STEL	750 ppm 1,810 mg/m <sup>3</sup>	GB EH40
Further information: Capable of causing cancer and/or heritable genetic damage.				
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	GB EH40
		TWA	20 ppm 72 mg/m <sup>3</sup>	2006/15/EC

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

Further information: Indicative

### Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Hexane	Workers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	75 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	5.3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	16 mg/m <sup>3</sup>
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	Workers	Inhalation	Long-term systemic effects	4 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0.66 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0.33 mg/m <sup>3</sup>
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	1.667 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0.8333 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2035 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	608 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	699 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	699 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	2085 mg/m <sup>3</sup>
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	Skin contact	Long-term systemic effects	300 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	447 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	149 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	149 mg/kg bw/day

### Predicted No Effect Concentration (PNEC):



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

Substance name	Environmental Compartment	Value
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	Fresh water	1 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	723500000 mg/kg
	Marine sediment	723500000 mg/kg
	Soil	16.667 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety glasses  
Equipment should conform to BS EN 166

Hand protection  
Material : Nitrile rubber  
Break through time : <= 480 min  
Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to BS EN 137

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Filter type : Self-contained breathing apparatus

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	Aerosol containing a liquefied gas
Propellant	:	Isobutane, Propane, Butane
Colour	:	beige
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	60 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	11 %(V)
Lower explosion limit / Lower flammability limit	:	1.0 %(V)
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	0.7175 g/cm <sup>3</sup> (20 °C) Method: DIN 51757
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	> 200 °C
Decomposition temperature	:	No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting  
due to the high vapor pressure.  
Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

---

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### n-Hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Butane:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

#### n-Hexane:

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

#### Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit  
Result : No eye irritation

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

#### n-Hexane:

Species : Rabbit  
Result : No eye irritation

#### Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Species : Rabbit

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Method : Draize Test  
Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

##### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

##### n-Hexane:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

##### Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Assessment : Probability or evidence of skin sensitisation in humans

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OPPTS 870.5395  
Result: negative

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

---

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

### n-Hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

#### **n-Hexane:**

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### **n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapour)  
Result: positive

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative  
Remarks: Based on data from similar materials

### **Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

---

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

### n-Hexane:

Assessment : May cause drowsiness or dizziness.

### Butane:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### n-Hexane:

Exposure routes : inhalation (vapour)  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

### Repeated dose toxicity

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rat  
NOAEL : 12.47 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

#### n-Hexane:

Species : Mouse  
LOAEL : 1.76 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3,973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

---

### **Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:**

Species : Rat  
NOAEL : 500 mg/kg  
Application Route : Ingestion  
Exposure time : 29 Days  
Method : OECD Test Guideline 407

Species : Rat  
NOAEL : > 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 28 Days  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

### **Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **Experience with human exposure**

#### **Components:**

#### **n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
aquatic invertebrates Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1  
plants mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5  
mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOELR: 2.6 mg/l  
aquatic invertebrates (Chron- Exposure time: 21 d  
ic toxicity) Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 3 mg/l  
aquatic invertebrates Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100  
plants mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.17 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **n-Hexane:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:**

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): >

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

plants 1,000 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

### 12.2 Persistence and degradability

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **n-Hexane:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 8 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Remarks: Based on data from similar materials

##### **Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

### 12.3 Bioaccumulative potential

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: 4  
octanol/water Remarks: Based on data from similar materials

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Partition coefficient: n- : log Pow: > 4  
octanol/water Remarks: Based on data from similar materials

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

### **n-Hexane:**

Partition coefficient: n-octanol/water : log Pow: 4

### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

No data available

---

## **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

Please ensure aerosol cans are sprayed completely empty  
(including propellant)

Waste Code

: The following Waste Codes are only suggestions:

used product

16 05 04, gases in pressure containers (including halons)  
containing hazardous substances

unused product

16 05 04, gases in pressure containers (including halons)  
containing hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated  
by hazardous substances

### SECTION 14: Transport information

#### 14.1 UN number

ADN : UN 1950

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

#### 14.2 UN proper shipping name

ADN : AEROSOLS

ADR : AEROSOLS

RID : AEROSOLS

IMDG : AEROSOLS

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-  
hexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

ADN : 2

ADR : 2

RID : 2

IMDG : 2.1

IATA : 2.1

#### 14.4 Packing group

ADN



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

### ADR

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

### RID

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : yes

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version 9.0      Revision Date: 15.11.2022      SDS Number: 9985679-00003      Date of last issue: 30.05.2022  
Date of first issue: 21.12.2009

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	: Not applicable

#### Control of Major Accident Hazards Regulations 2015 (COMAH)

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in	2,500 t	25,000 t

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009



points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 94.6 %, 619 g/l  
Remarks: VOC content excluding water

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H336 : May cause drowsiness or dizziness.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Gas : Flammable gases  
Flam. Liq. : Flammable liquids  
Press. Gas : Gases under pressure  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2006/15/EC : Europe. Indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2006/15/EC / TWA : Limit Value - eight hours  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## High Perf Dry Chain Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
9.0	15.11.2022	9985679-00003	Date of first issue: 21.12.2009

---

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN