

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BOND + SEAL BLACK - 600 ML  
Product code : 0890100183  
Unique Formula Identifier (UFI) : EFX1-G0PJ-U00D-HTPP

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives, Sealant  
Professional use product  
Recommended restrictions on use : May only be used by trained personnel.

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
Telephone : +49 794015 0  
Telefax : +49 794015 10 00  
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1      H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity - repeated exposure, Category 2      H373: May cause damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)


# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	:	<b>Prevention:</b> P260 Do not breathe vapours. P284 Wear respiratory protection. <b>Response:</b> P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
4,4'-Diphenylmethane diisocyanate  
m-Tolyldiene diisocyanate

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).  
Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Methylene-bis-4,1-(N-phenylene-N'-butylurea)	77703-56-1 416-600-4 01-0000016345-72	Aquatic Chronic 4; H413	>= 2,5 - < 10
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412  Acute toxicity estimate  Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 1 - < 2,5
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1  01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2,5
Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317	>= 0,1 - < 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

		Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract)	
		specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	
m-Tolylidene diisocyanate	26471-62-5 247-722-4 615-006-00-4 01-2119454791-34	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 0,0025 - < 0,025
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 0,24 mg/l	

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause damage to organs through prolonged or repeated exposure.
- Respiratory symptoms, including pulmonary edema, may be delayed.  
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray in large fire situations
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Metal oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Chlorine compounds

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapours.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from water.  
Protect from moisture.  
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Do not eat, drink or smoke when using this product.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Protect from moisture. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases

Storage class (TRGS 510) : 10

Storage period : 12 Months

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Polyvinyl chloride	9002-86-2	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
Xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: Skin absorption		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	AGW	300 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: Group exposure limit for hydrocarbon solvent mixtures		
		AGW	50 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: Group exposure limit for hydrocarbon solvent mixtures		
Titanium dioxide; [in powder form containing 1 % or	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]				
Peak-limit: excursion factor (category): 2;(II)				
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
4,4'-Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m <sup>3</sup>	TRGS 430
Peak-limit: excursion factor (category): 1;=2=(I)				
Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance				
		AGW (Vapour and aerosols, inhalable fraction)	0,05 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category): 1;=2=(I)				
Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system				
m-Tolyldiene diisocyanate	26471-62-5	AGW	0,005 ppm 0,035 mg/m <sup>3</sup>	TRGS 430
Peak-limit: excursion factor (category): 1;=4=(I)				
Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance				
		AGW (Vapour and aerosols)	0,005 ppm 0,035 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category): 1;=4=(I)				
Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system				

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-	Workers	Inhalation	Long-term systemic	5,29 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version  
19.1

Revision Date:  
21.11.2022

SDS Number:  
10621481-00012

Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich			effects	
	Workers	Skin contact	Long-term systemic effects	41,67 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,3 mg/m3
	Consumers	Skin contact	Long-term systemic effects	20,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
Carbon black	Workers	Inhalation	Long-term local effects	0,5 mg/m3
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Workers	Inhalation	Long-term systemic effects	330 mg/m3
	Workers	Skin contact	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	71 mg/m3
	Consumers	Skin contact	Long-term systemic effects	26 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg bw/day
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local effects	0,05 mg/m3
	Workers	Inhalation	Acute local effects	0,1 mg/m3
	Consumers	Inhalation	Long-term local effects	0,025 mg/m3
	Consumers	Inhalation	Acute local effects	0,05 mg/m3
Methylene-bis-4,1-(N-	Workers	Inhalation	Long-term systemic	49,37 mg/m3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

phenylene-N'-butylurea)			effects	
	Workers	Skin contact	Long-term systemic effects	140 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	7,4 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
m-Tolyldiene diisocyanate	Workers	Inhalation	Long-term systemic effects	0,035 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	0,14 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,035 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,14 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Carbon black	Fresh water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Marine water	0,1 mg/l
	Marine water - intermittent	1 mg/l
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
4,4'-Diphenylmethane diisocyanate	Fresh water	1 mg/l
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg
Methylene-bis-4,1-(N-phenylene-N'-butylurea)	Fresh water	0,1 mg/l
	Freshwater - intermittent	1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	76,36 mg/kg dry weight (d.w.)
	Marine sediment	7,636 mg/kg dry weight (d.w.)
	Soil	15,15 mg/kg dry weight (d.w.)
m-Tolyldiene diisocyanate	Fresh water	0,0125 mg/l
	Marine water	0,00125 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

	Intermittent use/release	0,125 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety glasses  
Equipment should conform to DIN EN 166

#### Hand protection

Material : Fluorinated rubber  
Break through time : > 30 min  
Glove thickness : 0,4 mm  
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : paste  
Colour : black

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 76 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : No data available

Relative density : No data available

Density : ca. 1,26 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

Evaporation rate : No data available

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Polymerises at high temperatures with evolution of carbon dioxide.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.  
Vapours may form explosive mixture with air.  
Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate.  
Exothermic reaction with acids, amines and alcohols  
Reacts with water to form carbon dioxide and heat  
Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea.  
Hazardous decomposition products will be formed upon contact with water or humid air.

#### 10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture  
Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents  
Acids  
Bases  
Water  
Alcohols  
Amines  
Ammonia  
Aluminium  
Zinc  
Brass  
Tin  
Copper  
Galvanised metals  
Humid air

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

##### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

##### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Acute oral toxicity : LD50 (Rat): > 15.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Acute inhalation toxicity : LC50 (Rat): > 13,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 3.400 mg/kg

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

### **4,4'-Diphenylmethane diisocyanate:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Remarks: Based on data from similar materials

### **m-Tolylidene diisocyanate:**

Acute oral toxicity : LD50 (Rat, female): 4.130 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,48 mg/l  
Exposure time: 1 h  
Test atmosphere: vapour  
  
Acute toxicity estimate: 0,24 mg/l  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit): > 9.400 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Species : Rabbit  
Method : OECD Test Guideline 404



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Result : No skin irritation

### **Xylene:**

Species : Rabbit  
Result : Skin irritation

### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rabbit  
Result : No skin irritation

### **4,4'-Diphenylmethane diisocyanate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

### **m-Tolyldiene diisocyanate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

### **Xylene:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rabbit  
Result : No eye irritation

### **4,4'-Diphenylmethane diisocyanate:**

Result : Irritation to eyes, reversing within 7 days  
Remarks : Based on national or regional regulation.

### **m-Tolylidene diisocyanate:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### **Components:**

#### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Xylene:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

### 4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation  
Species : Rat  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on animal testing

### m-Tolylidene diisocyanate:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : inhalation (vapour)  
Species : Guinea pig  
Result : positive

Assessment : Probability of respiratory sensitisation in humans based on animal testing

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Methylene-bis-4,1-(N-phenylene-N'-butylurea):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Skin contact

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Method: OECD Test Guideline 474  
Result: negative

### Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

### 4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 474  
Result: negative

### **m-Tolylidene diisocyanate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Xylene:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 105 weeks  
Result : negative  
Remarks : Based on data from similar materials

#### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

#### **4,4'-Diphenylmethane diisocyanate:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **m-Tolylidene diisocyanate:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rabbit  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

#### **Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

### **4,4'-Diphenylmethane diisocyanate:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Result: negative  
Remarks: Based on data from similar materials

### **m-Tolylidene diisocyanate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **Xylene:**

Assessment : May cause respiratory irritation.

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : May cause drowsiness or dizziness.

### **4,4'-Diphenylmethane diisocyanate:**

Assessment : May cause respiratory irritation.

### **m-Tolylidene diisocyanate:**

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **Xylene:**

Exposure routes : inhalation (vapour)  
Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Exposure routes : Inhalation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Target Organs : Central nervous system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

### **4,4'-Diphenylmethane diisocyanate:**

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

### **Repeated dose toxicity**

#### **Components:**

##### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Species : Rat  
NOAEL : >= 1.000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 407

##### **Xylene:**

Species : Rat  
LOAEL : > 0,2 - 1 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

##### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Species : Rat  
NOAEL : 1.056 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 3,950 mg/l  
LOAEL : 7,400 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days

##### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]:**

Species : Rat  
NOAEL : 24.000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 yr

### 4,4'-Diphenylmethane diisocyanate:

Species : Rat  
NOAEL : 0,2 mg/m<sup>3</sup>  
LOAEL : 1 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 yr  
Remarks : Based on data from similar materials

### m-Tolylidene diisocyanate:

Species : Rat, female  
LOAEL : 0,000362 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 113 Weeks

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Experience with human exposure

#### Components:

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Inhalation : Symptoms: central nervous system effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 250 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- NOELR (Desmodesmus subspicatus (green algae)): 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC (activated sludge): 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

##### **Xylene:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h
- Toxicity to microorganisms : NOEC : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l  
Exposure time: 35 d  
Species: Danio rerio (zebra fish)  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other : EL10: > 1 - 10 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

aquatic invertebrates (Chronic toxicity)      Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Toxicity to fish      :    LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates      :    EL50 (Daphnia magna (Water flea)): > 10 - 22 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants      :    EL50 (Pseudokirchneriella subcapitata (green algae)): 4,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,76 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      :    NOEC: 0,097 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:

Toxicity to fish      :    LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates      :    EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants      :    EC50 (Skeletonema costatum (marine diatom)): > 10.000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms      :    EC50 : > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### 4,4'-Diphenylmethane diisocyanate:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

- Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 129,7 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50 : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **m-Tolylidene diisocyanate:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 133 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): 18,3 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 4.300 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **Ecotoxicology Assessment**

- Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

### 12.2 Persistence and degradability

#### Components:

##### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 11 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### **Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 75,9 %  
Exposure time: 31 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **4,4'-Diphenylmethane diisocyanate:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302  
Remarks: Based on data from similar materials

##### **m-Tolyldiene diisocyanate:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d

Stability in water : Degradation half life (DT50): 30 s

### 12.3 Bioaccumulative potential

#### Components:

##### **Methylene-bis-4,1-(N-phenylene-N'-butylurea):**

Partition coefficient: n-octanol/water : log Pow: 5,5  
Method: OECD Test Guideline 107

##### **Xylene:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

Partition coefficient: n-octanol/water : log Pow: 3,16  
Remarks: Calculation

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Partition coefficient: n-octanol/water : Pow: > 4

### 4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 200

Partition coefficient: n-octanol/water : log Pow: 4,51

### m-Tolylidene diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 3,43

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product  
08 05 01, waste isocyanates

unused product  
08 05 01, waste isocyanates

uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

---

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)  
4,4'-Diphenylmethane diisocyanate (Number on list 74, 56)  
m-Tolyldiene diisocyanate (Number on list 74, 56)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Water hazard class (Germany) : WGK 1 slightly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 3,42 %, 48,3 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

TRGS 430 (German regulatory requirements)

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer.
H351	: Suspected of causing cancer if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version 19.1      Revision Date: 21.11.2022      SDS Number: 10621481-00012      Date of last issue: 01.03.2022  
Date of first issue: 11.06.2010

H411 : exposure if inhaled.  
H412 : Toxic to aquatic life with long lasting effects.  
H413 : Harmful to aquatic life with long lasting effects.  
EUH066 : May cause long lasting harmful effects to aquatic life.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Resp. Sens. : Respiratory sensitisation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 430 : Germany. TRGS 430 - Isocyanates  
TRGS 903 : TRGS 903 - Biological limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
DE TRGS 527 / BM : Assessment scale  
DE TRGS 900 / AGW : Time Weighted Average  
TRGS 430 / AGW : Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BOND + SEAL BLACK - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2022
19.1	21.11.2022	10621481-00012	Date of first issue: 11.06.2010

---

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Observe requirements and guidance related to training before using this product at work.

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Resp. Sens. 1	H334
STOT RE 2	H373

### Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN