

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DIESEL-INJECTION-CLEANER - 300 ML
Product code : 5861011300
Unique Formula Identifier (UFI) : NRJ4-T0AG-W002-X3HS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Fuels and fuel additives
Professional use product
Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau
Telephone : +49 794015 0
Telefax : +49 794015 10 00
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-ways.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

|| This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

|| Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

|| Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version
18.0

Revision Date:
13.04.2023

SDS Number:
10781773-00015

Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

	EC-No. Index-No. Registration number		(% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 70 - < 90
2-Ethylhexyl nitrate	27247-96-7 248-363-6 01-2119539586-27	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Aquatic Chronic 2; H411 EUH044, EUH066 Acute toxicity estimate Acute oral toxicity: 500 mg/kg Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 2,5 - < 10
2-Ethylhexan-1-ol	104-76-7 203-234-3 01-2119487289-20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 10
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8 203-749-3 01-2119488991-20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 M-Factor (Acute aquatic toxicity): 1 Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,01 mg/l	>= 1 - < 2,5
Heptadecenyl imidazoline ethanol	95-38-5 202-414-9 01-2119777867-13	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 STOT RE 2; H373 (Gastrointestinal tract, thymus gland) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

		EUH071	
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
		Acute toxicity estimate	
		Acute oral toxicity: 1.265 mg/kg	
Morpholine	110-91-8 203-815-1 613-028-00-9 01-2119496057-30	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318 Repr. 2; H361fd	>= 0,1 - < 1
		Acute toxicity estimate	
		Acute oral toxicity: 1.900 mg/kg Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 500 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.
Causes serious eye irritation.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

- Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases
- Storage class (TRGS 510) : 10

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	AGW	300 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
Further information: Group exposure limit for hydrocarbon solvent mixtures				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 4;(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
2-Ethylhexan-1-ol	104-76-7	TWA	1 ppm 5,4 mg/m ³	2017/164/EU
Further information: Indicative				
		AGW (Vapour and aerosols)	10 ppm 54 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 1;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	AGW (Inhalable fraction)	0,05 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
Morpholine	110-91-8	TWA	10 ppm 36 mg/m ³	2006/15/EC
Further information: Indicative				
		STEL	20 ppm 72 mg/m ³	2006/15/EC
Further information: Indicative				
		AGW	5 ppm 18 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 1;=2=(I)				
Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Ethylhexan-1-ol	Workers	Inhalation	Long-term systemic effects	12,8 mg/m ³
	Workers	Inhalation	Long-term local effects	53,2 mg/m ³
	Workers	Inhalation	Acute local effects	53,2 mg/m ³
	Workers	Skin contact	Long-term systemic effects	23 mg/kg bw/day
	Workers	Inhalation	Acute local effects	106,4 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2,3 mg/m ³
	Consumers	Inhalation	Long-term local effects	26,6 mg/m ³
	Consumers	Inhalation	Acute local effects	26,6 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	11,4 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,1 mg/kg bw/day
Heptadecenyl imidaz-	Workers	Inhalation	Long-term systemic	0,46 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version
18.0

Revision Date:
13.04.2023

SDS Number:
10781773-00015

Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Substance	Exposure	Route	Effects	Limit Value
Diethylhexyl nitrate	Workers	Inhalation	Acute systemic effects	14 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,06 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	2 mg/kg bw/day
2-Ethylhexyl nitrate	Workers	Inhalation	Long-term systemic effects	0,35 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0,44 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,087 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,52 mg/kg bw/day
	Consumers	Ingestion	Long-term local effects	0,025 mg/kg bw/day
Morpholine	Workers	Inhalation	Long-term local effects	36 mg/m ³
	Workers	Inhalation	Acute local effects	72 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,84 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Oral (Secondary Poisoning)	9,33 mg/kg food
	Fresh water	0,017 mg/l
	Intermittent use/release	0,17 mg/l
	Marine water	0,002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,284 mg/kg dry weight (d.w.)
	Marine sediment	0,028 mg/kg dry weight (d.w.)
Heptadecenyl imidazoline ethanol	Soil	0,047 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	55 mg/kg food
	Fresh water	0,0003 mg/l
	Marine water	0,000003 mg/l
	Intermittent use/release	0,0003 mg/l
	Sewage treatment plant	0,27 mg/l
	Fresh water sediment	0,376 mg/kg
2-Ethylhexyl nitrate	Marine water	0,0376 mg/kg
	Soil	0,075 mg/kg
	Fresh water	0,0008 mg/l
	Marine sediment	0,00008 mg/l
	Sewage treatment plant	10 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

	Fresh water sediment	0,00074 mg/l
	Marine sediment	0,00074 mg/l
	Soil	0,000191 mg/l
Morpholine	Fresh water	0,163 mg/l
	Freshwater - intermittent	0,45 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,83 mg/kg dry weight (d.w.)
	Marine sediment	0,183 mg/kg dry weight (d.w.)
	Soil	0,269 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,45 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

|| Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 100 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 0,5 %(V)

Flash point : 62 °C
Method: ISO 3679

Auto-ignition temperature : 215 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity
Viscosity, kinematic : 2,11 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : No data available

Density : 0,831 g/cm³ (20 °C)
Method: DIN 51757

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): >= 3.160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Acute oral toxicity : LD50 (Rat): > 9.600 mg/kg

Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Test atmosphere: vapour
Method: Expert judgement

Acute dermal toxicity : LD50 (Rabbit): > 4.800 mg/kg

Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement

2-Ethylhexan-1-ol:

Acute oral toxicity : LD50 (Rat): 2.047 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0,89 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 3.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 1 - 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Acute oral toxicity : LD50 (Rat): 1.265 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Morpholine:

Acute oral toxicity : LD50 (Rat): 1.900 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit, male): 500 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Ethylhexyl nitrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Morpholine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Result : Irreversible effects on the eye
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Species : Rabbit
Result : Irreversible effects on the eye

Morpholine:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Test Type : Maurer optimisation test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Morpholine:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative
- Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

2-Ethylhexyl nitrate:

- Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
- Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

2-Ethylhexan-1-ol:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials
- Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Morpholine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Hamster
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

2-Ethylhexan-1-ol:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Morpholine:

Species : Rat
Application Route : inhalation (vapour)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Exposure time : 104 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

2-Ethylhexyl nitrate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

2-Ethylhexan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

ment

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Morpholine:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments., Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

2-Ethylhexan-1-ol:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Components:

2-Ethylhexan-1-ol:

Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Heptadecenyl imidazoline ethanol:

Exposure routes : Ingestion
Target Organs : Gastrointestinal tract, thymus gland
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
NOAEL : >= 1.000 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Species : Rabbit
NOAEL : 500 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

2-Ethylhexan-1-ol:

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : 0,6384 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Heptadecenyl imidazoline ethanol:

Species : Rat
NOAEL : 20 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 31 - 51 Days
Method : OECD Test Guideline 422

Morpholine:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 18 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : 0,543 mg/l
Application Route : inhalation (vapour)
Exposure time : 104 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 12,6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 3,22 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 1,54 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

2-Ethylhexan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 28,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 16,6 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

EC10 (Desmodesmus subspicatus (green algae)): 16,6 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,43 mg/l
Exposure time: 96 h
Test substance: Neutralised product
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,1 - 1 mg/l
Exposure time: 48 h
Test substance: Neutralised product
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): > 0,1 - 1 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : NOEC : > 1 mg/l
Exposure time: 3 h
Test substance: Neutralised product
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,3 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,163 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0,03 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC10 (Desmodesmus subspicatus (green algae)): 0,014 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 10
- Toxicity to microorganisms : IC50 : 26 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- M-Factor (Chronic aquatic toxicity) : 1
- Morpholine:**
- Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44,5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 64,63 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC10 (Raphidocelis subcapitata (freshwater green alga)): 31,49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 30 min
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 8,134 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

12.2 Persistence and degradability

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 310

2-Ethylhexan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 - 99,9 %
Exposure time: 14 d

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Heptadecenyl imidazoline ethanol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Morpholine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 93 %
Exposure time: 25 d
Method: OECD Test Guideline 301E

12.3 Bioaccumulative potential

Components:

2-Ethylhexyl nitrate:

Partition coefficient: n-octanol/water : log Pow: 5,24

2-Ethylhexan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 2,9

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

octanol/water

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Partition coefficient: n-octanol/water : log Pow: < 4

Morpholine:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 2,8
Method: OECD Test Guideline 305C

Partition coefficient: n-octanol/water : log Pow: -2,55
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Waste Code

: The following Waste Codes are only suggestions:

used product

07 07 04, other organic solvents, washing liquids and mother liquors

unused product

07 07 04, other organic solvents, washing liquids and mother liquors

uncleaned packagings

15 01 10, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:

Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Not applicable

Water hazard class (Germany) : WGK 3 highly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 90,51 %, 752 g/l
Remarks: VOC content excluding water

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H361fd : Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH044 : Risk of explosion if heated under confinement.
EUH066 : Repeated exposure may cause skin dryness or cracking.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version 18.0 Revision Date: 13.04.2023 SDS Number: 10781773-00015 Date of last issue: 08.02.2023
Date of first issue: 28.11.2011

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
2006/15/EC / TWA : Limit Value - eight hours
2006/15/EC / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Asp. Tox. 1 H304

Classification procedure:

Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DIESEL-INJECTION-CLEANER - 300 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
18.0	13.04.2023	10781773-00015	Date of first issue: 28.11.2011

Eye Irrit. 2	H319	Calculation method
Aquatic Chronic 3	H412	Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN