

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : VARIOPRIMER - 20 ML
Product code : 0890024021
Unique Formula Identifier (UFI) : EXN2-30HK-3002-U8CK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Primers
Professional use product

Recommended restrictions on use : May only be used by trained personnel.

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau
Telephone : +49 794015 0
Telefax : +49 794015 10 00
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex-	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Ethyl acetate
Butanone
Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol
4,4'-Diphenylmethane diisocyanate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
Butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidenetri-methanol	53317-61-6	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	26115-70-8 247-465-8	Acute Tox. 4; H302 STOT SE 2; H371 (Central nervous system, optic nerve) Acute toxicity estimate Acute oral toxicity: > 300 - 2.000 mg/kg	>= 1 - < 10
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334	>= 0,1 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

			Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract)
			specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

Respiratory symptoms, including pulmonary edema, may be delayed.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray in large fire situations

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Silicon oxides
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local cir-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

ods cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Protect from moisture. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Explosives
Gases
Very acutely toxic substances and mixtures

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017/164/EU
		Further information: Indicative		
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU
		Further information: Indicative		
		AGW	200 ppm 730 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Butanone	78-93-3	STEL	300 ppm 900 mg/m ³	2000/39/EC
		Further information: Indicative		
		TWA	200 ppm 600 mg/m ³	2000/39/EC
		Further information: Indicative		
		AGW	200 ppm 600 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 1;(I)		
		Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
4,4'-Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m ³	TRGS 430
		Peak-limit: excursion factor (category): 1;=2=(I)		
		Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance		
		AGW (Vapour and aerosols, inhalable fraction)	0,05 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 1;=2=(I)		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

	Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system
--	--

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 260 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m ³
	Workers	Inhalation	Acute systemic effects	1468 mg/m ³
	Workers	Inhalation	Long-term local effects	734 mg/m ³
	Workers	Inhalation	Acute local effects	1468 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic effects	734 mg/m ³
	Consumers	Inhalation	Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute local effects	734 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg bw/day
Butanone	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	600 mg/m ³
	Workers	Skin contact	Long-term systemic	1161 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	106 mg/m ³
	Workers	Skin contact	Long-term systemic effects	412 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	31 mg/kg bw/day
Carbon black	Workers	Inhalation	Long-term local effects	0,5 mg/m ³
Tris(p-isocyanatophenyl) thiophosphate	Workers	Inhalation	Long-term local effects	0,047 mg/m ³
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local effects	0,05 mg/m ³
	Workers	Inhalation	Acute local effects	0,1 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,025 mg/m ³
	Consumers	Inhalation	Acute local effects	0,05 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethyl acetate	Fresh water	0,24 mg/l
	Marine water	0,024 mg/l
	Intermittent use/release	1,65 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1,15 mg/kg dry weight (d.w.)
	Marine sediment	0,115 mg/kg dry weight (d.w.)
	Soil	0,148 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	200 mg/kg food
Butanone	Fresh water	55,8 mg/l
	Freshwater - intermittent	55,8 mg/l
	Marine water	55,8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284,74 mg/kg dry weight (d.w.)
	Marine sediment	284,7 mg/kg dry weight (d.w.)
	Soil	22,5 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	1000 mg/kg food
Carbon black	Fresh water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Marine water	0,1 mg/l
	Marine water - intermittent	1 mg/l
	Fresh water sediment	2557 mg/kg dry
Tris(p-isocyanatophenyl) thiophosphate	Fresh water	0,1 mg/l
	Freshwater - intermittent	1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	2557 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

		weight (d.w.)
	Marine sediment	155 mg/kg dry weight (d.w.)
	Soil	510 mg/kg dry weight (d.w.)
4,4'-Diphenylmethane diisocyanate	Fresh water	1 mg/l
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : < 10 min
Glove thickness : 0,4 mm
Directive : Equipment should conform to DIN EN 374

Material : butyl-rubber
Break through time : < 10 min
Glove thickness : 0,4 mm
Directive : Equipment should conform to DIN EN 374

Material : Viton®
Break through time : > 30 min
Glove thickness : 0,4 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : black

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 11,5 %(V)

Lower explosion limit / Lower flammability limit : 1,8 %(V)

Flash point : -4 °C

Auto-ignition temperature : 427 °C

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Viscosity

Viscosity, dynamic : ca. 15 mPa.s (20 °C)

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Vapour pressure	: 99,9915 hPa
Relative density	: No data available
Density	: ca. 0,97 g/cm ³ (20 °C)
Relative vapour density	: No data available
Particle characteristics	
Particle size	: Not applicable

9.2 Other information

Explosives	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Evaporation rate	: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Polymerises at high temperatures with evolution of carbon dioxide.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Highly flammable liquid and vapour. Vapours may form explosive mixture with air. Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols Reacts with water to form carbon dioxide and heat Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Hazardous decomposition products will be formed upon contact with water or humid air.
---------------------	--

10.4 Conditions to avoid

Conditions to avoid	: Exposure to moisture
---------------------	------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Acids
Bases
Water
Alcohols
Amines
Ammonia
Aluminium
Zinc
Brass
Tin
Copper
Galvanised metals
Humid air

10.6 Hazardous decomposition products

Contact with water or humid air : Methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Ethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22,5 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Butanone:

- Acute oral toxicity : LD50 (Rat): > 2.000 - 5.000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 25,5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol:

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 2,462 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

- Acute oral toxicity : Acute toxicity estimate (Humans): > 300 - 2.000 mg/kg
Method: Expert judgement
Remarks: Based on data from similar materials
- LD50 (Rat, female): 1.651 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

4,4'-Diphenylmethane diisocyanate:

- Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Components:

Ethyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy- lidenetrimethanol:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

Species : Rabbit
Result : No skin irritation

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Butanone:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy- lidenetrimethanol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

Species : Rabbit
Result : No eye irritation

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Ethyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Butanone:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol:

Exposure routes : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation
Species : Rat
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on animal testing

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Hamster
Application Route: Ingestion
Result: negative

Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene-trimethanol:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

Ethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Species: Rat
Application Route: inhalation (vapour)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

4,4'-Diphenylmethane diisocyanate:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Ethyl acetate:

Assessment : May cause drowsiness or dizziness.

Butanone:

Assessment : May cause drowsiness or dizziness.

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

Exposure routes : Ingestion
Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity

Components:

Ethyl acetate:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 3.600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 1,28 mg/l
LOAEL : 2,75 mg/kg
Application Route : inhalation (vapour)
Exposure time : 94 Days

Butanone:

Species : Rat
NOAEL : 14,84 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

4,4'-Diphenylmethane diisocyanate:

Species : Rat
NOAEL : 0,2 mg/m³
LOAEL : 1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 yr
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Components:

Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

Components:

Ethyl acetate:

Eye contact : Target Organs: Eye
Symptoms: Irritation

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.090 mg/l
Exposure time: 24 h
Method: DIN 38412

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1.650 mg/l
Exposure time: 0,25 h

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 9,65 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic) : NOEC: 2,4 mg/l
Exposure time: 24 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

ic toxicity) Species: Daphnia magna (Water flea)

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 308 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2.029
plants mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.240
mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy- lidenetrimethanol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to daphnia and other : (Daphnia magna (Water flea)): Exposure time: 48 h
aquatic invertebrates Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to algae/aquatic : (Scenedesmus subspicatus): Exposure time: 72 h
plants Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10.000 mg/l
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

plants Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 : 270 mg/l
Exposure time: 3 h
Remarks: Based on data from similar materials

4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 129,7 mg/l
aquatic invertebrates Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): > 1.640
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC: 10 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %
Exposure time: 20 d

Butanone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propy- lidenetriethanol:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

1,3,5-Tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Ethyl acetate:

Bioaccumulation : Species: *Leuciscus idus* (Golden orfe)
Bioconcentration factor (BCF): 30

Partition coefficient: n-
octanol/water : log Pow: 0,68

Butanone:

Partition coefficient: n-
octanol/water : log Pow: 0,3

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: *Cyprinus carpio* (Carp)
Bioconcentration factor (BCF): 200

Partition coefficient: n-
octanol/water : log Pow: 4,51

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
 - used product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
 - unused product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
 - uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substancesAcc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1866
ADR : UN 1866
RID : UN 1866
IMDG : UN 1866
IATA : UN 1866

14.2 UN proper shipping name

ADN : RESIN SOLUTION
ADR : RESIN SOLUTION
RID : RESIN SOLUTION
IMDG : RESIN SOLUTION
IATA : Resin solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG
Packing group : II

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : If you intend to use this product as tattoo ink, please contact your vendor.

4,4'-Diphenylmethane diisocyanate
(Number on list 74, 56)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 68,15 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

TRGS 430 (German regulatory requirements)

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H334 : May cause allergy or asthma symptoms or breathing difficul-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version 12.0 Revision Date: 01.03.2023 SDS Number: 10626263-00013 Date of last issue: 15.11.2022
Date of first issue: 11.06.2010

H335 : ties if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer.
H371 : May cause damage to organs.
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitisation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC : Europe. Indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430 : Germany. TRGS 430 - Isocyanates
TRGS 903 : TRGS 903 - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2006/15/EC / TWA : Limit Value - eight hours
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
DE TRGS 900 / AGW : Time Weighted Average
TRGS 430 / AGW : Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



VARIOPRIMER - 20 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2022
12.0	01.03.2023	10626263-00013	Date of first issue: 11.06.2010

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Observe requirements and guidance related to training before using this product at work.

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 2	H225
Resp. Sens. 1	H334
Skin Sens. 1	H317
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN