

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : POWER 5 MULTIPURPOSE 200 ML

Product code : 9500000033

Manufacturer or supplier's detailsCompany : Wuerth (Thailand) Co. Ltd.
777 WHA TOWER, 14th FloorAddress : Moo 13, Debaratna(Bangna-Trad) Road KM.7
Bang Kaeo, Bang Phli, Samut Prakan 10540

Telephone : +66 21705000

Emergency telephone number : Emergency call +66 21705000.

E-mail address : prodsafe@wuerth.com

Telefax : +66 21705050

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use :
Not applicable

2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin corrosion/irritation : Category 3





Specific target organ toxicity - : Category 3
single exposure

Aspiration hazard : Category 1

GHS label elements

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
 Date of first issue: 01/31/2017

- Hazard pictograms :    
- Signal word : Danger
- Hazard statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H316 Causes mild skin irritation.
 H336 May cause drowsiness or dizziness.
- Precautionary statements : **Prevention:**
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
- Response:**
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- Storage:**
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
- Disposal:**
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 50 -< 70
Liquified petroleum gas (LPG)	68476-85-7	>= 50 -< 70

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
Date of first issue: 01/31/2017

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes mild skin irritation.
May cause drowsiness or dizziness.
Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion prod- : Carbon oxides
-

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

ucts

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

- Advice on safe handling** : Do not get on skin or clothing.
 Avoid breathing spray.
 Do not swallow.
 Avoid contact with eyes.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep container tightly closed.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.
 Do not spray on an open flame or other ignition source.
- Conditions for safe storage** : Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.
- Materials to avoid** : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable liquids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Explosives

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Liquefied petroleum gas (LPG)	68476-85-7	TWA	1,000 ppm	TH OEL

- Engineering measures** : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
Date of first issue: 01/31/2017

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber

Break through time : > 480 min

Glove thickness : > 0.4 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Liquefied petroleum gas (LPG)

Colour : brown

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : 6.2

Melting point/freezing point : No data available

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

Initial boiling point and boiling range : Not applicable

Flash point : 36 °C
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Relative density : 0.8

Density : ca. 0.80 g/cm³ (20 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : 22 mm²/s (40 °C)
Distillates (petroleum), hydrotreated light naphthenic

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : Extremely flammable aerosol.

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

tions	Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 4,951 mg/m ³ Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): >= 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Acute inhalation toxicity	: LC50 (Mouse): 520400 ppm Exposure time: 2 h Test atmosphere: gas Remarks: Based on data from similar materials
---------------------------	---

Skin corrosion/irritation

Causes mild skin irritation.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Species	: Rabbit
Result	: Mild skin irritation

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
Date of first issue: 01/31/2017

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Liquified petroleum gas (LPG):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
Date of first issue: 01/31/2017

cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Liquified petroleum gas (LPG):

Species : Mouse
Application Route : inhalation (gas)
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:**Liquified petroleum gas (LPG):**

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

POWER 5 MULTIPURPOSE 200 ML

Version 1.8 Revision Date: 11/10/2022 SDS Number: 10790017-00005 Date of last issue: 06/09/2022
Date of first issue: 01/31/2017

Repeated dose toxicity**Components:****Naphtha (petroleum), hydrotreated heavy:**

Species : Rat
NOAEL : $\geq 1,000$ mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Remarks : Based on data from similar materials

Liquified petroleum gas (LPG):

Species : Rat
NOAEL : 10000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:**Naphtha (petroleum), hydrotreated heavy:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Naphtha (petroleum), hydrotreated heavy:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): $> 1,000$ mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): $> 1,000$ mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): $> 1,000$ mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)):
1,000 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Naphtha (petroleum), hydrotreated heavy:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %

Bioaccumulative potential**Components:****Liquified petroleum gas (LPG):**

Partition coefficient: n-octanol/water : log Pow: 1.09

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or ex-

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

pose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

14. TRANSPORT INFORMATION
International Regulations
UNRTDG

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1

IATA-DGR

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION
Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act	:	Conditions of restriction for the following entries should be considered: liquefied petroleum gas
-------------------------	---	---

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

(List 6, Number on list 2)

Emergency Decree on Controlling the Use of Volatile Substances : Not applicable

16. OTHER INFORMATION

Revision Date : 11/10/2022

Further informationSources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : yyyy/mm/dd

Full text of other abbreviationsACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure LimitsACGIH / TWA : 8-hour, time-weighted average
TH OEL / TWA : Time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substances Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

POWER 5 MULTIPURPOSE 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.8	11/10/2022	10790017-00005	Date of first issue: 01/31/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

TH / EN