

1K PUR Mounting Foam, B2

Version Revision Date: SDS Number: Date of last issue: 11/15/2022
5.9 05/22/2023 10710748-00008 Date of first issue: 02/05/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 1K PUR Mounting Foam, B2

Product code : 892155210

Manufacturer or supplier's details

Company : Wurth Lanka (PVT) LTD

Address : 375/B, High Level Road
Makumbura, Pannipitya, Sri Lanka

Telephone : 0094-112894930

Emergency telephone number : 0094-777328880

E-mail address : prodsafe@wuerth.com

Telefax : 0094-112894955

Recommended use of the chemical and restrictions on use

Recommended use : Sealant
Construction material

2. HAZARDS IDENTIFICATION**GHS Classification**

Aerosols : Category 1

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2B

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Effects on or via lactation

Specific target organ toxicity - single exposure : Category 3

Specific target organ toxicity - : Category 2 (Respiratory Tract)

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
 Date of first issue: 02/05/2013

repeated exposure (Inhalation)

Long-term (chronic) aquatic hazard : Category 4

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 + H320 Causes skin and eye irritation.
 H317 May cause an allergic skin reaction.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H362 May cause harm to breast-fed children.
 H373 May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.
 H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements :

Prevention:

P203 Obtain, read and follow all safety instructions before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P263 Avoid contact during pregnancy and while nursing.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
 P304 + P340 + P317 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P318 IF exposed or concerned, get medical advice.

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

P333 + P317 If skin irritation or rash occurs: Get medical help.
P337 + P317 If eye irritation persists: Get medical help.
P342 + P316 If experiencing respiratory symptoms: Get emergency medical help immediately.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

May displace oxygen and cause rapid suffocation.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethane diisocyanate, isomers and homologues	9016-87-9	>= 30 - < 50
Isobutane	75-28-5	>= 5 - < 10
Tris(2-chloro-1-methylethyl) phosphate	13674-84-5	>= 5 - < 10
alkanes, C14-17, chloro	85535-85-9	>= 5 - < 10
Dimethyl ether	115-10-6	>= 1 - < 5
Propane	74-98-6	>= 1 - < 5
4,4'-Diphenylmethane diisocyanate	101-68-8	>= 0.1 - < 1

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

- Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin and eye irritation.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause harm to breast-fed children.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Gas reduces oxygen available for breathing.
Respiratory symptoms, including pulmonary edema, may be delayed.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray in large fire situations
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Oxides of phosphorus
Chlorine compounds
Nitrogen oxides (NO_x)

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

Isocyanates
Hydrogen cyanide (hydrocyanic acid)

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Avoid contact during pregnancy and while nursing.
Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Do not breathe decomposition products.
- Conditions for safe storage : Store locked up.
Protect from moisture.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Explosives

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
 Date of first issue: 02/05/2013

		(Form of exposure)	ters / Permissible concentration	
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
4,4'-Diphenylmethane diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10). Minimize workplace exposure concentrations. If sufficient ventilation is unavailable, use with local exhaust ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Polyethylene
 Break through time : < 30 min
 Glove thickness : 0.025 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment:
 If assessment demonstrates that there is a risk of explosive

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

atmospheres or flash fires, use flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Propellant : Isobutane, Propane, Butane, Dimethyl ether

Colour : opaque

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

Relative density	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	199 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions. Polymerises at high temperatures with evolution of carbon dioxide.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols Reacts with water to form carbon dioxide and heat Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Hazardous decomposition products will be formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	Exposure to moisture Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Acids

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Bases
Water
Alcohols
Amines
Ammonia
Aluminium
Zinc
Brass
Tin
Copper
Galvanised metals
Humid air

Hazardous decomposition products

Thermal decomposition : Formaldehyde
Methanol

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 2.97 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Exposure time: 4 h
Test atmosphere: gas

Tris(2-chloro-1-methylethyl) phosphate:

Acute oral toxicity : LD50 (Rat): 931 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

alkanes, C14-17, chloro:

Acute oral toxicity : LD50 (Rat): > 4,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

1K PUR Mounting Foam, B2

Version Revision Date: SDS Number: Date of last issue: 11/15/2022
5.9 05/22/2023 10710748-00008 Date of first issue: 02/05/2013

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rabbit
Result : Skin irritation

Tris(2-chloro-1-methylethyl) phosphate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

alkanes, C14-17, chloro:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes eye irritation.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Result : Irritation to eyes, reversing within 7 days

Tris(2-chloro-1-methylethyl) phosphate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

alkanes, C14-17, chloro:

Species : Rabbit
Result : No eye irritation

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : inhalation (dust/mist/fume)
Species : Rat
Result : positive

Assessment : Probability of respiratory sensitisation in humans based on animal testing

Tris(2-chloro-1-methylethyl) phosphate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

alkanes, C14-17, chloro:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation
Species : Rat
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on animal testing

Germ cell mutagenicity

Not classified based on available information.

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Isobutane:

- Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Tris(2-chloro-1-methylethyl) phosphate:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive
- Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

alkanes, C14-17, chloro:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

4,4'-Diphenylmethane diisocyanate:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

May cause harm to breast-fed children.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Tris(2-chloro-1-methylethyl) phosphate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

ment

Species: Rat
 Application Route: Ingestion
 Result: negative

alkanes, C14-17, chloro:

Effects on fertility : Test Type: One-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 421
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rabbit
 Application Route: Ingestion
 Result: negative

Reproductive toxicity - Assessment : Studies indicating a hazard to babies during the lactation period
 Remarks: Based on national or regional regulation.

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: inhalation (vapour)
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: inhalation (vapour)
 Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: inhalation (gas)
 Method: OECD Test Guideline 422
 Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: inhalation (gas)
 Method: OECD Test Guideline 422
 Result: negative

4,4'-Diphenylmethane diisocyanate:

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: inhalation (dust/mist/fume)
 Result: negative

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

Remarks: Based on data from similar materials

STOT - single exposure

May cause respiratory irritation.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Assessment : May cause respiratory irritation.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Tris(2-chloro-1-methylethyl) phosphate:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

4,4'-Diphenylmethane diisocyanate:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity**Components:****Diphenylmethane diisocyanate, isomers and homologues:**

1K PUR Mounting Foam, B2

Version Revision Date: SDS Number: Date of last issue: 11/15/2022
5.9 05/22/2023 10710748-00008 Date of first issue: 02/05/2013

Species : Rat
NOAEL : 1.4 mg/m³
LOAEL : 4.1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Tris(2-chloro-1-methylethyl) phosphate:

Species : Rat
LOAEL : 52 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

alkanes, C14-17, chloro:

Species : Rat
NOAEL : 100 mg/kg
LOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Dimethyl ether:

Species : Rat
NOAEL : 47.11 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

4,4'-Diphenylmethane diisocyanate:

Species : Rat
NOAEL : 0,2 mg/m³
LOAEL : 1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 yr
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Scenedesmus capricornutum (fresh water algae)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 28 d
Species: Daphnia (water flea)
Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.
Remarks: Information given is based on data on the components and the ecotoxicology of similar products.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Tris(2-chloro-1-methylethyl) phosphate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 51 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 131 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 42 mg/l

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

- Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: 784 mg/l
Exposure time: 30 min
Method: ISO 8192
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
- alkanes, C14-17, chloro:**
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.0059 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 0.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- ErC50 (Pseudokirchneriella subcapitata (green algae)): > 3.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 100
- Toxicity to microorganisms : NOEC: 800 mg/l
Exposure time: 24 h
- Toxicity to fish (Chronic toxicity) : NOEC: 4.5 mg/l
Exposure time: 60 d
Species: Oncorhynchus mykiss (rainbow trout)
- M-Factor (Chronic aquatic toxicity) : 100
- Dimethyl ether:**
- Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4,400 mg/l
Exposure time: 48 h
- Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1,600 mg/l
- 4,4'-Diphenylmethane diisocyanate:**
- Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 129.7 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Desmodesmus subspicatus (green algae)): 1,640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Diphenylmethane diisocyanate, isomers and homologues:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Tris(2-chloro-1-methylethyl) phosphate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d

alkanes, C14-17, chloro:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 51 %
Exposure time: 28 d

1K PUR Mounting Foam, B2

Version 5.9 Revision Date: 05/22/2023 SDS Number: 10710748-00008 Date of last issue: 11/15/2022
Date of first issue: 02/05/2013

Method: OECD Test Guideline 301D

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

Tris(2-chloro-1-methylethyl) phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 0.8 - 4.6
Method: OECD Test Guideline 305C

Partition coefficient: n-octanol/water : log Pow: 2.68

alkanes, C14-17, chloro:

Partition coefficient: n-octanol/water : log Pow: > 4

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200

1K PUR Mounting Foam, B2

Version Revision Date: SDS Number: Date of last issue: 11/15/2022
5.9 05/22/2023 10710748-00008 Date of first issue: 02/05/2013

Partition coefficient: n-octanol/water : log Pow: 4.51

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****16. OTHER INFORMATION**

Revision Date : 05/22/2023

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

1K PUR Mounting Foam, B2

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
5.9	05/22/2023	10710748-00008	Date of first issue: 02/05/2013

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

LK / EN