

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

**SECTION 1: IDENTIFICATION**

Product name : SPRAY PAINT PRO GLOSS RAL9003 SIGNALWHITE 400ML

Product code : 0892 109 017

**Manufacturer or supplier's details**

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway  
Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National  
Poisons Centre: 131 126

E-mail address : product@wurth.com.au

**Recommended use of the chemical and restrictions on use**

Recommended use : Solvent-borne coatings

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Aerosols : Category 1

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Carcinogenicity : Category 2




Specific target organ toxicity - single exposure : Category 3

**GHS label elements**

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.
Precautionary statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. <b>Disposal:</b>

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Dimethyl ether	115-10-6	>= 20 -< 30
Dichloromethane	75-09-2	>= 20 -< 30
n-Butyl acetate	123-86-4	< 10
Acetone	67-64-1	< 10
Titanium dioxide	13463-67-7	>= 1 -< 10

---

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Chlorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 2YE

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages

---

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---



cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.  
  
Do not breathe decomposition products.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

Conditions for safe storage : Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Explosives

Recommended storage temperature : < 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dimethyl ether	115-10-6	TWA	400 ppm 760 mg/m <sup>3</sup>	AU OEL
		STEL	500 ppm 950 mg/m <sup>3</sup>	AU OEL
Dichloromethane	75-09-2	TWA	50 ppm 174 mg/m <sup>3</sup>	AU OEL
		Further information: Category 2 (Carc. 2) Suspected human carcinogen, Skin absorption		
n-Butyl acetate	123-86-4	TWA	50 ppm	ACGIH
		TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL
		TWA	50 ppm	ACGIH
Acetone	67-64-1	STEL	150 ppm	ACGIH
		STEL	1,000 ppm 2,375 mg/m <sup>3</sup>	AU OEL
		TWA	500 ppm 1,185 mg/m <sup>3</sup>	AU OEL

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	AU OEL

**Occupational exposure limits of decomposition products**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Chlorine	7782-50-5	Peak limit	1 ppm 3 mg/m <sup>3</sup>	AU OEL
		TWA	0.1 ppm	ACGIH
		STEL	0.4 ppm	ACGIH
Hydrogen chloride	7647-01-0	Peak limit	5 ppm 7.5 mg/m <sup>3</sup>	AU OEL
		C	2 ppm	ACGIH
		TWA	30 ppm 34 mg/m <sup>3</sup>	AU OEL
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	0.02 ppm 0.08 mg/m <sup>3</sup>	AU OEL
		STEL	0.06 ppm 0.25 mg/m <sup>3</sup>	AU OEL
Phosgene	75-44-5	C	0.02 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Dichloromethane	75-09-2	Dichloromethane	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

lation.

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : butyl-rubber
  - Break through time : > 120 min
  - Glove thickness : 0.1 mm
- Remarks : Wash hands before breaks and at the end of workday. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a liquefied gas
- Propellant : Dimethyl ether
- Colour : white
- Odour : solvent-like



**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	0.9 - 1 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

---

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : Not classified as a reactivity hazard.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.
- Conditions to avoid : Heat, flames and sparks.
- Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

- Thermal decomposition : Chlorine  
Hydrogen chloride  
Carbon monoxide  
Phosgene

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Dimethyl ether:**

- Acute inhalation toxicity : LC50 (Rat): 164000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Dichloromethane:**

- Acute oral toxicity : LD50 (Rat):  $\geq$  2,000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Mouse): 49 mg/l  
Exposure time: 7 h

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat):  $\geq 2,000$  mg/kg  
Method: OECD Test Guideline 402

**n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat):  $> 5,000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 21.1$  mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit):  $> 5,000$  mg/kg

**Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat):  $> 5,000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 6.82$  mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Dichloromethane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

**Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Titanium dioxide:**

Species : Rabbit  
Result : No skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Dichloromethane:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

**n-Butyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Acetone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

**Titanium dioxide:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Dichloromethane:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

**n-Butyl acetate:**

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative

**Acetone:**

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative

**Titanium dioxide:**

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Result	: negative

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Dimethyl ether:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---

	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
--	---

	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
--	--

Genotoxicity in vivo	: Test Type: Sex-linked recessive lethal test in <i>Drosophila melanogaster</i> (in vivo) Application Route: inhalation (gas) Result: negative
----------------------	--

**Dichloromethane:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: positive
-----------------------	--

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

Test Type: Bacterial reverse mutation assay (AMES)  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

**n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Components:****Dimethyl ether:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

**Dichloromethane:**

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 102 weeks  
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**Acetone:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

**Titanium dioxide:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Reproductive toxicity**

Not classified based on available information.

**Components:****Dimethyl ether:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**Dichloromethane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

**n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Dimethyl ether:**

Assessment : May cause drowsiness or dizziness.

**Dichloromethane:**

Assessment : May cause drowsiness or dizziness.

**n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Acetone:**

Assessment : May cause drowsiness or dizziness.



**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

**STOT - repeated exposure**

Not classified based on available information.

**Components:****Dichloromethane:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Repeated dose toxicity****Components:****Dimethyl ether:**

Species : Rat  
NOAEL : 47.11 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr

**Dichloromethane:**

Species : Rat  
NOAEL : 6 mg/kg  
Application Route : Ingestion  
Exposure time : 104 Weeks

Species : Rat  
NOAEL : 694 mg/l  
LOAEL : 1,736 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr

**n-Butyl acetate:**

Species : Rat  
NOAEL : 2.4 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days

**Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapour)

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Exposure time : 8 Weeks

**Titanium dioxide:**

Species : Rat  
NOAEL : 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 yr

**Aspiration toxicity**

Not classified based on available information.

**Components:****Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Dimethyl ether:**

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4,400 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1,600 mg/l

**Dichloromethane:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 193 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 27 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to fish (Chronic tox- : NOEC (Pimephales promelas (fathead minnow)): 83 mg/l  
icity) Exposure time: 28 d

Toxicity to microorganisms : EC50: 2,590 mg/l

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Exposure time: 40 min  
Method: OECD Test Guideline 209

**n-Butyl acetate:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (water flea)): 44 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

**Acetone:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 79 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50: 61,150 mg/l  
Exposure time: 30 min  
Method: ISO 8192

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version 5.0      Revision Date: 25.06.2024      SDS Number: 6283741-00007      Date of last issue: 11.06.2023  
Date of first issue: 21.08.2020

---

**Titanium dioxide:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h
- Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Persistence and degradability****Components:****Dimethyl ether:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Dichloromethane:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 68 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**n-Butyl acetate:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Acetone:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

**Bioaccumulative potential****Components:****Dimethyl ether:**

- Partition coefficient: n- : log Pow: 0.2

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

octanol/water

**Dichloromethane:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 40  
Method: OECD Test Guideline 305

Partition coefficient: n-  
octanol/water : log Pow: 1.25

**n-Butyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 2.3

**Acetone:**

Partition coefficient: n-  
octanol/water : log Pow: -0.27 - -0.23

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- |                        |  |
|------------------------|--|
| Waste from residues    | : Do not dispose of waste into sewer.<br><br>Dispose of in accordance with local regulations.  |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.<br>Empty containers retain residue and can be dangerous.<br>Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.<br>If not otherwise specified: Dispose of as unused product.<br>Please ensure aerosol cans are sprayed completely empty (including propellant) |

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Hazchem Code : 2YE  
Environmentally hazardous : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Therapeutic Goods (Poisons Standard) Instrument : No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 250 - 750 g/l

**The components of this product are reported in the following inventories:**

AIIC : All ingredients listed or exempt.

---

**SECTION 16: ANY OTHER RELEVANT INFORMATION****Further information**

Revision Date : 25.06.2024

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
ACGIH / C : Ceiling limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
AU OEL / Peak limit : Exposure standard - peak

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for

**SPRAY PAINT PRO GLOSS RAL9003  
SIGNALWHITE 400ML**

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2023
5.0	25.06.2024	6283741-00007	Date of first issue: 21.08.2020

---

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN