

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CONTACT SW - 200 ML

Product code : 089365

Manufacturer or supplier's details

Company : Wuerth India Pvt. Ltd.

Address : 703/704, Windfall, Sahar Plaza Complex
Andheri (East), Mumbai 400059

Telephone : +91 8828111830

Emergency telephone number : 1800 102 5061

E-mail address : customer.care@wuerth.in

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Detergent

Restrictions on use : Not applicable

2. HAZARDS IDENTIFICATION

Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

Classification

Flammable gas

GHS Classification

Aerosols : Category 1

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3

Aspiration hazard : Category 1

Short-term (acute) aquatic hazard : Category 2

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :    

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P316 IF SWALLOWED: Get emergency medical help immediately.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P332 + P317 If skin irritation occurs: Get medical help.
P337 + P317 If eye irritation persists: Get medical help.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014



P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 20 - < 30
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 20 - < 25
Butan-2-ol	78-92-2	>= 10 - < 20
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	>= 10 - < 20
1-Methoxy-2-propanol	107-98-2	>= 5 - < 10
Carbon dioxide	124-38-9	>= 1 - < 5
Butanone	78-93-3	>= 1 - < 5

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
8.0	08/30/2023	10772028-00013	Date of first issue: 08/05/2014

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for : Non-sparking tools should be used.

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

containment and cleaning up Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Explosives

Recommended storage temperature : < 50 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butan-2-ol	78-92-2	TWA	100 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	TWA (Mist)	5 mg/m ³	IN OEL
		STEL (Mist)	10 mg/m ³	IN OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
1-Methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Butanone	78-93-3	TWA	200 ppm 590 mg/m ³	IN OEL
		STEL	300 ppm 885 mg/m ³	IN OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as	2 mg/l	ACGIH BEI

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version
8.0

Revision Date:
08/30/2023

SDS Number:
10772028-00013

Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

				possible after exposure ceases)		
--	--	--	--	--	--	--

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection
Material : Fluorinated rubber
Break through time : ≥ 240 min
Glove thickness : 0.6 mm

Material : butyl-rubber
Break through time : ≥ 240 min
Glove thickness : 0.6 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

II

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a compressed gas
Propellant	:	Carbon dioxide
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	82 °C
Flash point	:	< -20 °C
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	0.7 %(V)
Vapour pressure	:	ca. 8,000 hPa (20 °C)
Relative vapour density	:	Not applicable
Density	:	0.754 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	270 °C

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
8.0	08/30/2023	10772028-00013	Date of first issue: 08/05/2014

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Components:

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Butan-2-ol:

Acute oral toxicity : LD50 (Rat): 2,054 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): 16,750 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 259.354 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,350 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4,016 mg/kg

Acute inhalation toxicity : LC50 (Mouse): < 22.2 mg/l
Exposure time: 6 h

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm
Exposure time: 30 min
Test atmosphere: vapour

Butanone:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Propan-2-ol:

Species : Rabbit
Result : No skin irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Butan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

1-Methoxy-2-propanol:

Species : Rabbit

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Result : No skin irritation

Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Propan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Butan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

1-Methoxy-2-propanol:

Species : Rabbit
Result : No eye irritation

Butanone:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Respiratory sensitisation

Not classified based on available information.

Components:

Propan-2-ol:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Butan-2-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative
Remarks : Based on data from similar materials

1-Methoxy-2-propanol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Butanone:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Components:

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Butan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosomal aberration
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)
Result: negative

1-Methoxy-2-propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Method: OECD Test Guideline 482
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)
Result: negative

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Species : Mouse
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

1-Methoxy-2-propanol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Butan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

1-Methoxy-2-propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Application Route: inhalation (vapour)
Result: negative

Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Butan-2-ol:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

1-Methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

Butanone:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Propan-2-ol:

Species : Rat

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

NOAEL : 12.5 mg/l
Application Route : inhalation (vapour)
Exposure time : 104 Weeks

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rat
NOAEL : 12.47 mg/l
Application Route : Inhalation
Exposure time : 90 Days
Remarks : Based on data from similar materials

Butan-2-ol:

Species : Rat
NOAEL : ≥ 15.11 mg/l
Application Route : inhalation (vapour)
Exposure time : 80 - 90 Days
Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat, male
NOAEL : 10.504 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Remarks : Based on data from similar materials

1-Methoxy-2-propanol:

Species : Rat
NOAEL : 919 mg/kg
Application Route : Ingestion
Exposure time : 35 Days

Species : Rat
NOAEL : 1.1 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr
Method : OECD Test Guideline 453

Species : Rabbit
NOAEL : 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Butanone:

Species : Rat
NOAEL : 14.84 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

plants mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (*Selenastrum capricornutum* (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.17 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Butan-2-ol:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

EC10 (*Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to fish : LL50 (*Oncorhynchus mykiss* (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 0.1 - 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

1-Methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l
Exposure time: 96 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23,300 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 6,745 mg/l
Exposure time: 72 h
Method: ISO 10253

Toxicity to microorganisms : IC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Butan-2-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 5 d

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

1-Methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 96 %
Exposure time: 28 d
Method: OECD Test Guideline 301E

Butanone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version 8.0 Revision Date: 08/30/2023 SDS Number: 10772028-00013 Date of last issue: 07/28/2023
Date of first issue: 08/05/2014

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Based on data from similar materials

Butan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.65

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n-octanol/water : log Pow: 3.6

1-Methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: < 1

Carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0.83

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or ex-

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
8.0	08/30/2023	10772028-00013	Date of first issue: 08/05/2014

pose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
(Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
8.0	08/30/2023	10772028-00013	Date of first issue: 08/05/2014

16. OTHER INFORMATION

Revision Date : 08/30/2023

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
IN OEL : India. Permissible levels of certain chemical substances in work environment.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
IN OEL / TWA : Time-Weighted Average Concentration (TWA) (8 hrs.)
IN OEL / STEL : Short-term exposure Limit STEL (15 min)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Sub-

SAFETY DATA SHEET

according to the Globally Harmonized System



CONTACT SW - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
8.0	08/30/2023	10772028-00013	Date of first issue: 08/05/2014

stances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IN / EN