

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Section 1: Identification

Product name : ULTRA 2040 20 LTR
Product code : 0890 085 021

Manufacturer or supplier's details

Company : Wurth NewZealand Ltd
Address : 99 McLauglins Road
Wiri, Auckland 2104
Telephone : +64 9 262 3040
Emergency telephone number : 0800 764 766
E-mail address : prodsafe@wuerth.com
Telefax : +64 9 262 3030

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant
Water repellent
Corrosion inhibitor
Restrictions on use : Not applicable

Section 2: Hazard identification**GHS Classification**

Flammable liquids : Category 2
Skin corrosion/irritation : Category 2
Specific target organ toxicity - single exposure : Category 3
Aspiration hazard : Category 1
Hazardous to the aquatic environment - acute hazard : Category 1
Hazardous to the aquatic environment - chronic hazard : Category 1

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

 : H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

 : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,	64742-49-0	>= 30 -< 50
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	>= 30 -< 50

Section 4: First-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Notes to physician : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

- | | | |
|---|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |
| Hazchem Code | : | 3YE |

Section 6: Accidental release measures

- | | | |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water |

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7: Handling and storage

- | | | |
|-----------------------------|---|---|
| Technical measures | : | Ground and bond container and receiving equipment.
See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing mist or vapours.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |

ULTRA 2040 20 LTR

Version 5.0 Revision Date: 21.11.2023 SDS Number: 10697293-00008 Date of last issue: 30.05.2023
 Date of first issue: 21.08.2018

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable gases
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Poisonous gases
 Explosives

Storage period : 24 Months

Section 8: Exposure controls/personal protection**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,	64742-49-0	WES-TWA	400 ppm 1,640 mg/m ³	NZ OEL
	Further information: Ototoxin			
		WES-STEL	500 ppm 2,050 mg/m ³	NZ OEL
	Further information: Ototoxin			
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	WES-TWA (Mist)	5 mg/m ³	NZ OEL
		WES-STEL (Mist)	10 mg/m ³	NZ OEL

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Hand protection
 Material : Nitrile rubber

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Break through time : ≥ 480 min
Glove thickness : 0.35 mm

Material : Fluorinated rubber
Break through time : ≥ 480 min
Glove thickness : 0.4 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Section 9: Physical and chemical properties

Appearance : liquid

Colour : light yellow, transparent

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : < 0 °C

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	ca. 0.74 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	1.316 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

Section 10: Stability and reactivity

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Highly flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

Section 11: Toxicological information

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

ULTRA 2040 20 LTR

Version 5.0 Revision Date: 21.11.2023 SDS Number: 10697293-00008 Date of last issue: 30.05.2023
Date of first issue: 21.08.2018

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Result : negative
Remarks : Based on data from similar materials

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

ULTRA 2040 20 LTR

Version 5.0 Revision Date: 21.11.2023 SDS Number: 10697293-00008 Date of last issue: 30.05.2023
Date of first issue: 21.08.2018

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Species : Rat
NOAEL : 12.47 mg/l
Application Route : Inhalation
Exposure time : 90 Days
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
NOAEL : 10,186 mg/m³
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

ULTRA 2040 20 LTR

Version 5.0 Revision Date: 21.11.2023 SDS Number: 10697293-00008 Date of last issue: 30.05.2023
Date of first issue: 21.08.2018

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Section 12: Ecological information**Ecotoxicity****Components:****Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Ecotoxicology Assessment

- Acute aquatic toxicity : Very toxic to aquatic life.
-

ULTRA 2040 20 LTR

Version 5.0 Revision Date: 21.11.2023 SDS Number: 10697293-00008 Date of last issue: 30.05.2023
Date of first issue: 21.08.2018

Remarks: Based on national or regional regulation.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.
Remarks: Based on national or regional regulation.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Bioaccumulative potential
Components:
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,:

Partition coefficient: n-octanol/water	:	log Pow: > 4	Remarks: Based on data from similar materials
--	---	--------------	---

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations
Disposal methods

Waste from residues	:	Do not dispose of waste into sewer.
	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Section 14: Transport information
International Regulations
UNRTDG

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Class	:	3
Packing group	:	II
Labels	:	3
Environmentally hazardous	:	yes

IATA-DGR

UN/ID No.	:	UN 1993
Proper shipping name	:	Flammable liquid, n.o.s. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Class	:	3

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**NZS 5433**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics,, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Class : 3
Packing group : II
Labels : 3
Hazchem Code : 3YE
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002603 Lubricants Flammable Group Standard

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

Section 16: Other information

Revision Date : 21.11.2023

Further informationSources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviationsACGIH : USA. ACGIH Threshold Limit Values (TLV)
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric ContaminantsACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

ULTRA 2040 20 LTR

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2023
5.0	21.11.2023	10697293-00008	Date of first issue: 21.08.2018

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN