

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Section 1: Identification

Product name : PAINT MARKER RED
Product code : 0967 910 402

Manufacturer or supplier's details

Company : Wurth NewZealand Ltd
Address : 99 McLauglins Road
Wiri, Auckland 2104
Telephone : +64 9 262 3040
Emergency telephone number : 0800 764 766
E-mail address : prodsafe@wuerth.com
Telefax : +64 9 262 3030

Recommended use of the chemical and restrictions on use

Recommended use : Colouring agents, dyes
Restrictions on use : Not applicable





Section 2: Hazard identification**GHS Classification**

Flammable liquids : Category 3
Acute toxicity (Oral) : Category 4
Serious eye damage/eye irritation : Category 1
Carcinogenicity (Inhalation) : Category 2
Specific target organ toxicity - single exposure : Category 3

GHS label elements

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Hazard pictograms	:	   
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer if inhaled.
Precautionary statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. Storage: P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 Store locked up. Disposal:

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
 Date of first issue: 28.06.2017

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-1-ol	71-23-8	>= 50 -< 70
titanium dioxide	13463-67-7	>= 10 -< 20
Diiron trioxide	1309-37-1	>= 1 -< 10
Carbon black	1333-86-4	>= 1 -< 10

Section 4: First-aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.
 If vomiting occurs have person lean forward.
 Call a physician or poison control centre immediately.
 Rinse mouth thoroughly with water.
 Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
 Causes serious eye damage.
 May cause drowsiness or dizziness.
 Suspected of causing cancer if inhaled.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Notes to physician : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : 3Y

Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7: Handling and storage

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
 Date of first issue: 28.06.2017

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable gases
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Poisonous gases
 Explosives

Section 8: Exposure controls/personal protection
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-1-ol	71-23-8	WES-TWA	200 ppm 492 mg/m ³	NZ OEL
		Further information: Skin absorption		
		WES-STEL	250 ppm 614 mg/m ³	NZ OEL
		Further information: Skin absorption		
		TWA	100 ppm	ACGIH
titanium dioxide	13463-67-7	WES-TWA	10 mg/m ³	NZ OEL
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
Diiron trioxide	1309-37-1	WES-TWA (Dust and fume)	5 mg/m ³ (Iron)	NZ OEL
		TWA (Respirable particulate matter)	5 mg/m ³	ACGIH
Carbon black	1333-86-4	WES-TWA	3 mg/m ³	NZ OEL
		Further information: Suspected human carcinogen		
		TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

titanium dioxide

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equip-

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

ment.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapour type
- Hand protection
- Material : PVC
- Material : Neoprene
- Material : Nitrile rubber
- Material : Natural Rubber
- Material : Fluorinated rubber
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Section 9: Physical and chemical properties

Appearance : liquid

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Colour	:	coloured
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	96 °C
Flash point	:	23 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	13.5 %(V)
Lower explosion limit / Lower flammability limit	:	2.1 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

Section 11: Toxicological information

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 714.29 mg/kg
Method: Calculation method

Components:**Propan-1-ol:**

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute inhalation toxicity : LC50 (Rat): > 33.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Acute dermal toxicity : LD50 (Rabbit): 4,032 mg/kg

titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Skin corrosion/irritation

|| Not classified based on available information.

Components:**Propan-1-ol:**

Species : Rabbit
Result : No skin irritation

titanium dioxide:

Species : Rabbit
Result : No skin irritation

Diiron trioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Carbon black:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

|| Causes serious eye damage.

Components:**Propan-1-ol:**

Species : Rabbit
Result : Irreversible effects on the eye

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

titanium dioxide:

Species : Rabbit
Result : No eye irritation

Diiron trioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Carbon black:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation**Skin sensitisation**

|| Not classified based on available information.

Respiratory sensitisation

|| Not classified based on available information.

Components:**Propan-1-ol:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

titanium dioxide:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Diiron trioxide:

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Carbon black:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Chronic toxicity**Germ cell mutagenicity**

|| Not classified based on available information.

Components:**Propan-1-ol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Diiron trioxide:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Method: OECD Test Guideline 479
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Species: *Drosophila melanogaster* (vinegar fly)
Application Route: Ingestion
Method: OECD Test Guideline 477
Result: negative

Carcinogenicity

|| Suspected of causing cancer if inhaled.

Components:**titanium dioxide:**

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Diiron trioxide:

Species : Rat
Application Route : Intraperitoneal injection
Exposure time : 790 - 914 days
Result : negative

Carbon black:

Species : Rat
Application Route : Inhalation
Exposure time : 24 Months
Result : positive

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.
Remarks: Based on national or regional regulation.

Reproductive toxicity

|| Not classified based on available information.

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Components:**Carbon black:**

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-foetal development
Species: Mouse
Application Route: inhalation (dust/mist/fume)
Result: negative

STOT - single exposure

|| May cause drowsiness or dizziness.

Components:**Propan-1-ol:**

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

|| Not classified based on available information.

Repeated dose toxicity**Components:****Propan-1-ol:**

Species : Rat
NOAEL : > 8 mg/l
Application Route : inhalation (vapour)
Method : OECD Test Guideline 413

titanium dioxide:

Species : Rat
NOAEL : 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Species : Rat
NOAEL : 10 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 yr

Aspiration toxicity

|| Not classified based on available information.

PAINT MARKER RED

Version 6.0 Revision Date: 14.12.2023 SDS Number: 10678073-00010 Date of last issue: 26.05.2023
Date of first issue: 28.06.2017

Components:**Propan-1-ol:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Section 12: Ecological information**Ecotoxicity****Components:****Propan-1-ol:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,555 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,644 mg/l
Exposure time: 48 h
Method: DIN 38412
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 9,170 mg/l
Exposure time: 48 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 21 d

titanium dioxide:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Diiron trioxide:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
-

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Toxicity to microorganisms : EC50: > 10,000 mg/l
Exposure time: 3 h

Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l
Exposure time: 24 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Persistence and degradability**Components:****Propan-1-ol:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 75 %
Exposure time: 20 d

Bioaccumulative potential**Components:****Propan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.2

Mobility in soil

No data available

Other adverse effects

No data available

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

Section 13: Disposal considerations

Disposal methods

- | | | |
|------------------------|---|--|
| Waste from residues | : | Do not dispose of waste into sewer. |
| | : | Dispose of in accordance with local regulations. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product. |

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1210
Proper shipping name	:	PRINTING INK
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1210
Proper shipping name	:	Printing ink
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1210
Proper shipping name	:	PRINTING INK
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-D
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

NZS 5433

UN number	:	UN 1210
Proper shipping name	:	PRINTING INK
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002669 Surface Coatings and Colourants Flammable Carcinogenic Group Standard

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

Section 16: Other information

Revision Date : 14.12.2023

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospher-

PAINT MARKER RED

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
6.0	14.12.2023	10678073-00010	Date of first issue: 28.06.2017

ic Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN