

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : POWER SPRAY GLUE PLUS - 400 ML

Product code : 0890100064

Unique Formula Identifier (UFI) : CUYD-Y09Q-A000-H7KY

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.

**Response:**

P391	Collect spillage.
------	-------------------

**Storage:**

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
-------------	---

#### Hazardous components which must be listed on the label:

Methyl acetate  
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Hydrocarbons, C6, isoalkanes, <5% n-hexane  
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Methyl acetate	79-20-9 201-185-2 607-021-00-X 01-2119459211-47	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0 01-2119475515-33	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0 01-2119484651-34	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	Not Assigned 01-2119475514-35	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
Cyclohexane	110-82-7 203-806-2 601-017-00-1 01-2119463273-41	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,25 - < 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

		H410	
n-Hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44	M-Factor (Acute aquatic toxicity): 1 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 STOT RE 2; H373 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 specific concentration limit STOT RE 2; H373 >= 5 %	>= 0,1 - < 0,25
2,6-Di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control centre immediately.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

### CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
- Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases
- Storage class (TRGS 510) : 2B
- Recommended storage temperature : 15 - 35 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methyl acetate	79-20-9	AGW	200 ppm 620 mg/m <sup>3</sup>	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(I)	
			Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child	
		MAK	100 ppm 310 mg/m <sup>3</sup>	DE DFG MAK
			Peak-limit: excursion factor (category): 4; I	
			Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed	
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m <sup>3</sup>	DE TRGS 900
			Peak-limit: excursion factor (category): 4;(II)	
		MAK	1.000 ppm 1.800 mg/m <sup>3</sup>	DE DFG MAK
			Peak-limit: excursion factor (category): 4; II	
			Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	500 ppm 2.085 mg/m <sup>3</sup>	2000/39/EC
			Further information: Indicative	
		AGW	500 ppm 2.100 mg/m <sup>3</sup>	DE TRGS 900
			Peak-limit: excursion factor (category): 1;(I)	
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
			Peak-limit: excursion factor (category): 4;(II)	
		MAK	1.000 ppm 2.400 mg/m <sup>3</sup>	DE DFG MAK
			Peak-limit: excursion factor (category): 4; II	
			Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	AGW	700 mg/m <sup>3</sup>	DE TRGS 900



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned	AGW	700 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Cyclohexane	110-82-7	TWA	200 ppm 700 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
		AGW	200 ppm 700 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	200 ppm 700 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
		AGW	50 ppm 180 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 8;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	50 ppm 180 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
2,6-Di-tert-butyl-p-cresol	128-37-0	AGW (Vapour and aerosols, inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (inhalable fraction)	10 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hydrocarbons, C7, n-	64742-49-0	heptan-2,5-dione:	Immediately after	TRGS 903

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

alkanes, isoalkanes, cyclics		250 µg/l (Urine)	exposure or after working hours	
Cyclohexane	110-82-7	1,2-cyclohexanediol: 150 mg/g creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903
		1,2-cyclohexanediol: 150 mg/g creatinine (Urine)	end of shift, for long-term exposures after several previous shifts	DE DFG BAT
n-Hexane	110-54-3	2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	end of shift, for long-term exposures after several previous shifts, Immediately after exposition or after working hours	DE DFG BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyl acetate	Workers	Inhalation	Long-term systemic effects	610 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	305 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	88 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	131 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	152 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	44 mg/kg bw/day
n-Hexane	Workers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	75 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	5,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	16 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2035 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	608 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	699 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	699 mg/kg bw/day
Hydrocarbons, C6, isoalkanes, <5% n- hexane	Workers	Inhalation	Long-term systemic effects	5306 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1377 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1301 mg/kg bw/day
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2085 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	447 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	149 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	149 mg/kg bw/day
Cyclohexane	Workers	Inhalation	Acute systemic ef- fects	700 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	700 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2016 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	700 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local ef- fects	700 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic ef- fects	412 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	206 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local ef- fects	206 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1186 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic	59,4 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

			effects	bw/day
2,6-Di-tert-butyl-p-cresol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,86 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0,25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,25 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Methyl acetate	Fresh water	0,12 mg/l
	Marine water	0,012 mg/l
	Freshwater - intermittent	1,2 mg/l
	Sewage treatment plant	600 mg/l
	Fresh water sediment	0,128 mg/kg dry weight (d.w.)
	Marine sediment	0,013 mg/kg dry weight (d.w.)
	Soil	0,042 mg/kg dry weight (d.w.)
Cyclohexane	Oral (Secondary Poisoning)	20,4 mg/kg food
	Fresh water	0,207 mg/l
	Marine water	0,207 mg/l
	Intermittent use/release	0,207 mg/l
	Sewage treatment plant	3,24 mg/l
	Fresh water sediment	3,627 mg/kg dry weight (d.w.)
	Marine sediment	3,627 mg/kg dry weight (d.w.)
2,6-Di-tert-butyl-p-cresol	Soil	2,99 mg/kg dry weight (d.w.)
	Fresh water	0,199 µg/l
	Intermittent use/release	0,02 µg/l
	Marine water	0,02 µg/l
	Sewage treatment plant	0,17 mg/l
	Fresh water sediment	0,0996 mg/kg dry weight (d.w.)
	Marine sediment	0,00996 mg/kg dry weight (d.w.)
Soil	0,04769 mg/kg dry weight (d.w.)	
	Oral (Secondary Poisoning)	8,33 mg/kg food

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles  
Equipment should conform to DIN EN 166

### Hand protection

Material : Nitrile rubber  
Break through time : 240 min  
Glove thickness : 0,4 mm  
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Butane, Isobutane, Propane

Colour : Colorless to pale yellow

Odour : ester-like

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : -25 °C  
Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

pH : 4 - 5  
Concentration: 50 %

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : 5.000 - 6.000 hPa (20 °C)

Density : 0,7 g/cm<sup>3</sup> (20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Relative vapour density : Not applicable

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

### Acute toxicity

Not classified based on available information.

### Components:

#### Methyl acetate:

Acute oral toxicity : LD50 (Rat): 6.482 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 49,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): 16.750 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 259,354 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3.350 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

### **Cyclohexane:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 19,07 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **n-Hexane:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31,86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **2,6-Di-tert-butyl-p-cresol:**

Acute oral toxicity : LD50 (Rat): > 6.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### **Skin corrosion/irritation**

Causes skin irritation.

### **Components:**

#### **Methyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Result : Skin irritation  
Remarks : Based on data from similar materials

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

### Cyclohexane:

Species : Rabbit  
Result : Skin irritation

### n-Hexane:

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### 2,6-Di-tert-butyl-p-cresol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### Methyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 7 days

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit  
Result : No eye irritation

### Cyclohexane:

Species : Rabbit  
Result : No eye irritation

### n-Hexane:

Species : Rabbit  
Result : No eye irritation

### 2,6-Di-tert-butyl-p-cresol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
Remarks : Based on data from similar materials

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative  
Remarks : Based on data from similar materials

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

### Cyclohexane:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

### n-Hexane:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

### 2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)  
Exposure routes : Skin contact  
Species : Humans  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Methyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 474  
Result: negative

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Result: negative  
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OPPTS 870.5395  
Result: negative

### Cyclohexane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **n-Hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### **2,6-Di-tert-butyl-p-cresol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Methyl acetate:**

Species : Rat  
Application Route : Inhalation  
Exposure time : 18 Months  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Remarks : Based on data from similar materials

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

### n-Hexane:

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

### 2,6-Di-tert-butyl-p-cresol:

Species : Rat  
Application Route : Ingestion  
Exposure time : 22 Months  
Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### Cyclohexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### n-Hexane:

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapour)  
Result: positive



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **2,6-Di-tert-butyl-p-cresol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **Components:**

##### **Methyl acetate:**

Assessment : May cause drowsiness or dizziness.

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Assessment : May cause drowsiness or dizziness.

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

##### **Cyclohexane:**

Assessment : May cause drowsiness or dizziness.

##### **n-Hexane:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

### Components:

#### **n-Hexane:**

Exposure routes : inhalation (vapour)  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **2,6-Di-tert-butyl-p-cresol:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### **Repeated dose toxicity**

### Components:

#### **Methyl acetate:**

Species : Rat  
NOAEL : 1,057 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rat  
NOAEL : 12,47 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species : Rat, male  
NOAEL : 10,504 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

#### **Cyclohexane:**

Species : Rat  
NOAEL : 24,08 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

### **n-Hexane:**

Species : Mouse  
LOAEL : 1,76 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3.973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### **2,6-Di-tert-butyl-p-cresol:**

Species : Rat  
NOAEL : 25 mg/kg  
Application Route : Ingestion  
Exposure time : 22 Months

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Product:**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Cyclohexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Experience with human exposure

##### Components:

##### n-Hexane:

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

## SECTION 12: Ecological information

### 12.1 Toxicity

##### Components:

##### Methyl acetate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 250 - 350 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.026,7 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 120 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): > 120 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1.830 mg/l  
Exposure time: 16 h

##### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,17 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 0,1 - 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8,2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,6 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### Cyclohexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,53 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,9 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 0,94 mg/l  
Exposure time: 72 h

EC50 (Pseudokirchneriella subcapitata (green algae)): 9,32 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

M-Factor (Acute aquatic toxicity) : 1

### Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### n-Hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### 2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,57 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,48 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : > 10.000 mg/l  
Exposure time: 3 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,053 mg/l  
Exposure time: 30 d  
Species: *Oryzias latipes* (Japanese medaka)  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,316 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

#### Components:

##### **Methyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77,05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Cyclohexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **n-Hexane:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

### 2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 4,5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

## 12.3 Bioaccumulative potential

### Components:

#### Methyl acetate:

Partition coefficient: n-  
octanol/water : log Pow: 0,18

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n-  
octanol/water : log Pow: > 4  
Remarks: Based on data from similar materials

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n-  
octanol/water : log Pow: 3,6

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-  
octanol/water : log Pow: 4  
Remarks: Based on data from similar materials

#### Cyclohexane:

Partition coefficient: n-  
octanol/water : log Pow: 3,44

#### n-Hexane:

Partition coefficient: n-  
octanol/water : log Pow: 4

### 2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 330 - 1.800

Partition coefficient: n-  
octanol/water : log Pow: 5,1

## 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
- Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant). Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product
  - 16 05 04, gases in pressure containers (including halons) containing hazardous substances
  - 08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
  - unused product
  - 16 05 04, gases in pressure containers (including halons) containing hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

---

08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances

uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

#### 14.2 UN proper shipping name

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.1
<b>ADR</b>	: 2	2.1
<b>RID</b>	: 2	2.1
<b>IMDG</b>	: 2.1	
<b>IATA</b>	: 2.1	

#### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version 4.0      Revision Date: 19.06.2024      SDS Number: 11188170-00006      Date of last issue: 19.04.2024  
Date of first issue: 31.03.2023

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Cyclohexane (Number on list 57)

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alterna-	2.500 t	25.000 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

---

tive fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Not applicable  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:  
Not applicable  
5.2.7.1.1: Formaldehyde:  
Not applicable  
5.2.7.1.1: fibres:  
Not applicable  
5.2.7.1.2: Germ cell mutagens:  
Not applicable  
5.2.7.1.3: Substances toxic to reproduction:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 81,4 %, 569,8 g/l  
Remarks: VOC content excluding water

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
DE DFG BAT	: Germany. MAK BAT Annex XIII
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2006/15/EC / TWA	: Limit Value - eight hours
DE DFG MAK / MAK	: MAK value
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## POWER SPRAY GLUE PLUS - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.04.2024
4.0	19.06.2024	11188170-00006	Date of first issue: 31.03.2023

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN