

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 1C PLASTIC PRIMER - 1 L

Product code : 5866106101

Unique Formula Identifier (UFI) : 5VWE-10KV-U008-4MJS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Primers
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Hazardous components which must be listed on the label:

Ethyl acetate
Xylene
Solvent naphtha (petroleum), light arom.
Diacetone alcohol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation tox-	>= 25 - < 30

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

		icity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4 01-2119486773-24	Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
Diacetone alcohol	123-42-2 204-626-7 603-016-00-1 01-2119473975-21	Flam. Liq. 3; H226 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 specific concentration limit Eye Irrit. 2; H319 >= 10 %	>= 3 - < 10
Ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute inhalation tox- icity (vapour): 17,8 mg/l	>= 2,5 - < 10
1,2,4-Trimethylbenzene	95-63-6 202-436-9 601-043-00-3	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Acute toxicity esti- mate Acute inhalation tox- icity (vapour): 11 mg/l	>= 2,5 - < 10

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Chlorine compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017/164/EU
		Further information: Indicative		
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU
		Further information: Indicative		
		AGW	200 ppm 730 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(l)		
		Further information: When there is compliance with the OEL and biological		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

			tolerance values, there is no risk of harming the unborn child	
		MAK	200 ppm 750 mg/m ³	DE DFG MAK
			Peak-limit: excursion factor (category): 2; I	
			Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed	
Xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
			Further information: Identifies the possibility of significant uptake through the skin, Indicative	
		STEL	100 ppm 442 mg/m ³	2000/39/EC
			Further information: Identifies the possibility of significant uptake through the skin, Indicative	
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(II)	
			Further information: Skin absorption	
		MAK	50 ppm 220 mg/m ³	DE DFG MAK
			Peak-limit: excursion factor (category): 2; II	
			Further information: Danger of absorption through the skin, Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C	
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	50 mg/m ³	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(II)	
			Further information: Group exposure limit for hydrocarbon solvent mixtures	
Diacetone alcohol	123-42-2	AGW	20 ppm 96 mg/m ³	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(I)	
			Further information: Skin absorption	
		MAK	20 ppm 96 mg/m ³	DE DFG MAK
			Peak-limit: excursion factor (category): 2; I	
			Further information: Danger of absorption through the skin, Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C	
Ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
			Further information: Identifies the possibility of significant uptake through the skin, Indicative	
		STEL	200 ppm 884 mg/m ³	2000/39/EC
			Further information: Identifies the possibility of significant uptake through the skin, Indicative	
		AGW	20 ppm 88 mg/m ³	DE TRGS 900

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	20 ppm 88 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
1,2,4-Trimethylbenzene	95-63-6	TWA	20 ppm 100 mg/m ³	2000/39/EC
	Further information: Indicative			
		AGW	20 ppm 100 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	20 ppm 100 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		Methylhippuric acid (toluric acid) (all isomers): 2.000 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT
Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
		mandelic acid plus phenylglyoxylic acid: 250 mg/g creatinine (Urine)	Immediately after exposition or after working hours	DE DFG BAT
1,2,4-Trimethylbenzene	95-63-6	Dimethylbenzoic acids (Sum of all Isomers): 400 mg/g creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after work-	TRGS 903

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

		Dimethyl benzoic acids (sum of all isomers): 400 mg/g creatinine (Urine)	ing hours end of shift, for long-term exposures after several previous shifts, Immediately after exposition or after working hours	DE DFG BAT
--	--	--	---	---------------

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Consumers	Inhalation	Long-term local effects	65,3 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
	Ethyl acetate	Workers	Inhalation	Long-term systemic effects
Workers		Inhalation	Acute systemic effects	1468 mg/m ³
Workers		Inhalation	Long-term local effects	734 mg/m ³
Workers		Inhalation	Acute local effects	1468 mg/m ³
Workers		Skin contact	Long-term systemic effects	63 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	367 mg/m ³
Consumers		Inhalation	Acute systemic effects	734 mg/m ³
Consumers		Inhalation	Long-term local effects	367 mg/m ³
Consumers		Inhalation	Acute local effects	734 mg/m ³
Consumers		Skin contact	Long-term systemic effects	37 mg/kg bw/day
Consumers		Ingestion	Long-term systemic effects	4,5 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Diacetone alcohol	Workers	Inhalation	Long-term systemic effects	32,6 mg/m ³
	Workers	Inhalation	Acute local effects	240 mg/m ³
	Workers	Skin contact	Long-term systemic effects	467 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,8 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	33 mg/kg bw/day
1,2,4-Trimethylbenzene	Consumers	Ingestion	Long-term systemic effects	1,67 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	100 mg/m ³
	Workers	Inhalation	Acute systemic effects	100 mg/m ³
	Workers	Inhalation	Long-term local effects	100 mg/m ³
	Workers	Inhalation	Acute local effects	100 mg/m ³
	Workers	Skin contact	Long-term systemic effects	16171 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	29,4 mg/m ³
	Consumers	Inhalation	Acute systemic effects	29,4 mg/m ³
	Consumers	Inhalation	Long-term local effects	29,4 mg/m ³
	Consumers	Inhalation	Acute local effects	29,4 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	9512 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	15 mg/kg bw/day
	Ethylbenzene	Workers	Inhalation	Long-term systemic effects
Workers		Inhalation	Acute local effects	293 mg/m ³
Workers		Skin contact	Long-term systemic effects	180 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	15 mg/m ³
Consumers		Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	1,9 mg/m ³
	Workers	Inhalation	Acute systemic effects	1286,4 mg/m ³
	Workers	Inhalation	Long-term local effects	837,5 mg/m ³
	Workers	Inhalation	Acute local effects	1066,67 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	410 µg/m ³
	Consumers	Inhalation	Acute systemic effects	1152 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

	Consumers	Inhalation	Long-term local effects	178,57 mg/m ³
	Consumers	Inhalation	Acute local effects	640 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
Ethyl acetate	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water	0,24 mg/l
	Marine water	0,024 mg/l
	Intermittent use/release	1,65 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1,15 mg/kg dry weight (d.w.)
Diacetone alcohol	Marine sediment	0,115 mg/kg dry weight (d.w.)
	Soil	0,148 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	200 mg/kg food
	Fresh water	2 mg/l
	Freshwater - intermittent	1 mg/l
	Marine water	0,2 mg/l
1,2,4-Trimethylbenzene	Sewage treatment plant	100 mg/l
	Fresh water sediment	7,4 mg/kg dry weight (d.w.)
	Marine sediment	0,74 mg/kg dry weight (d.w.)
	Soil	0,3 mg/kg dry weight (d.w.)
	Fresh water	0,12 mg/l
	Marine water	0,12 mg/l
Ethylbenzene	Intermittent use/release	0,12 mg/l
	Sewage treatment plant	2,41 mg/l
	Fresh water sediment	13,56 mg/kg dry weight (d.w.)
	Marine sediment	13,56 mg/kg dry weight (d.w.)
	Soil	2,34 mg/kg dry weight (d.w.)
	Fresh water	0,1 mg/l
Ethylbenzene	Freshwater - intermittent	0,1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water sediment	13,7 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

		weight (d.w.)
	Marine sediment	1,37 mg/kg dry weight (d.w.)
	Soil	2,68 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : Fluorinated rubber
Break through time : 10 min
Glove thickness : 0,7 mm
Directive : Equipment should conform to DIN EN 374
Protective index : Class 1

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	10 °C Method: DIN 53213
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Viscosity Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Flow time	:	10 - 13 s at 20 °C Cross section: 4 mm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Method: DIN 53211

Solubility(ies)
Water solubility : slightly soluble

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : 360 hPa (50 °C)

Density : 0,914 g/cm³ (20 °C)
Method: DIN 53217

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Highly flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Ethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22,5 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Remarks: Based on national or regional regulation.

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3.002 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7,6 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

1,2,4-Trimethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.280 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 3.160 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Ethyl acetate:

Species : Rabbit
Result : No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Solvent naphtha (petroleum), light arom.:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Diacetone alcohol:

Species : Rabbit
Result : No skin irritation

1,2,4-Trimethylbenzene:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Solvent naphtha (petroleum), light arom.:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Diacetone alcohol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 7 days

1,2,4-Trimethylbenzene:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Ethyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Solvent naphtha (petroleum), light arom.:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Diacetone alcohol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

1,2,4-Trimethylbenzene:

Test Type : Maximisation Type
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Components:

Ethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Hamster
Application Route: Ingestion
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Solvent naphtha (petroleum), light arom.:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Diacetone alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

1,2,4-Trimethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Solvent naphtha (petroleum), light arom.:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Ethylbenzene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Ethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Species: Rat
Application Route: inhalation (vapour)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Solvent naphtha (petroleum), light arom.:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Diacetone alcohol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

1,2,4-Trimethylbenzene:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

Ethyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Solvent naphtha (petroleum), light arom.:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

Diacetone alcohol:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

1,2,4-Trimethylbenzene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Ethyl acetate:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 3.600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 1,28 mg/l
LOAEL : 2,75 mg/kg
Application Route : inhalation (vapour)
Exposure time : 94 Days

Xylene:

Species : Rat
LOAEL : > 0,2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Solvent naphtha (petroleum), light arom.:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Species : Rat
NOAEL : > 1 mg/kg
Application Route : inhalation (vapour)
Exposure time : 109 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 600 mg/kg
Application Route : Skin contact
Exposure time : 28 Days
Remarks : Based on data from similar materials

Diacetone alcohol:

Species : Rat
NOAEL : ≥ 600 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

Species : Rat
NOAEL : $\geq 4,685$ mg/l
Application Route : inhalation (vapour)
Exposure time : 6 Weeks

Ethylbenzene:

Species : Rat
LOAEL : 0,868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

1,2,4-Trimethylbenzene:

Species : Rat
NOAEL : 600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Species : Rat
NOAEL : 1230 mg/m³
Application Route : inhalation (vapour)
Exposure time : 90 Days

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light arom.:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

1,2,4-Trimethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

Components:

Ethyl acetate:

Eye contact : Target Organs: Eye
Symptoms: Irritation

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.090 mg/l
Exposure time: 24 h
Method: DIN 38412
- Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1.650 mg/l
Exposure time: 0,25 h
- Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 9,65 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2,4 mg/l
Exposure time: 24 d
Species: Daphnia magna (Water flea)

Xylene:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 1 - 10 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Raphidocelis subcapitata (freshwater green alga)): > 0,1 - 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Diacetone alcohol:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): > 1.000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

1,2,4-Trimethylbenzene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7,72 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 2,356 mg/l
Exposure time: 96 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Exposure time: 20 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98,51 %
Exposure time: 28 d

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

1,2,4-Trimethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 60 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

Ethyl acetate:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 30

Partition coefficient: n-octanol/water : log Pow: 0,68

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3,16
Remarks: Calculation

Diacetone alcohol:

Partition coefficient: n-octanol/water : log Pow: -0,09
Remarks: Calculation

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3,6

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product
08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances
- unused product
08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version 11.1 Revision Date: 18.11.2024 SDS Number: 10780376-00011 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

uncleaned packagings
15 01 10*, packaging containing residues of or contaminated
by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : II

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :

Substance(s) or mixture(s) are listed

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

- Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)
- TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable
- Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 95,27 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- Other information : Items where changes have been made to the previous version
are highlighted in the body of this document by two vertical
lines.

Full text of H-Statements

- H225 : Highly flammable liquid and vapour.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

H226 : Flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H361d : Suspected of damaging the unborn child.
H373 : May cause damage to organs through prolonged or repeated exposure.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE DFG BAT : Germany. MAK BAT Annex XIII
DE DFG MAK : Germany. MAK BAT Annex IIa
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903 : TRGS 903 - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
DE DFG MAK / MAK : MAK value
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



1C PLASTIC PRIMER - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2024
11.1	18.11.2024	10780376-00011	Date of first issue: 11.06.2010

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 2	H225
STOT RE 2	H373
Asp. Tox. 1	H304
Repr. 2	H361d
STOT SE 3	H335
STOT SE 3	H336
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN