

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : REPAIR RESIN EXTREME II - 1,7 G

Product code : 0890014

Unique Formula Identifier (UFI) : 6Q90-C0RX-T00X-K29J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|---|--|
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Specific target organ toxicity - single ex- | H335: May cause respiratory irritation. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Benzyl methacrylate
2-Hydroxyethyl methacrylate
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate
Octyl acrylate
decyl acrylate
Acrylic acid

Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---|---|---|--------------------------|
| Benzyl methacrylate | 2495-37-6 219-674-4 607-134-00-4 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 STOT SE 3; H335 specific concentration limit STOT SE 3; H335 >= 10 % | >= 30 - < 50 |
| Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | 5888-33-5 227-561-6 607-756-00-6 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1A; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | >= 20 - < 25 |
| 2-Hydroxyethyl methacrylate | 868-77-9 212-782-2 607-124-00-X | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 20 - < 30 |
| Octyl acrylate | 2499-59-4 219-696-4 607-133-00-9 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 STOT SE 3; H335 Aquatic Chronic 2; H411 | >= 10 - < 20 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | | |
|--------------------------------------|--|---|-------------|
| | | specific concentration limit STOT SE 3; H335 ≥ 10 % | |
| decyl acrylate | 2156-96-9 218-462-9 607-133-00-9 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 2; H411 specific concentration limit STOT SE 3; H335 ≥ 10 % | ≥ 10 - < 20 |
| Acrylic acid | 79-10-7 201-177-9 607-061-00-8 | Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 specific concentration limit STOT SE 3; H335 ≥ 1 % Acute toxicity estimate Acute oral toxicity: 357 mg/kg Acute dermal toxicity: 1.100 mg/kg | ≥ 3 - < 5 |
| [3-(2,3-Epoxypropyl)trimethoxysilane | 2530-83-8 219-784-2 | Acute Tox. 4; H302 Eye Dam. 1; H318 STOT SE 2; H371 (Central nervous system, optic nerve) Aquatic Chronic 3; H412 | ≥ 3 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | | |
|----------|--------------------------------------|--|--------------|
| | | Acute toxicity estimate Acute oral toxicity: > 300 - 2.000 mg/kg | |
| Methanol | 67-56-1 200-659-6 603-001-00-X | Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 (optic nerve, Central nervous system) | >= 0,1 - < 1 |
| | | specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 % | |
| | | Acute toxicity estimate Acute oral toxicity: 300 mg/kg Acute inhalation toxicity (vapour): 3 mg/l Acute dermal toxicity: 300 mg/kg | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases

Storage class (TRGS 510) : 10

Storage period : 24 Months

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------|---------|-------------------------------|--------------------------------|-------------|
| Acrylic acid | 79-10-7 | TWA | 10 ppm 29 mg/m ³ | 2017/164/EU |
| Further information: Indicative | | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | | | |
|----------|---|------|----------------------------------|----------------|
| | | STEL | 20 ppm 59 mg/m ³ | 2017/164/EU |
| | Further information: Indicative | | | |
| | | AGW | 10 ppm 30 mg/m ³ | DE TRGS 900 |
| | Peak-limit: excursion factor (category): 1;=2=(I) | | | |
| | Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| | | MAK | 10 ppm 30 mg/m ³ | DE DFG MAK |
| | Peak-limit: excursion factor (category): 1; I | | | |
| | Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |
| Methanol | 67-56-1 | TWA | 200 ppm 260 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | AGW | 100 ppm 130 mg/m ³ | DE TRGS 900 |
| | Peak-limit: excursion factor (category): 2;(II) | | | |
| | Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| | | MAK | 100 ppm 130 mg/m ³ | DE DFG MAK |
| | Peak-limit: excursion factor (category): 2; II | | | |
| | Further information: Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |

Occupational exposure limits of decomposition products

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|------------|---|-------------------------------|----------------------------------|----------------|
| Methanol | 67-56-1 | TWA | 200 ppm 260 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | AGW | 100 ppm 130 mg/m ³ | DE TRGS 900 |
| | Peak-limit: excursion factor (category): 2;(II) | | | |
| | Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| | | MAK | 100 ppm 130 mg/m ³ | DE DFG MAK |
| | Peak-limit: excursion factor (category): 2; II | | | |
| | Further information: Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|----------------|---------|--------------------|------------------|----------|
| Methanol | 67-56-1 | Methanol: 15 mg/l | In case of long- | TRGS 903 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | | | |
|--|--|------------------------------|--|---------------|
| | | (Urine) | term exposure: after more than one shift, Immedi- ately after expo- sure or after work- ing hours | |
| | | Methanol: 15 mg/l (Urine) | Immediately after exposition or after working hours | DE DFG BAT |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name | End Use | Exposure routes | Potential health ef- fects | Value | |
|---|----------------------------------|-----------------|-------------------------------|-------------------------------|----------------------|
| Benzyl methacrylate | Workers | Inhalation | Long-term systemic effects | 24,2 mg/m3 | |
| | Workers | Skin contact | Long-term systemic effects | 6,94 mg/kg bw/day | |
| | Consumers | Inhalation | Long-term systemic effects | 7,2 mg/m3 | |
| | Consumers | Skin contact | Long-term systemic effects | 4,17 mg/kg bw/day | |
| | Consumers | Ingestion | Long-term systemic effects | 4,17 mg/kg bw/day | |
| | 2-Hydroxyethyl meth- acrylate | Workers | Inhalation | Long-term systemic effects | 4,9 mg/m3 |
| Workers | | Skin contact | Long-term systemic effects | 1,3 mg/kg bw/day | |
| Consumers | | Inhalation | Long-term systemic effects | 2,9 mg/m3 | |
| Consumers | | Skin contact | Long-term systemic effects | 0,83 mg/kg bw/day | |
| Consumers | | Ingestion | Long-term systemic effects | 0,83 mg/kg bw/day | |
| Exo-1,7,7- trimethylbicy- clo[2.2.1]hept-2-yl acrylate | | Workers | Skin contact | Long-term systemic effects | 1,39 mg/kg bw/day |
| | Consumers | Skin contact | Long-term systemic effects | 0,83 mg/kg bw/day | |
| | Consumers | Ingestion | Long-term systemic effects | 0,83 mg/kg bw/day | |
| | Acrylic acid | Workers | Inhalation | Long-term local ef- fects | 30 mg/m3 |
| | | Workers | Inhalation | Acute local effects | 30 mg/m3 |
| | | Workers | Skin contact | Acute local effects | 1 mg/cm2 |
| Consumers | | Inhalation | Long-term local ef- fects | 3,6 mg/m3 | |
| Consumers | | Inhalation | Acute local effects | 3,6 mg/m3 | |
| Consumers | | Skin contact | Acute local effects | 1 mg/cm2 | |
| [3-(2,3- Epoxypro- poxy)propyl]trimethox | Workers | Inhalation | Long-term systemic effects | 70,5 mg/m3 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | | | |
|----------|-----------|--------------|----------------------------|-----------------------|
| ysilane | | | | |
| | Workers | Skin contact | Long-term systemic effects | 10 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 17 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 5 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 5 mg/kg bw/day |
| Methanol | Workers | Inhalation | Long-term systemic effects | 130 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 130 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 130 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 130 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 20 mg/kg bw/day |
| | Workers | Skin contact | Acute systemic effects | 20 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 26 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 26 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 26 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 26 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 4 mg/kg bw/day |
| | Consumers | Skin contact | Acute systemic effects | 4 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 4 mg/kg bw/day |
| | Consumers | Ingestion | Acute systemic effects | 4 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|-----------------------------|---------------------------|-------------|
| Benzyl methacrylate | Fresh water | 0,022 mg/l |
| | Marine water | 0,002 mg/l |
| | Intermittent use/release | 0,023 mg/l |
| | Sewage treatment plant | 1,31 mg/l |
| | Fresh water sediment | 0,888 mg/kg |
| | Marine sediment | 0,089 mg/kg |
| | Soil | 0,165 mg/kg |
| 2-Hydroxyethyl methacrylate | Fresh water | 0,482 mg/l |
| | Marine water | 0,482 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Sewage treatment plant | 10 mg/l |
| | Fresh water sediment | 3,79 mg/kg |
| | Marine sediment | 3,79 mg/kg |
| | Soil | 0,476 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

| | | |
|---|----------------------------|-------------------------------|
| Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | Fresh water | 0,00092 mg/l |
| | Marine water | 0,000092 mg/l |
| | Intermittent use/release | 0,00704 mg/l |
| | Sewage treatment plant | 2 mg/l |
| | Fresh water sediment | 0,145 mg/kg |
| Acrylic acid | Marine sediment | 0,0145 mg/kg |
| | Soil | 0,0285 mg/kg |
| | Fresh water | 0,003 mg/l |
| | Marine water | 0,0003 mg/l |
| | Intermittent use/release | 0,0013 mg/l |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | Sewage treatment plant | 0,9 mg/l |
| | Fresh water sediment | 0,0236 mg/kg |
| | Marine sediment | 0,00236 mg/kg |
| | Soil | 1 mg/kg |
| | Oral (Secondary Poisoning) | 0,03 mg/kg food |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | Fresh water | 0,45 mg/l |
| | Marine water | 0,045 mg/l |
| | Freshwater - intermittent | 0,45 mg/l |
| | Sewage treatment plant | 8,2 mg/l |
| | Fresh water sediment | 1,6 mg/kg dry weight (d.w.) |
| Soil | Marine sediment | 0,16 mg/kg dry weight (d.w.) |
| | Soil | 0,063 mg/kg dry weight (d.w.) |

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
Equipment should conform to DIN EN 166

Hand protection

Material : Neoprene gloves
Break through time : 240 - 480 min
Glove thickness : > 0,3 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

we recommend clarifying the resistance to chemicals of the
aforementioned protective gloves with the glove manufactur-
er. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical
resistance data and an assessment of the local exposure
potential.
Skin contact must be avoided by using impervious protective
clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-
sure assessment demonstrates exposures outside the rec-
ommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

| | | |
|--|---|--|
| Flash point | : | 101 °C |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| pH | : | substance/mixture is non-polar/aprotic |
| Viscosity | : | |
| Viscosity, kinematic | : | No data available |
| Solubility(ies) | : | |
| Water solubility | : | practically insoluble |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Vapour pressure | : | No data available |
| Relative density | : | No data available |
| Density | : | No data available |
| Relative vapour density | : | No data available |
| Particle characteristics | : | |
| Particle size | : | Not applicable |

9.2 Other information

| | | |
|----------------------|---|--|
| Explosives | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Evaporation rate | : | No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : Methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Components:

Benzyl methacrylate:

Acute oral toxicity : LD50 (Rat): 3.980 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Acute oral toxicity : LD50 (Rat): 4.350 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3.000 mg/kg

2-Hydroxyethyl methacrylate:

Acute oral toxicity : LD50 (Rat): 5.564 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Octyl acrylate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

decyl acrylate:

Acute oral toxicity : LD50 (Rat): 6.460 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Acrylic acid:

Acute oral toxicity : LD50 (Rat): 357 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity : LD50 (Rat): 8.025 mg/kg

Acute toxicity estimate (Humans): > 300 - 2.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Method: Expert judgement
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit, male): 4.248 mg/kg

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Skin corrosion/irritation

Causes skin irritation.

Components:

Benzyl methacrylate:

Result : Skin irritation
Remarks : Based on national or regional regulation.

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Result : Skin irritation
Remarks : Based on national or regional regulation.

2-Hydroxyethyl methacrylate:

Result : Skin irritation
Remarks : Based on national or regional regulation.

Octyl acrylate:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

decyl acrylate:

Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Acrylic acid:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Species : Rabbit
Result : Mild skin irritation

Methanol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Benzyl methacrylate:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

2-Hydroxyethyl methacrylate:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Octyl acrylate:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

decyl acrylate:

Result : Eye irritation

Acrylic acid:

Species : Rabbit
Result : Irreversible effects on the eye

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Methanol:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Benzyl methacrylate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

2-Hydroxyethyl methacrylate:

Assessment : Probability or evidence of skin sensitisation in humans
Remarks : Based on national or regional regulation.

Octyl acrylate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

decyl acrylate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Assessment : Probability or evidence of skin sensitisation in humans

Acrylic acid:

Test Type : Freund's complete adjuvant test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Methanol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Benzyl methacrylate:

Genotoxicity in vitro : Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

2-Hydroxyethyl methacrylate:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Octyl acrylate:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials
- Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials
- Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

decyl acrylate:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials
- Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials
- Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Acrylic acid:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: negative

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Result: positive

Test Type: In vitro mammalian cell gene mutation test
Result: positive

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 489
Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: positive

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ
cell mutagen.

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: in vitro micronucleus test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Hydroxyethyl methacrylate:

Species : Rat
Application Route : Inhalation
Exposure time : 102 weeks
Method : OECD Test Guideline 451
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Acrylic acid:

Species : Mouse
Application Route : Skin contact
Exposure time : 21 Months
Result : negative

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Species : Mouse, male
Application Route : Skin contact
Exposure time : 482 days
Result : negative

Methanol:

Species : Monkey
Application Route : inhalation (vapour)
Exposure time : 7 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Benzyl methacrylate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Method: OECD Test Guideline 422
Result: negative

2-Hydroxyethyl methacrylate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Octyl acrylate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

decyl acrylate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Acrylic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Effects on fertility : Test Type: One-generation reproduction toxicity study

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Methanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Monkey
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Monkey
Application Route: inhalation (vapour)
Result: negative

STOT - single exposure

May cause respiratory irritation.

Components:

Benzyl methacrylate:

Assessment : May cause respiratory irritation.
Remarks : Based on national or regional regulation.

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Assessment : May cause respiratory irritation.
Remarks : Based on national or regional regulation.

Octyl acrylate:

Assessment : May cause respiratory irritation.

decyl acrylate:

Assessment : May cause respiratory irritation.

Acrylic acid:

Assessment : May cause respiratory irritation.

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Exposure routes : Ingestion
Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Remarks : Based on data from similar materials

Methanol:

Target Organs : optic nerve, Central nervous system
Assessment : Causes damage to organs.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Benzyl methacrylate:

Species : Rat
NOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Method : OECD Test Guideline 422

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 2 Weeks
Method : OECD Test Guideline 422

2-Hydroxyethyl methacrylate:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 21 Days
Method : OECD Test Guideline 422

Octyl acrylate:

Species : Rabbit
NOAEL : 887 mg/kg
LOAEL : 1.774 mg/kg
Application Route : Ingestion
Exposure time : 14 Days
Remarks : Based on data from similar materials

decyl acrylate:

Species : Rabbit
NOAEL : 887 mg/kg
LOAEL : 1.774 mg/kg
Application Route : Ingestion
Exposure time : 14 Days
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Acrylic acid:

| | |
|-------------------|-------------|
| Species | : Rat |
| NOAEL | : 40 mg/kg |
| LOAEL | : 100 mg/kg |
| Application Route | : Ingestion |
| Exposure time | : 12 Months |

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

| | |
|-------------------|--|
| Species | : Rat |
| NOAEL | : > 100 mg/kg |
| Application Route | : Ingestion |
| Exposure time | : 90 Days |
| Method | : OECD Test Guideline 408 |
| Remarks | : Based on data from similar materials |

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

| | |
|------------|---|
| Assessment | : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|

SECTION 12: Ecological information

12.1 Toxicity

Product:

| | |
|---|---|
| Toxicity to daphnia and other aquatic invertebrates | : Remarks: No toxicity at the limit of solubility |
|---|---|

| | |
|--|---|
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: 125 mg/l Species: Daphnia pulex (Water flea) |
|--|---|

Components:

Benzyl methacrylate:

| | |
|------------------|---|
| Toxicity to fish | : LC50 (Pimephales promelas (fathead minnow)): 4,67 mg/l Exposure time: 96 h |
|------------------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 2,28 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 1,08 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 3,34 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,704 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,98 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,405 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,092 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

2-Hydroxyethyl methacrylate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 380 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 836 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

NOEC (Selenastrum capricornutum (green algae)): 400 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC0 : > 3.000 mg/l
Exposure time: 16 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 24,1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Octyl acrylate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

decyl acrylate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Acrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 27 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 95 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus subspicatus): 0,205 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

Method: Directive 67/548/EEC, Annex V, C.3.

EC10 (*Scenedesmus subspicatus*): 0,031 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : NOEC : 100 mg/l
Exposure time: 30 min
Method: ISO 8192

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3,8 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (*Cyprinus carpio* (Carp)): 55 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 710 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): 350 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 130 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (activated sludge): > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 100 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

Methanol:

Toxicity to fish : LC50 (*Lepomis macrochirus* (Bluegill sunfish)): 15.400 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Method: DIN 38412

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)):
22.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test substance: Neutralised product
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

Benzyl methacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 51 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-Hydroxyethyl methacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

Octyl acrylate:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

decyl acrylate:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Acrylic acid:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 14 d
Method: OECD Test Guideline 301

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 37 %
Exposure time: 28 d
Method: Regulation (EC) No. 440/2008, Annex, C.4-A

Methanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 95 %
Exposure time: 20 d

12.3 Bioaccumulative potential

Components:

Benzyl methacrylate:

Partition coefficient: n-octanol/water : log Pow: 3,1

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate:

Bioaccumulation : Species: Zebrafish
Bioconcentration factor (BCF): 37
Method: OECD Test Guideline 305
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 4,52

2-Hydroxyethyl methacrylate:

Partition coefficient: n-octanol/water : log Pow: 0,42

Octyl acrylate:

Partition coefficient: n-octanol/water : log Pow: 4,17

decyl acrylate:

Partition coefficient: n-octanol/water : log Pow: > 4

Acrylic acid:

Partition coefficient: n-octanol/water : log Pow: 0,46

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane:

Partition coefficient: n-octanol/water : log Pow: 0,5
Remarks: Calculation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): < 10

Partition coefficient: n-
octanol/water : log Pow: -0,77

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

|| used product
08 04 09*, waste adhesives and sealants containing organic solvents or other hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

IMDG : Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 69: Methanol

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

Version 9.0 Revision Date: 18.11.2024 SDS Number: 10785039-00014 Date of last issue: 20.06.2024
Date of first issue: 11.06.2010

mixtures and articles (Annex XVII)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Class 1: 5 % Acrylic acid, Methanol
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

|| Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H331 : Toxic if inhaled.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H370 : Causes damage to organs.
H371 : May cause damage to organs.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

| | | |
|--------------------|---|--|
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Skin Corr. | : | Skin corrosion |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitisation |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2006/15/EC | : | Europe. Indicative occupational exposure limit values |
| 2017/164/EU | : | Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values |
| DE DFG BAT | : | Germany. MAK BAT Annex XIII |
| DE DFG MAK | : | Germany. MAK BAT Annex IIa |
| DE TRGS 900 | : | Germany. TRGS 900 - Occupational exposure limit values. |
| TRGS 903 | : | TRGS 903 - Biological limit values |
| 2006/15/EC / TWA | : | Limit Value - eight hours |
| 2017/164/EU / STEL | : | Short term exposure limit |
| 2017/164/EU / TWA | : | Limit Value - eight hours |
| DE DFG MAK / MAK | : | MAK value |
| DE TRGS 900 / AGW | : | Time Weighted Average |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



REPAIR RESIN EXTREME II - 1,7 G

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 20.06.2024 |
| 9.0 | 18.11.2024 | 10785039-00014 | Date of first issue: 11.06.2010 |

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

| | |
|---------------|------|
| Skin Sens. 1 | H317 |
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| STOT SE 3 | H335 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN