

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Product code : 0893050007

Unique Formula Identifier (UFI) : AX0H-P0ST-000D-HD8P

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Processing aid
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H318 Causes serious eye damage.
H361d Suspected of damaging the unborn child.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Phosphoric acid
2-Methyl-2,4-pentanediol
Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 10 - < 20
Diethylene glycol	111-46-6 203-872-2 603-140-00-6	Acute Tox. 4; H302 Acute toxicity esti- mate Acute oral toxicity: 1.120 mg/kg	>= 1 - < 10
Phosphoric acid	7664-38-2 231-633-2 015-011-00-6	Met. Corr. 1; H290 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 EUH071 specific concentration limit Skin Corr. 1B; H314 >= 25 % Skin Irrit. 2; H315 10 - < 25 % Eye Irrit. 2; H319 10 - < 25 % EUH071 >= 25 % Acute toxicity esti- mate Acute oral toxicity: 2.000 mg/kg	>= 3 - < 5
2-Methyl-2,4-pentanediol	107-41-5 203-489-0 603-053-00-3	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d	>= 3 - < 10
Diisopropanolamine	110-97-4 203-820-9 603-083-00-7	Eye Irrit. 2; H319	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

Poly(oxy-1,2-ethanediyl), α - (carboxymethyl)- ω -[(9Z)-9- octadecen-1-yloxy]-	57635-48-0	Eye Dam. 1; H318	$\geq 3 - < 10$
----------------------------------------------------------------------------------------------------	------------	------------------	-----------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye damage.
Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Oxides of phosphorus
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases

Storage class (TRGS 510) : 2B

Storage period : >= 24 Months

Recommended storage temperature : 15 - 35 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m ³	2000/39/EC
		Further information: Indicative		
		AGW	1.000 ppm 1.900 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 8;(II)		
		MAK	1.000 ppm 1.900 mg/m ³	DE DFG MAK
		Peak-limit: excursion factor (category): 8; II		
		Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

	available data are not sufficient for classification in one of the groups A - C			
Diethylene glycol	111-46-6	AGW (Vapour and aerosols)	10 ppm 44 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	10 ppm 44 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Phosphoric acid	7664-38-2	TWA	1 mg/m ³	2000/39/EC
	Further information: Indicative			
		STEL	2 mg/m ³	2000/39/EC
	Further information: Indicative			
		AGW (Inhalable fraction)	2 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (inhalable fraction)	2 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 2; I			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
2-Methyl-2,4-pentandiol	107-41-5	MAK	10 ppm 49 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 2; I			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Diethylene glycol	Workers	Inhalation	Long-term systemic effects	44 mg/m ³
	Workers	Inhalation	Long-term local effects	60 mg/m ³
	Workers	Skin contact	Long-term systemic effects	43 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	12 mg/m ³
	Consumers	Inhalation	Long-term local effects	12 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	21 mg/kg bw/day
Phosphoric acid	Workers	Inhalation	Long-term local effects	1 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

	Workers	Inhalation	Acute local effects	2 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,73 mg/m ³
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	471 mg/m ³
2-Methyl-2,4-pentanediol	Workers	Inhalation	Long-term systemic effects	44,43 mg/m ³
	Workers	Inhalation	Long-term local effects	49 mg/m ³
	Workers	Inhalation	Acute local effects	98 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	7,83 mg/m ³
	Consumers	Inhalation	Long-term local effects	25 mg/m ³
	Consumers	Inhalation	Acute local effects	49 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	22,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,25 mg/kg bw/day
Diisopropanolamine	Workers	Inhalation	Long-term systemic effects	16 mg/m ³
	Workers	Skin contact	Long-term systemic effects	12,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,9 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	6,3 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,3 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Diethylene glycol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	20,9 mg/kg dry weight (d.w.)
	Soil	1,53 mg/kg dry weight (d.w.)
	Marine sediment	2,09 mg/kg dry weight (d.w.)
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

		weight (d.w.)
	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
2-Methyl-2,4-pentanediol	Fresh water	0,429 mg/l
	Freshwater - intermittent	4,29 mg/l
	Marine water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Fresh water sediment	1,59 mg/kg dry weight (d.w.)
	Marine sediment	0,159 mg/kg dry weight (d.w.)
	Soil	0,066 mg/kg dry weight (d.w.)
Diisopropanolamine	Fresh water	0,278 mg/l
	Freshwater - intermittent	2,777 mg/l
	Marine water	0,028 mg/l
	Sewage treatment plant	15000 mg/l
	Fresh water sediment	2,33 mg/kg dry weight (d.w.)
	Marine sediment	0,233 mg/kg dry weight (d.w.)
	Soil	0,303 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,4 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Skin and body protection	:	er. Wash hands before breaks and at the end of workday. Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	:	If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to DIN EN 137
Filter type	:	Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	Aerosol containing a dissolved gas
Propellant	:	Dimethyl ether
Colour	:	light yellow
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-24 °C
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	18,6 %(V) (20 °C)(3500,0 - 5000 hPa)
Lower explosion limit / Lower flammability limit	:	3,0 %(V) (20 °C)(3500,0 - 5000 hPa)
Flash point	:	Not applicable
Auto-ignition temperature	:	235 °C
Decomposition temperature	:	No data available
pH	:	6 - 8 (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Concentration: 100 %

Viscosity
Viscosity, kinematic : Not applicable

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : Not applicable

Density : ca. 0,965 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting
due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Diethylene glycol:

Acute oral toxicity : Acute toxicity estimate (Humans): 1.120 mg/kg
Method: Expert judgement

Phosphoric acid:

Acute oral toxicity : LD50 (Rat): 2.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

2-Methyl-2,4-pentanediol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 420

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Diisopropanolamine:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Diethylene glycol:

Species : Rabbit
Result : No skin irritation

Phosphoric acid:

Result : Corrosive after 3 minutes to 1 hour of exposure
Remarks : Based on national or regional regulation.

2-Methyl-2,4-pentanediol:

Result : Skin irritation
Remarks : Based on national or regional regulation.

Diisopropanolamine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-:

Result : Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Diethylene glycol:

Species : Rabbit
Result : No eye irritation

Phosphoric acid:

Species : Rabbit
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

2-Methyl-2,4-pentanediol:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Diisopropanolamine:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-:

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Diethylene glycol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : negative

2-Methyl-2,4-pentanediol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Diisopropanolamine:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

Diethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Phosphoric acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

2-Methyl-2,4-pentanediol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Diisopropanolamine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: Directive 67/548/EEC, Annex V, B.10.
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

Diethylene glycol:

Species : Rat
Application Route : Ingestion
Exposure time : 108 weeks
Result : negative

Diisopropanolamine:

Species : Rat
Application Route : Ingestion
Exposure time : 94 weeks
Result : negative

Reproductive toxicity

Suspected of damaging the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version 1.0 Revision Date: 13.09.2024 SDS Number: 11439142-00001 Date of last issue: -
Date of first issue: 13.09.2024

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Diethylene glycol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Phosphoric acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

2-Methyl-2,4-pentanediol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative

Effects on foetal development : Test Type: One-generation reproduction toxicity study

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

ment
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Diisopropanolamine:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47,11 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr

Diethylene glycol:

Species : Rat
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 98 Days

Species : Dog
NOAEL : 2.220 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Phosphoric acid:

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 40 - 52 Days
Method : OECD Test Guideline 422

2-Methyl-2,4-pentanediol:

Species : Rat
NOAEL : \geq 450 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

Diisopropanolamine:

Species : Rat, male
NOAEL : 100 mg/kg
LOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

Components:

2-Methyl-2,4-pentanediol:

Eye contact : Target Organs: Eyes
Symptoms: Irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

- Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l
Exposure time: 48 h
- Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

Diethylene glycol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 75.200 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h
Method: DIN 38412
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC: > 1 mg/l
Exposure time: 7 d
Species: Pimephales promelas (fathead minnow)
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on data from similar materials

Phosphoric acid:

- Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

2-Methyl-2,4-pentanediol:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 8.510 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Ceriodaphnia dubia (water flea)): 2.800 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Raphidocelis subcapitata (freshwater green alga)): >
plants 429 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Raphidocelis subcapitata (freshwater green alga)): >
429 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Bacteria): 200 mg/l
Exposure time: 10 d

Toxicity to daphnia and other : NOEC: 25 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Diisopropanolamine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1.466 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 277,7 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): 339 mg/l
plants Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 219 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Toxicity to microorganisms : EC10 : > 1.995 mg/l
Exposure time: 30 min
Method: ISO 8192

Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 5 - 10 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Diethylene glycol:

Biodegradability : Result: Readily biodegradable.

2-Methyl-2,4-pentanediol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Diisopropanolamine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 94 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Poly(oxy-1,2-ethanediyl), α -(carboxymethyl)- ω -[(9Z)-9-octadecen-1-yloxy]-:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-
octanol/water : log Pow: 0,2

Diethylene glycol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Partition coefficient: n-octanol/water : log Pow: -1,98
Remarks: Calculation

2-Methyl-2,4-pentanediol:

Partition coefficient: n-octanol/water : log Pow: < 4
Remarks: Calculation

Diisopropanolamine:

Partition coefficient: n-octanol/water : log Pow: -0,79

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or ex-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Waste Code : pose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

: The following Waste Codes are only suggestions:

used product
16 05 04*, gases in pressure containers (including halons) containing hazardous substances

unused product
16 05 04*, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings
15 01 10*, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

ADN

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
-----	--------------------	---------------------	---------------------

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 17,30 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity
Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national
regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version
are highlighted in the body of this document by two vertical
lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.
H290 : May be corrosive to metals.
H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H361d : Suspected of damaging the unborn child.
EUH071 : Corrosive to the respiratory tract.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Met. Corr.	:	Corrosive to metals
Press. Gas	:	Gases under pressure
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CUT+COOL CUTTING AND DRILLING FOAM - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	13.09.2024	11439142-00001	Date of first issue: 13.09.2024

- Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1	H222, H229
Eye Dam. 1	H318
Repr. 2	H361d

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN