

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BITUMEN SEALANT - 310 ML

Product code : 0890103100

Unique Formula Identifier (UFI) : 3AHG-K05J-800A-486X

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Sealant  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

#### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

	Index-No. Registration number		
Hydrocarbons, C9, aromatics	128601-23-0 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
Methanol	67-56-1 200-659-6 603-001-00-X 01-2119433307-44	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 (optic nerve, Central nervous system)  specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %  Acute toxicity esti- mate  Acute oral toxicity: 300 mg/kg Acute inhalation tox- icity (vapour): 3 mg/l Acute dermal toxicity: 300 mg/kg	>= 1 - < 3

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Remove contaminated clothing and shoes.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Silicon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Asphalt	8052-42-4	MAK (Sum of vapour and inhalable fraction)	1,5 mg/m <sup>3</sup> (bitumen condensate standard)	DE DFG MAK
Peak-limit: excursion factor (category): 2; II				
Further information: Substances that cause concern that they could be carcinogenic for man but cannot be assessed conclusively because of lack of data, Danger of absorption through the skin, Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C				
Hydrocarbons, C9, aromatics	128601-23-0	AGW	50 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Methanol	67-56-1	TWA	200 ppm 260 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	100 ppm 130 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Methanol	67-56-1	Methanol: 15 mg/l (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903
		Methanol: 15 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Methanol	Workers	Inhalation	Long-term systemic effects	130 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	130 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	130 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	130 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	20 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	20 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	26 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	26 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	26 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	26 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

	Consumers	Skin contact	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	4 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	4 mg/kg bw/day

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

#### Personal protective equipment

- Eye/face protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
- Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Equipment should conform to DIN EN 166
- Hand protection  
Material : Nitrile rubber
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 137



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Filter type : Self-contained breathing apparatus

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : black

Odour : hydrocarbon-like

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 55 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-  
octanol/water : Not applicable

Vapour pressure : No data available

Density : 1,25 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure :  
Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 (Rat, female): 3.492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

##### Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

##### Methanol:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Species : Rabbit  
Result : No eye irritation

##### Methanol:

Species : Rabbit  
Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

##### Methanol:

Test Type : Maximisation Test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C9, aromatics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC)  
1272/2008, Annex VI, Part 3, Note P)

#### Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: in vitro micronucleus test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C9, aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC)  
1272/2008, Annex VI, Part 3, Note P)

#### Methanol:

Species : Monkey  
Application Route : inhalation (vapour)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Exposure time : 7 Months  
Result : negative

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

##### Methanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Monkey  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Monkey  
Application Route: inhalation (vapour)  
Result: negative

### STOT - single exposure

Not classified based on available information.

#### Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

#### Components:

##### Hydrocarbons, C9, aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

##### Methanol:

Target Organs : optic nerve, Central nervous system  
Assessment : Causes damage to organs.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

#### Hydrocarbons, C9, aromatics:

Species	:	Rat, female
NOAEL	:	900 mg/m <sup>3</sup>
Application Route	:	inhalation (vapour)
Exposure time	:	12 Months
Remarks	:	Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

#### Product:

No aspiration toxicity classification

#### Components:

#### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3,2 mg/l Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 7,9 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 99 mg/l  
Exposure time: 10 min

### **Methanol:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15.400 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l  
Exposure time: 48 h  
Method: DIN 38412

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 22.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l  
Exposure time: 3 h  
Test substance: Neutralised product  
Method: OECD Test Guideline 209

## 12.2 Persistence and degradability

### Components:

#### **Hydrocarbons, C9, aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### **Methanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 95 %  
Exposure time: 20 d



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

### 12.3 Bioaccumulative potential

#### Components:

#### Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water : log Pow: 3,7 - 4,5

#### Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): < 10

Partition coefficient: n-octanol/water : log Pow: -0,77

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product  
08 04 09\*, waste adhesives and sealants containing organic solvents or other hazardous substances

unused product  
08 04 09\*, waste adhesives and sealants containing organic solvents or other hazardous substances

uncleaned packagings  
15 01 10\*, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	:	UN 1999
ADR	:	UN 1999
RID	:	UN 1999
IMDG	:	UN 1999
IATA	:	UN 1999

#### 14.2 UN proper shipping name

ADN	:	TARS, LIQUID
ADR	:	TARS, LIQUID
RID	:	TARS, LIQUID
IMDG	:	TARS, LIQUID
IATA	:	Tars, liquid

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	3
ADR	:	3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

---

**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

#### ADN

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Remarks : Complies with the chemical and physical criteria according to 2.2.3.1.5 ADN.

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : Complies with the chemical and physical criteria according to 2.2.3.1.5 ADR.

#### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Remarks : Complies with the chemical and physical criteria according to 2.2.3.1.5 RID.

#### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : Complies with the chemical and physical criteria according to 2.3.2.5 of the International Maritime Code for Dangerous Goods (IMDG Code).

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 69: Methanol

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High : Not applicable

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version 7.0      Revision Date: 25.10.2024      SDS Number: 6280484-00013      Date of last issue: 28.06.2024  
Date of first issue: 21.08.2020

---

Concern for Authorisation (Article 59).

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Class 1: 1,5 % Methanol  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:  
Not applicable  
5.2.7.1.1: Formaldehyde:  
Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

5.2.7.1.1: fibres:  
Not applicable  
5.2.7.1.2: Germ cell mutagens:  
Not applicable  
5.2.7.1.3: Substances toxic to reproduction:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic  
organic substances:  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial  
emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 144 g/l  
Remarks: VOC content excluding water

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version  
are highlighted in the body of this document by two vertical  
lines.

#### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H301 : Toxic if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H331 : Toxic if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H370 : Causes damage to organs.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
2006/15/EC : Europe. Indicative occupational exposure limit values  
DE DFG BAT : Germany. MAK BAT Annex XIII  
DE DFG MAK : Germany. MAK BAT Annex IIa  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : TRGS 903 - Biological limit values  
2006/15/EC / TWA : Limit Value - eight hours  
DE DFG MAK / MAK : MAK value

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Flam. Liq. 3 H226  
Aquatic Chronic 3 H412

### Classification procedure:

Based on product data or assessment  
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BITUMEN SEALANT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.06.2024
7.0	25.10.2024	6280484-00013	Date of first issue: 21.08.2020

---

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN