

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : WINDSCREEN ADHESIVE EXPERT - 310 ML

Product code : 0890023702

Unique Formula Identifier (UFI) : 1YR0-D0AU-P002-DR18

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives
Professional use product

Recommended restrictions on use : May only be used by trained personnel.

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)


SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Precautionary statements	:	Prevention: P261 Avoid breathing vapours. P284 Wear respiratory protection. Response: P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

4,4'-Diphenylmethane diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

|| Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract) specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 0,1 - < 1
Dibutyl hydrogen phosphate	107-66-4 203-509-8	Skin Corr. 1; H314 Eye Dam. 1; H318 Carc. 2; H351 EUH071	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Respiratory symptoms, including pulmonary edema, may be delayed.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray in large fire situations

- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specific hazards during fire-fighting | : | Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : | Carbon oxides
Metal oxides |

5.3 Advice for firefighters

- | | | |
|-----------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- | | | |
|----------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions | : | Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
|----------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------|

6.2 Environmental precautions

- | | | |
|---------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental precautions | : | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. |
|---------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

6.3 Methods and material for containment and cleaning up

- | | | |
|-------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods for cleaning up | : | Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding |
|-------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015



certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe vapours.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|-----------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------|
| Requirements for storage areas and containers | : | Keep in properly labelled containers. Protect from moisture.
Store in accordance with the particular national regulations. |
| Advice on common storage | : | Do not store with the following product types:
Strong oxidizing agents
Gases |
| Storage class (TRGS 510) | : | 10 |
| Recommended storage temperature | : | 0 - 35 °C |

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
4,4'-Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m ³	TRGS 430
		Peak-limit: excursion factor (category): 1;=2=(I)		
		Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance		
		AGW (Vapour and aerosols, inhalable fraction)	0,05 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 1;=2=(I)		
		Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system		
		MAK (inhalable fraction)	0,05 mg/m ³	DE DFG MAK
		Peak-limit: excursion factor (category): 1; I		
		Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
		Mow	0,1 mg/m ³	DE DFG MAK
		Peak-limit: excursion factor (category): 1; I		
		Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
		TWA (NCO)	0,01 mg/m ³	98/24/EC I
		Further information: Skin, Dermal and respiratory sensitisation, Binding		
		STEL (NCO)	0,02 mg/m ³	98/24/EC I
		Further information: Skin, Dermal and respiratory sensitisation, Binding		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Substance name	End Use	Exposure routes	Potential health effects	Value
Di-isononyl phthalate	Workers	Inhalation	Long-term systemic effects	51,72 mg/m ³
	Workers	Skin contact	Long-term systemic effects	366 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,3 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	220 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,4 mg/kg bw/day
	Carbon black	Workers	Inhalation	Long-term local effects
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local effects	0,05 mg/m ³
	Workers	Inhalation	Acute local effects	0,1 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,025 mg/m ³
	Consumers	Inhalation	Acute local effects	0,05 mg/m ³
Dibutyl hydrogen phosphate	Workers	Inhalation	Long-term systemic effects	1,25 mg/m ³
	Workers	Inhalation	Acute systemic effects	5 mg/m ³
	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Workers	Inhalation	Acute local effects	1 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,44 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	1,78 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,31 mg/m ³
	Consumers	Inhalation	Acute systemic effects	1,24 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,22 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0,88 mg/kg bw/day
Consumers	Ingestion	Long-term systemic effects	0,22 mg/kg bw/day	
	Ingestion	Acute systemic effects	0,88 mg/kg bw/day	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Di-isononyl phthalate	Soil	30 mg/kg
Carbon black	Fresh water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Marine water	0,1 mg/l
	Marine water - intermittent	1 mg/l
4,4'-Diphenylmethane diisocya-	Fresh water	1 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

nate		
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,12 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	paste
Colour	:	black
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	270 °C
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	164 °C
Auto-ignition temperature	:	> 300 °C
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, kinematic	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : No data available

Density : 1,19 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

|| Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.
|| Polymerises at high temperatures with evolution of carbon dioxide.

10.3 Possibility of hazardous reactions

|| Hazardous reactions : Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols
Reacts with water to form carbon dioxide and heat
Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea.
Hazardous decomposition products will be formed upon con-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

|| tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

|| Materials to avoid : Oxidizing agents
Acids
Bases
Water
Alcohols
Amines
Ammonia
Aluminium
Zinc
Brass
Tin
Copper
Galvanised metals
Humid air

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

|| Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute toxicity estimate: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Dibutyl hydrogen phosphate:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431
Result : Corrosive after 4 hours or less of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days
Remarks : Based on national or regional regulation.

Dibutyl hydrogen phosphate:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Components:

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation
Species : Rat
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on animal testing

Dibutyl hydrogen phosphate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Dibutyl hydrogen phosphate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Dibutyl hydrogen phosphate:

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative
Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Dibutyl hydrogen phosphate:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rat
NOAEL : 0,2 mg/m³
LOAEL : 1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 yr
Remarks : Based on data from similar materials

Dibutyl hydrogen phosphate:

Species : Rat
NOAEL : 30 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 40 - 50 Days
Method : OECD Test Guideline 422

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

4,4'-Diphenylmethane diisocyanate:

- Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 129,7 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
- EC10 (Desmodesmus subspicatus (green algae)): 76 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
- Toxicity to microorganisms : EC50 : > 10.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 66 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

4,4'-Diphenylmethane diisocyanate:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302
Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 12 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.

12.3 Bioaccumulative potential

Components:

4,4'-Diphenylmethane diisocyanate:

- Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
- Partition coefficient: n-octanol/water : log Pow: 4,51

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

Dibutyl hydrogen phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 7

Partition coefficient: n-octanol/water : log Pow: < 4

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

|| used product
08 04 09*, waste adhesives and sealants containing organic solvents or other hazardous substances
08 05 01, waste isocyanates

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015



unused product
08 04 09*, waste adhesives and sealants containing organic solvents or other hazardous substances
08 05 01, waste isocyanates

uncleaned packagings
15 01 10*, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : UN 3334

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Aviation regulated liquid, n.o.s.
(4,4'-Diphenylmethane diisocyanate)

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
Class Subsidiary risks
IATA : 9

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo aircraft) : 964

Packing instruction (LQ) : Y964

Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964

Packing instruction (LQ) : Y964

Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 52: Di-isononyl phthalate

Number on list 56: 4,4'-Diphenylmethane diisocyanate

Number on list 74: 4,4'-Diphenylmethane diisocyanate

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version 9.0 Revision Date: 25.10.2024 SDS Number: 10613115-00023 Date of last issue: 02.04.2024
Date of first issue: 09.11.2015

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Class 1: 1 % 4,4'-Diphenylmethane diisocyanate
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %, 0 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national
regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version
are highlighted in the body of this document by two vertical
lines.

Full text of H-Statements

H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H334 : May cause allergy or asthma symptoms or breathing difficul-
ties if inhaled.
H335 : May cause respiratory irritation.
H351 : Suspected of causing cancer.
H373 : May cause damage to organs through prolonged or repeated
exposure if inhaled.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Resp. Sens. : Respiratory sensitisation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
98/24/EC I	:	Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	:	Germany. TRGS 430 - Isocyanates
98/24/EC I / STEL	:	Limit values Short-term
98/24/EC I / TWA	:	Limit values 8 hours
DE DFG MAK / Mow	:	Momentary value
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average
TRGS 430 / AGW	:	Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Observe requirements and guidance related to training before using this product at work.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



WINDSCREEN ADHESIVE EXPERT - 310 ML

Version	Revision Date:	SDS Number:	Date of last issue: 02.04.2024
9.0	25.10.2024	10613115-00023	Date of first issue: 09.11.2015

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Resp. Sens. 1

H334

Classification procedure:

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN