

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : PURlogic EASY - 500 ML

Product code : 0892143

Unique Formula Identifier (UFI) : 5MD2-00K2-D002-P4UA

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Foams, Sealant  
Professional use product

Recommended restrictions on use : May only be used by trained personnel.

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878






## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

**Storage:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

P410 + P412    Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

Diphenylmethane diisocyanate, isomers and homologues  
4,4'-Diphenylmethane diisocyanate

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May displace oxygen and cause rapid suffocation.  
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethane diisocyanate, isomers and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract) <hr/> Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 1,5	>= 30 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

		mg/l	
Dimethyl ether	115-10-6 204-065-8 603-019-00-8	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 1 - < 10
Phosphorous oxychloride, reaction products with propylene oxide	1244733-77-4	Acute Tox. 4; H302 Aquatic Chronic 3; H412  Acute toxicity estimate  Acute oral toxicity: 500 mg/kg	>= 2,5 - < 10
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract)  specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %  Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 0,1 - < 1

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.
- Gas reduces oxygen available for breathing.  
Respiratory symptoms, including pulmonary edema, may be delayed.  
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray in large fire situations

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Chlorine compounds  
Oxides of phosphorus  
Nitrogen oxides (NO<sub>x</sub>)

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from water.  
Protect from moisture.  
Already sensitised individuals, and those susceptible

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Protect from moisture. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Storage class (TRGS 510) : 2B

Storage period : 12 Months

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Diphenylmethane	9016-87-9	MAK (inhalable)	0,05 mg/m <sup>3</sup>	DE DFG MAK



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

diisocyanate, isomers and homologues		fraction)		
	Peak-limit: excursion factor (category): 1; I			
	Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		Mow	0,1 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 1; I			
	Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable fraction)	0,05 mg/m3 (MDI)	DE TRGS 900
	Peak-limit: excursion factor (category): 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 2.400 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further information: Indicative			
		AGW	1.000 ppm 1.900 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 8;(II)			
		MAK	1.000 ppm 1.900 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category): 4;(II)				
		MAK	1.000 ppm 1.800 mg/m3	DE DFG MAK
Peak-limit: excursion factor (category): 4; II				
Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C				
4,4'-Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m3	TRGS 430
Peak-limit: excursion factor (category): 1;=2=(I)				
Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance				
		AGW (Vapour and aerosols, inhalable fraction)	0,05 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category): 1;=2=(I)				
Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system				
		MAK (inhalable fraction)	0,05 mg/m3	DE DFG MAK
Peak-limit: excursion factor (category): 1; I				
Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				
		Mow	0,1 mg/m3	DE DFG MAK
Peak-limit: excursion factor (category): 1; I				
Further information: Danger of sensitization of the airways and the skin, Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
Further information: Skin, Dermal and respiratory sensitisation, Binding				
		STEL	0,02 mg/m3 (NCO)	98/24/EC I
Further information: Skin, Dermal and respiratory sensitisation, Binding				

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

Substance name	End Use	Exposure routes	Potential health effects	Value
Poly(PO) Glycerine Ether	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	13,9 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	8,3 mg/kg bw/day
Polypropylene glycol	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	13,9 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	29 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg bw/day
Paraffin waxes and Hydrocarbon waxes, chloro	Consumers	Ingestion	Long-term systemic effects	8,3 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	65,5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term local effects	450 mg/kg bw/day
Dimethyl ether	Consumers	Skin contact	Long-term local effects	225 mg/kg bw/day
	Consumers	Ingestion	Long-term local effects	4,5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	1894 mg/m <sup>3</sup>
4,4'-Diphenylmethane diisocyanate	Consumers	Inhalation	Long-term systemic effects	471 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,05 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,1 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0,025 mg/m <sup>3</sup>
Phosphorous oxychloride, reaction products with propylene oxide	Consumers	Inhalation	Acute local effects	0,05 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	8,2 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	22,6 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2,91 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,45 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	5,6 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1,04 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,52 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
--	-----------	-----------	------------------------	----------------

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Poly(PO) Glycerine Ether	Fresh water	0,2 mg/l
	Marine water	0,02 mg/l
	Intermittent use/release	1 mg/l
	Sewage treatment plant	1000 mg/l
	Fresh water sediment	0,52 mg/kg
	Marine sediment	0,052 mg/kg
Polypropylene glycol	Fresh water	0,2 mg/l
	Freshwater - intermittent	1,06 mg/l
	Marine water	0,02 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	0,419 mg/kg dry weight (d.w.)
Paraffin waxes and Hydrocarbon waxes, chloro	Marine sediment	0,042 mg/kg dry weight (d.w.)
	Soil	0,031 mg/kg dry weight (d.w.)
	Fresh water	0,0029 mg/l
	Marine water	0,00058 mg/l
	Intermittent use/release	0,0029 mg/l
Dimethyl ether	Sewage treatment plant	60 mg/l
	Fresh water sediment	5710 mg/kg
	Soil	4640 mg/kg
	Oral (Secondary Poisoning)	10 mg/kg food
	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
4,4'-Diphenylmethane diisocyanate	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
Phosphorous oxychloride, reaction products with propylene oxide	Fresh water	1 mg/l
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
Phosphorous oxychloride, reaction products with propylene oxide	Soil	1 mg/kg
	Fresh water	0,32 mg/l
	Freshwater - intermittent	0,51 mg/l
	Marine water	0,032 mg/l
	Sewage treatment plant	19,1 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

	Fresh water sediment	11,5 mg/kg dry weight (d.w.)
	Marine sediment	1,15 mg/kg dry weight (d.w.)
	Soil	0,34 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	11,6 mg/kg food

### 8.2 Exposure controls

#### Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles  
Equipment should conform to DIN EN 166

Hand protection  
Material : Polyethylene  
Break through time : > 30 min  
Glove thickness : 0,025 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Isobutane, Propane, Butane, Dimethyl ether

Colour : coloured

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : -21 °C

Auto-ignition temperature : 199 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : Not applicable

Relative density : No data available

Relative vapour density : Not applicable

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Heating may cause an explosion.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Polymerises at high temperatures with evolution of carbon dioxide.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Exothermic reaction with acids, amines and alcohols  
Reacts with water to form carbon dioxide and heat  
Isocyanates are not soluble in water and sink to the bottom,  
but react slowly at the interface. The reaction forms carbon  
dioxide gas and a layer of solid polyurea.  
If the temperature rises there is danger of the vessels bursting  
due to the high vapor pressure.  
Hazardous decomposition products will be formed upon con-  
tact with water or humid air.

### 10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture  
Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents  
Acids  
Bases  
Water  
Alcohols  
Amines  
Ammonia  
Aluminium  
Zinc  
Brass  
Tin  
Copper  
Galvanised metals  
Humid air

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Harmful if inhaled.

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 3,33 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

Method: Calculation method

### Components:

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

#### **Dimethyl ether:**

Acute inhalation toxicity : LC50 (Rat): 164000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

#### **Phosphorous oxychloride, reaction products with propylene oxide:**

Acute oral toxicity : LD50 (Rat): 500 - 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

#### **4,4'-Diphenylmethane diisocyanate:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute toxicity estimate: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Remarks: Based on data from similar materials

### Skin corrosion/irritation

Causes skin irritation.

#### Components:

##### Diphenylmethane diisocyanate, isomers and homologues:

Species : Rabbit  
Result : Skin irritation

##### Phosphorous oxychloride, reaction products with propylene oxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### 4,4'-Diphenylmethane diisocyanate:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

##### Diphenylmethane diisocyanate, isomers and homologues:

Result : Irritation to eyes, reversing within 21 days

##### Phosphorous oxychloride, reaction products with propylene oxide:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

##### 4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days  
Remarks : Based on national or regional regulation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Components:

##### Diphenylmethane diisocyanate, isomers and homologues:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : inhalation (dust/mist/fume)  
Species : Rat  
Result : positive

Assessment : Probability of respiratory sensitisation in humans based on animal testing

### **Phosphorous oxychloride, reaction products with propylene oxide:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

### **4,4'-Diphenylmethane diisocyanate:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation  
Species : Rat  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on animal testing

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

Method: OECD Test Guideline 474  
Result: negative

### Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)  
Application Route: inhalation (gas)  
Result: negative

### Phosphorous oxychloride, reaction products with propylene oxide:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Method: OECD Test Guideline 482  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### 4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 474  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

### **Carcinogenicity**

Suspected of causing cancer.

### **Components:**

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

#### **Dimethyl ether:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative

#### **4,4'-Diphenylmethane diisocyanate:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Result: negative

#### **Dimethyl ether:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Result: negative

### Phosphorous oxychloride, reaction products with propylene oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rabbit  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### 4,4'-Diphenylmethane diisocyanate:

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Result: negative  
Remarks: Based on data from similar materials

### STOT - single exposure

May cause respiratory irritation.

#### Components:

### Diphenylmethane diisocyanate, isomers and homologues:

Assessment : May cause respiratory irritation.

### Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

### 4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Components:

### Diphenylmethane diisocyanate, isomers and homologues:

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

### Phosphorous oxychloride, reaction products with propylene oxide:

Assessment : No significant health effects observed in animals at concentra-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

tions of 100 mg/kg bw or less.

### **4,4'-Diphenylmethane diisocyanate:**

Exposure routes : inhalation (dust/mist/fume)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

### **Repeated dose toxicity**

#### **Components:**

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rat  
NOAEL : 1.4 mg/m<sup>3</sup>  
LOAEL : 4.1 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 13 Weeks

#### **Dimethyl ether:**

Species : Rat  
NOAEL : 47,11 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr

#### **Phosphorous oxychloride, reaction products with propylene oxide:**

Species : Rat  
NOAEL : 52 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

### **4,4'-Diphenylmethane diisocyanate:**

Species : Rat  
NOAEL : 0,2 mg/m<sup>3</sup>  
LOAEL : 1 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 yr  
Remarks : Based on data from similar materials

### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at  
levels of 0.1% or higher.

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Diphenylmethane diisocyanate, isomers and homologues:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1.000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 : > 1.000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
plants Exposure time: 72 h

EC10 : 1.640 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other : NOEC: > 10 mg/l  
aquatic invertebrates (Chron- Exposure time: 21 d  
ic toxicity) Species: Daphnia magna (Water flea)

##### **Dimethyl ether:**

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

##### **Phosphorous oxychloride, reaction products with propylene oxide:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 51 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 131 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 82  
plants mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 42 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Toxicity to microorganisms : EC50 : 784 mg/l  
Exposure time: 3 h  
Method: ISO 8192

Toxicity to daphnia and other : NOEC: 32 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### 4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 129,7 mg/l  
aquatic invertebrates Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): > 1.640  
plants mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC: 10 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

## 12.2 Persistence and degradability

### Components:

#### **Diphenylmethane diisocyanate, isomers and homologues:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d

#### **Dimethyl ether:**

Biodegradability : Result: Not readily biodegradable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### Phosphorous oxychloride, reaction products with propylene oxide:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 14 %  
Exposure time: 28 d  
Method: Directive 67/548/EEC Annex V, C.4.D.

### 4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302  
Remarks: Based on data from similar materials

## 12.3 Bioaccumulative potential

### Components:

#### Dimethyl ether:

Partition coefficient: n-  
octanol/water : log Pow: 0,2

### Phosphorous oxychloride, reaction products with propylene oxide:

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 0,8 - 14

Partition coefficient: n-  
octanol/water : log Pow: 2,68

### 4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 200

Partition coefficient: n-  
octanol/water : log Pow: 4,51

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)
Waste Code	: The following Waste Codes are only suggestions:  used product 08 04 09*, waste adhesives and sealants containing organic solvents or other hazardous substances 16 05 04, gases in pressure containers (including halons) containing hazardous substances 08 05 01, waste isocyanates  unused product 08 04 09*, waste adhesives and sealants containing organic solvents or other hazardous substances 16 05 04, gases in pressure containers (including halons) containing hazardous substances 08 05 01, waste isocyanates  uncleaned packagings 08 05 01*, waste isocyanates

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

### II

---

#### SECTION 14: Transport information

##### 14.1 UN number or ID number

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

##### 14.2 UN proper shipping name

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

##### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.1
<b>ADR</b>	: 2	2.1
<b>RID</b>	: 2	2.1
<b>IMDG</b>	: 2.1	
<b>IATA</b>	: 2.1	

##### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 56: 4,4'-Diphenylmethane diisocyanate, Diphenylmethane diisocyanate, isomers and homologues  Number on list 74: 4,4'-Diphenylmethane diisocyanate, Diphenylmethane diisocyanate, isomers and homologues
--	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

	Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS 150 t	500 t

Water hazard class (Germany) : WGK 1 slightly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Class 1: 1 % 4,4'-Diphenylmethane diisocyanate  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

Not applicable  
5.2.7.1.1: Formaldehyde:  
Not applicable  
5.2.7.1.1: fibres:  
Not applicable  
5.2.7.1.2: Germ cell mutagens:  
Not applicable  
5.2.7.1.3: Substances toxic to reproduction:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic  
organic substances:  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 20,6 %, 200 g/l  
Remarks: VOC content excluding water

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Contains a substance which is subject to the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances. : Diphenylmethane diisocyanate, isomers and homologues  
carcinogenic: category 2 according to Annex I of the CLP Directive  
mutagenic: based on the available data no classification in the categories of Annex I of the CLP Directive could be made  
Harmful for fertility: based on the available data no classification in the categories of Annex I of the CLP Directive could be made  
Harmful for development: based on the available data no classification in the categories of Annex I of the CLP Directive could be made

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version 14.0      Revision Date: 06.11.2024      SDS Number: 10622303-00013      Date of last issue: 26.06.2024  
Date of first issue: 03.03.2015

---

### Full text of H-Statements

H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.  
H302 : Harmful if swallowed.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H351 : Suspected of causing cancer.  
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.  
  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Gas : Flammable gases  
Press. Gas : Gases under pressure  
Resp. Sens. : Respiratory sensitisation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values  
  
DE DFG MAK : Germany. MAK BAT Annex IIa  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 430 : Germany. TRGS 430 - Isocyanates  
2000/39/EC / TWA : Limit Value - eight hours  
98/24/EC I / STEL : Limit values Short-term  
98/24/EC I / TWA : Limit values 8 hours  
DE DFG MAK / Mow : Momentary value  
DE DFG MAK / MAK : MAK value  
DE TRGS 900 / AGW : Time Weighted Average  
TRGS 430 / AGW : Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Observe requirements and guidance related to training before using this product at work.

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## PURlogic EASY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.06.2024
14.0	06.11.2024	10622303-00013	Date of first issue: 03.03.2015

---

safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN