

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**Section 1: Identification**

Product name : MAINTENANCE SPRAY 150ML  
Product code : 0893 051

**Manufacturer or supplier's details**

Company : Wurth NewZealand Ltd  
Address : 99 McLauglins Road  
Wiri, Auckland 2104  
Telephone : +64 9 262 3040  
Emergency telephone number : 0800 764 766  
E-mail address : prodsafe@wuerth.com  
Telefax : +64 9 262 3030

**Recommended use of the chemical and restrictions on use**

Recommended use : Corrosion inhibitor  
Restrictions on use : Not applicable

---

**Section 2: Hazard identification****GHS Classification**

Aerosols : Category 1  
Skin corrosion/irritation : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity - single exposure : Category 3  
Hazardous to the aquatic environment - chronic hazard : Category 3

**GHS label elements**

Hazard pictograms :   

Signal word : Danger

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

Hazard statements : H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H361f Suspected of damaging fertility.  
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.

**Storage:**  
 P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

---

**Section 3: Composition/information on ingredients**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Isobutane	75-28-5	>= 20 -< 30

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
 Date of first issue: 05.09.2017

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 10 -< 20
Propane	74-98-6	>= 1 -< 10
Butane	106-97-8	>= 1 -< 10
n-Hexane	110-54-3	>= 0.25 -< 1
2,6-Di-tert-butyl-4-nonylphenol	4306-88-1	>= 0.1 -< 0.25

**Section 4: First-aid measures**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention.  
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
 May cause drowsiness or dizziness.  
 Suspected of damaging fertility.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

**Section 5: Fire-fighting measures**

- Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Flash back possible over considerable distance.  
 Vapours may form explosive mixtures with air.  
 Exposure to combustion products may be a hazard to health.  
 If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion prod- : Carbon oxides

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

ucts

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**Section 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**Section 7: Handling and storage**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

- only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Do not spray on an open flame or other ignition source.  
If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Explosives
- Recommended storage temperature : 10 - 30 °C

**Section 8: Exposure controls/personal protection**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	WES-TWA (Mist)	5 mg/m <sup>3</sup>	NZ OEL
		WES-STEL (Mist)	10 mg/m <sup>3</sup>	NZ OEL

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
 Date of first issue: 05.09.2017

		WES-TWA	300 ppm 890 mg/m <sup>3</sup>	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m <sup>3</sup>	NZ OEL
		TWA	200 ppm	ACGIH
Butane	106-97-8	WES-TWA	800 ppm 1,900 mg/m <sup>3</sup>	NZ OEL
		STEL	1,000 ppm	ACGIH
n-Hexane	110-54-3	WES-TWA	20 ppm 72 mg/m <sup>3</sup>	NZ OEL
Further information: Ototoxin, Exposure can also be estimated by biological monitoring				
		TWA	50 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
n-Hexane	110-54-3	2,5-hexanedi-one	Urine	End of shift	5 mg/l	NZ BEI
		2,5-Hexanedi-one	Urine	End of shift	0.5 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber

Break through time : < 480 min

Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

---

**Section 9: Physical and chemical properties**

Appearance	:	aerosol
Propellant	:	Isobutane, Propane, Butane
Colour	:	red brown
Odour	:	bitter almond
Odour Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	-12 °C  Flash point is only valid for liquid portion in the aerosol can.
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	11 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	0.83 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

**Section 10: Stability and reactivity**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**Section 11: Toxicological information**

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Isobutane:**

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l  
Exposure time: 4 h

---



## MAINTENANCE SPRAY 150ML

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

**n-Hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**2,6-Di-tert-butyl-4-nonylphenol:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

## MAINTENANCE SPRAY 150ML

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

**n-Hexane:**

Species	:	Rabbit
Result	:	Skin irritation
Remarks	:	Based on data from similar materials

**2,6-Di-tert-butyl-4-nonylphenol:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Mild skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species	:	Rabbit
Result	:	No eye irritation

**n-Hexane:**

Result	:	Irritation to eyes, reversing within 21 days
Remarks	:	Based on national or regional regulation.

**2,6-Di-tert-butyl-4-nonylphenol:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**n-Hexane:**

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Result	:	negative

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**2,6-Di-tert-butyl-4-nonylphenol:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Isobutane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OPPTS 870.5395  
Result: negative

**Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat

## MAINTENANCE SPRAY 150ML

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**n-Hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**2,6-Di-tert-butyl-4-nonylphenol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: in vitro micronucleus test  
Method: OECD Test Guideline 487  
Result: negative

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**n-Hexane:**

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Suspected of damaging fertility.

**Components:****Isobutane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapour)  
Result: positive

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**2,6-Di-tert-butyl-4-nonylphenol:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

## MAINTENANCE SPRAY 150ML

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Isobutane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Propane:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**n-Hexane:**

Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Components:****n-Hexane:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

Remarks : Based on national or regional regulation.

**2,6-Di-tert-butyl-4-nonylphenol:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Repeated dose toxicity****Components:****Isobutane:**

Species : Rat  
NOAEL : 9000 ppm

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**n-Hexane:**

Species : Mouse  
LOAEL : 1.76 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3,973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**2,6-Di-tert-butyl-4-nonylphenol:**

Species : Rat  
LOAEL : 100 mg/kg  
Application Route : Ingestion  
Exposure time : 63 Days  
Method : OECD Test Guideline 422

**Aspiration toxicity**

Not classified based on available information.



**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Components:****n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

**Section 12: Ecological information****Ecotoxicity****Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron- : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d

---

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

ic toxicity) Method: OECD Test Guideline 211

**n-Hexane:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 3.88 mg/l  
aquatic invertebrates Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
plants Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**2,6-Di-tert-butyl-4-nonylphenol:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.124 mg/l  
aquatic invertebrates Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): >  
plants 0.007 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): > 0.007 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1  
icity)

M-Factor (Chronic aquatic : 1  
toxicity)

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**MAINTENANCE SPRAY 150ML**

Version 6.1      Revision Date: 14.11.2024      SDS Number: 10782036-00015      Date of last issue: 24.06.2024  
Date of first issue: 05.09.2017

---

**Persistence and degradability****Components:****Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**n-Hexane:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**2,6-Di-tert-butyl-4-nonylphenol:**

Biodegradability : Result: Not inherently biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302C

**Bioaccumulative potential****Components:****Isobutane:**

Partition coefficient: n- : log Pow: 2.8  
octanol/water

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: 4

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

octanol/water

Remarks: Based on data from similar materials

**Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

**n-Hexane:**

Partition coefficient: n-octanol/water : log Pow: 4

**2,6-Di-tert-butyl-4-nonylphenol:**

Partition coefficient: n-octanol/water : log Pow: &gt; 6.5

**Mobility in soil**

No data available

**Other adverse effects**No data available

---

**Section 13: Disposal considerations****Disposal methods**

Waste from residues	:	Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**Section 14: Transport information****International Regulations****UNRTDG**

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
Environmentally hazardous	:	no

**IATA-DGR**

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****NZS 5433**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**Section 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002515 Aerosols Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

**HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

**The components of this product are reported in the following inventories:**

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

NZIoC : All ingredients listed or exempt.

---

**Section 16: Other information**

Revision Date : 14.11.2024

**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
 NZ BEI : New Zealand. Biological Exposure Indices  
 NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average  
 ACGIH / STEL : Short-term exposure limit  
 NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
 NZ OEL / WES-STEEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Sub-

**MAINTENANCE SPRAY 150ML**

Version	Revision Date:	SDS Number:	Date of last issue: 24.06.2024
6.1	14.11.2024	10782036-00015	Date of first issue: 05.09.2017

---

stances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN