

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EPOXY-STICK METAL - 120 G

Product code : 0893449011

Unique Formula Identifier (UFI) : RX51-T0JS-W00T-8910

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

Category 3

Effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

**Response:**

P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

#### Hazardous components which must be listed on the label:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ )  
Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide

#### Additional Labelling

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	25068-38-6 500-033-5 603-074-00-8	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Eye Irrit. 2; H319 $\geq$ 5 % Skin Irrit. 2; H315 $\geq$ 5 %	$\geq$ 10 - < 20
Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide	72244-98-5 01-2120118957-46	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	$\geq$ 10 - < 20
2,4,6-Tris((Dimethylamino)methyl)phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 EUH071  Acute toxicity estimate  Acute oral toxicity: 1.653 mg/kg	$\geq$ 1 - < 3

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Metal oxides  
Sulphur oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing dust, fume, gas, mist, vapours or spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents
- Storage class (TRGS 510) : 11

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Aluminium powder (pyrophoric)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (measured as the alveolate fraction)	0,3 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Aluminium powder (pyrophoric)	7429-90-5	Aluminium: 50 µg/g creatinine (Urine)	In case of long-term exposure: after more than one shift	TRGS 903
		Aluminium: 50 µg/g creatinine (Urine)	end of shift, for long-term exposures after several previous shifts	DE DFG BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Workers	Inhalation	Long-term systemic effects	12,25 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	12,25 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	8,33 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

	Workers	Skin contact	Acute systemic effects	8,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	3,571 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	3,571 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,75 mg/kg bw/day
Aluminium powder (pyrophoric)	Workers	Inhalation	Long-term local effects	3,72 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3,95 mg/m <sup>3</sup> 3,95 mg/kg bw/day
Carbon black	Workers	Inhalation	Long-term local effects	0,5 mg/m <sup>3</sup>
Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide	Workers	Inhalation	Long-term systemic effects	22 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6,52 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1,61 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,9 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	Fresh water	0,006 mg/l
	Freshwater - intermittent	0,018 mg/l
	Marine water	0,001 mg/l
	Marine water - intermittent	0,002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,996 mg/kg dry weight (d.w.)
	Marine sediment	0,1 mg/kg dry weight (d.w.)
	Soil	0,196 mg/kg dry weight (d.w.)
	Secondary Poisoning	11 mg/kg food
Aluminium powder (pyrophoric)	Sewage treatment plant	20 mg/l
2,4,6-Tris{(Dimethylamino)methyl}phen	Fresh water	0,084 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

ol		
	Marine water	0,0084 mg/l
	Sewage treatment plant	0,2 mg/l
	Intermittent use/release	0,84 mg/l
Carbon black	Fresh water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Marine water	0,1 mg/l
	Marine water - intermittent	1 mg/l
Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide	Fresh water	0,07 mg/l
	Marine water	0,007 mg/l
	Intermittent use/release	0,120 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,322 mg/kg dry weight (d.w.)
	Marine sediment	0,032 mg/kg dry weight (d.w.)
	Soil	0,023 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles  
Equipment should conform to DIN EN 166

#### Hand protection

Material : PVC  
Break through time : > 480 min  
Glove thickness : > 0,5 mm  
Directive : DIN EN 374

Material : Polyethylene  
Break through time : > 480 min  
Glove thickness : > 0,5 mm  
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	Pasty solid
Colour	:	grey
Odour	:	aromatic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Flash point	:	> 100 °C
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)  
Water solubility : practically insoluble

Partition coefficient: n-  
octanol/water : Not applicable

Vapour pressure : Not applicable

Density : 2,5 g/cm<sup>3</sup> (23 °C)

Relative vapour density : Not applicable

Particle characteristics  
Particle size : No data available

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Self-ignition : The substance or mixture is not classified as pyrophoric.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

#### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:

Acute oral toxicity : LD50 (Rat): 2.600 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Acute inhalation toxicity : LC50 (Rat): > 0,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

Acute oral toxicity : LD50 (Rat): 1.653 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Components:**

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Result : Skin irritation  
Remarks : Based on national or regional regulation.

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Corrosive after 1 to 4 hours of exposure

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Components:**

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on national or regional regulation.

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Species : Rabbit  
Result : No eye irritation

### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Species : Rabbit  
Result : Irreversible effects on the eye

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

#### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

#### **Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

#### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : equivocal

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

#### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

---

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Genotoxicity in vitro      :    Test Type: Bacterial reverse mutation assay (AMES)  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo      :    Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Genotoxicity in vitro      :    Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

**2,4,6-Tris((Dimethylamino)methyl)phenol:**

Genotoxicity in vitro      :    Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Species      :    Rat  
Application Route      :    Ingestion  
Exposure time      :    24 Months  
Method      :    OECD Test Guideline 453  
Result      :    negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	24 Months
Method	:	OECD Test Guideline 453
Result	:	negative

### Reproductive toxicity

Not classified based on available information.

#### Components:

#### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative
----------------------	---	--

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rabbit Application Route: Skin contact Result: negative
-------------------------------	---	--

#### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
----------------------	---	---

Effects on foetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
-------------------------------	---	---

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

#### Components:

#### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):**

Assessment	:	No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.
------------	---	--



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

### Repeated dose toxicity

#### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Species	:	Rat
NOAEL	:	50 mg/kg
LOAEL	:	250 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	OECD Test Guideline 408

Species	:	Mouse
NOAEL	:	$\geq 100$ mg/kg
Application Route	:	Skin contact
Exposure time	:	13 Weeks
Method	:	OECD Test Guideline 411

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Species	:	Rat
NOAEL	:	75 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	OECD Test Guideline 408

**2,4,6-Tris((Dimethylamino)methyl)phenol:**

Species	:	Rat
NOAEL	:	15 mg/kg
Application Route	:	Ingestion
Exposure time	:	43 Days
Method	:	OECD Test Guideline 422

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials
- NOELR (Scenedesmus capricornutum (fresh water algae)): > 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : IC50 : > 100 mg/l  
Exposure time: 3 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0,1 - 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Remarks: Based on data from similar materials

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 87 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 12 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 733 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version 13.2      Revision Date: 16.01.2025      SDS Number: 10707232-00016      Date of last issue: 14.11.2024  
Date of first issue: 11.06.2010

---

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 338 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3,5 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 84 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 6,25 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : 2 mg/l  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

## 12.2 Persistence and degradability

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### **2,4,6-Tris((Dimethylamino)methyl)phenol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Partition coefficient: n- : log Pow: 3,5  
octanol/water

**2,4,6-Tris((Dimethylamino)methyl)phenol:**

Partition coefficient: n- : log Pow: 0,219  
octanol/water

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product  
08 04 09\*, waste adhesives and sealants containing organic solvents or other hazardous substances

unused product  
08 04 09\*, waste adhesives and sealants containing organic solvents or other hazardous substances

uncleaned packagings  
15 01 10\*, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

---

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Not applicable  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:  
Not applicable  
5.2.7.1.1: Formaldehyde:  
Not applicable  
5.2.7.1.1: fibres:  
Not applicable  
5.2.7.1.2: Germ cell mutagens:  
Not applicable  
5.2.7.1.3: Substances toxic to reproduction:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0 %, 0 g/l

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
DE DFG BAT : Germany. MAK BAT Annex XIII  
DE DFG MAK : Germany. MAK BAT Annex IIa  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : TRGS 903 - Biological limit values  
DE DFG MAK / MAK : MAK value  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## EPOXY-STICK METAL - 120 G

Version	Revision Date:	SDS Number:	Date of last issue: 14.11.2024
13.2	16.01.2025	10707232-00016	Date of first issue: 11.06.2010

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 3	H412

### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN