

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SILICONE SPRAY - 500 ML

Product code : 0893221

Unique Formula Identifier (UFI) : ADPC-K06R-100W-YF4K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Professional use product
Preservative, Lubricant

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Additional Labelling

EUH208 Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May displace oxygen and cause rapid suffocation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0 01-2119475515-33	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 10 - < 20$
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0 01-2119484651-34	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 2,5 - < 10$
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 EUH066	$\geq 1 - < 2,5$
Propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	$\geq 1 - < 10$
(R)-p-mentha-1,8-diene	5989-27-5 227-813-5 601-096-00-2 01-2119529223-47	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1B; H317 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 <hr/> M-Factor (Acute aquatic toxicity): 1	$\geq 0,1 - < 0,25$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Gas reduces oxygen available for breathing.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting
due to the high vapor pressure.

Hazardous combustion prod- : Carbon oxides
ucts : Silicon oxides

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters : Use personal protective equipment.

Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-
ods : cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do
so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal pro-
tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil
barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages
cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water
spray jet.
For large spills, provide dyking or other appropriate contain-
ment to keep material from spreading. If dyked material can
be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absor-
bent.
Local or national regulations may apply to releases and dis-
posal of this material, as well as those materials and items

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use with local exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|---|
| Requirements for storage areas and containers | : | Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Explosives
Gases

Storage class (TRGS 510) : 2B

Recommended storage temperature : < 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900	
		Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 2.400 mg/m ³	DE DFG MAK	
Peak-limit: excursion factor (category): 4; II					
Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C					
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900	
		Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 1.800 mg/m ³	DE DFG MAK	
Peak-limit: excursion factor (category): 4; II					
Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C					
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	500 ppm 2.085 mg/m ³	2000/39/EC	
		Further information: Indicative			
		AGW	500 ppm 2.100 mg/m ³	DE TRGS 900	
Peak-limit: excursion factor (category): 1;(I)					
Further information: Indicative					
Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C					
Hydrocarbons, C6,	64742-49-0	AGW	700 mg/m ³	DE TRGS	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

isoalkanes, <5% n-hexane				900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
		MAK	500 ppm 1.800 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	AGW	300 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
		MAK	50 ppm 300 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	200 ppm 500 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 2; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
(R)-p-mentha-1,8-diene	5989-27-5	AGW	5 ppm 28 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			
		MAK	5 ppm 28 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Danger of sensitization of the skin, Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	heptan-2,5-dione: 250 µg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		2,5-heptandione:	Immediately after	DE DFG

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

		250 µg/l (Urine)	exposition or after working hours	BAT
Propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l (Blood)	Immediately after exposition or after working hours	DE DFG BAT
		Acetone: 25 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m ³
	Workers	Skin contact	Long-term systemic effects	888 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	89 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	319 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg bw/day
(R)-p-mentha-1,8-diene	Workers	Inhalation	Long-term systemic effects	66,7 mg/m ³
	Workers	Skin contact	Acute local effects	9,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	16,6 mg/m ³
	Consumers	Skin contact	Acute local effects	4,8 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,8 mg/kg bw/day
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	5306 mg/m ³
	Workers	Skin contact	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1377 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1301 mg/kg bw/day
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2085 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

	Workers	Skin contact	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	447 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	149 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	149 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Propan-2-ol	Fresh water	140,9 mg/l
	Marine water	140,9 mg/l
	Intermittent use/release	140,9 mg/l
	Sewage treatment plant	2251 mg/l
	Fresh water sediment	552 mg/kg dry weight (d.w.)
	Marine sediment	552 mg/kg dry weight (d.w.)
	Soil	28 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	160 mg/kg food
(R)-p-mentha-1,8-diene	Fresh water	0,014 mg/l
	Marine water	0,0014 mg/l
	Sewage treatment plant	1,8 mg/l
	Fresh water sediment	3,85 mg/kg dry weight (d.w.)
	Marine sediment	0,385 mg/kg dry weight (d.w.)
	Soil	0,763 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	133 mg/kg food

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
Use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,35 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous sub-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

stance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Propane, Butane

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : -42 - 165 °C

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 12,0 %(V)

Lower explosion limit / Lower : 0,8 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

flammability limit

Flash point : 3,5 °C(1.013,25 hPa)
Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : 287 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : 1 mPa.s (20 °C)

Viscosity, kinematic : 1 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : 8.530 hPa (20 °C)

Density : 0,757 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.800 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): 16.750 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 259,354 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3.350 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

(R)-p-mentha-1,8-diene:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Propan-2-ol:

Species : Rabbit
Result : No skin irritation

(R)-p-mentha-1,8-diene:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Propan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

(R)-p-mentha-1,8-diene:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Propan-2-ol:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Result : negative

(R)-p-mentha-1,8-diene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

(R)-p-mentha-1,8-diene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Species : Mouse
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

(R)-p-mentha-1,8-diene:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

ment
Species: Rat
Application Route: Ingestion
Result: negative

(R)-p-mentha-1,8-diene:

Effects on foetal develop-
ment : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

(R)-p-mentha-1,8-diene:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rat
NOAEL : 12,47 mg/l
Application Route : Inhalation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

Exposure time : 90 Days
Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat, male
NOAEL : 10,504 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
NOAEL : 10.186 mg/m3
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Propan-2-ol:

Species : Rat
NOAEL : 12,5 mg/l
Application Route : inhalation (vapour)
Exposure time : 104 Weeks

(R)-p-mentha-1,8-diene:

Species : Rat, male
NOAEL : 5 mg/kg
LOAEL : 30 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

(R)-p-mentha-1,8-diene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,17 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
aquatic invertebrates
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100
plants
mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOELR: > 0,1 - 1 mg/l
aquatic invertebrates (Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l
aquatic invertebrates
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000
plants
mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1.050 mg/l
Exposure time: 16 h

(R)-p-mentha-1,8-diene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0,720 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 307 µg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0,25 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 0,14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : EC10: 0,37 mg/l
Exposure time: 8 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic) : EC10: 0,153 mg/l
Exposure time: 21 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version 14.1 Revision Date: 04.02.2025 SDS Number: 10633744-00019 Date of last issue: 26.11.2024
Date of first issue: 01.03.2012

ic toxicity) Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Propan-2-ol:

Biodegradability : Result: rapidly degradable
BOD/COD : BOD: 1,19 (BOD5)
COD: 2,23
BOD/COD: 53 %

(R)-p-mentha-1,8-diene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71,4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n- : log Pow: > 4
octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n- : log Pow: 3,6

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

octanol/water

Propan-2-ol:

Partition coefficient: n-
octanol/water : log Pow: 0,05

(R)-p-mentha-1,8-diene:

Partition coefficient: n-
octanol/water : log Pow: 4,38

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty
(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

unused product
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

uncleaned packagings
15 01 10*, packaging containing residues of or contaminated
by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 1950
ADR	: UN 1950
RID	: UN 1950
IMDG	: UN 1950
IATA	: UN 1950

14.2 UN proper shipping name

ADN	: AEROSOLS
ADR	: AEROSOLS
RID	: AEROSOLS
IMDG	: AEROSOLS
IATA	: Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

ADN

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas,	2.500 t	25.000 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

(b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 93,13 %, 566,74 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

DE DFG BAT : Germany. MAK BAT Annex XIII
DE DFG MAK : Germany. MAK BAT Annex IIa
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903 : TRGS 903 - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
DE DFG MAK / MAK : MAK value
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



SILICONE SPRAY - 500 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.11.2024
14.1	04.02.2025	10633744-00019	Date of first issue: 01.03.2012

sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN